

DESCRIPTION


- Low Distortion at Low Supply Voltage.
IM₂- 55 dB TYP., IM₃- 76 dB TYP.
@V_{CE} = 5 V, I_C = 50 mA, V_O = 105dB μ /75 Ω
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Designed for low distortion ,low noise RF amplifier operating with low supply voltage (V_{CE} = 5V).

ABSOLUTE MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{CBO}	Collector-Base Voltage	25	V
V _{CEO}	Collector-Emitter Voltage	12	V
V _{EBO}	Emitter-Base Voltage	2.5	V
I _C	Collector Current-Continuous	0.15	A
P _C	Collector Power Dissipation @T _c =25°C	1.8	W
T _J	Junction Temperature	150	°C
T _{stg}	Storage Temperature Range	-55~150	°C



isc Silicon NPN RF Transistor
2SC4703
ELECTRICAL CHARACTERISTICS

 T_c=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
I _{CB0}	Collector Cutoff Current	V _{CB} = 20V; I _E = 0			1.5	μ A
I _{EB0}	Emitter Cutoff Current	V _{EB} = 2V; I _C = 0			1.5	μ A
h _{FE}	DC Current Gain	I _C = 5mA ; V _{CE} = 5V	50		250	
f _T	Current-Gain—Bandwidth Product	I _C = 5mA ; V _{CE} = 5V		6.0		GHz
C _{OB}	Output Capacitance	I _E = 0 ; V _{CB} = 5V;f= 1.0MHz		1.5	2.5	pF
S _{21e} ²	Insertion Power Gain	I _C = 50mA ; V _{CE} = 5V;f= 1.0GHz	6.5	8.3		dB
S _{21e} ²	Insertion Power Gain	I _C = 20mA ; V _{CE} = 10V;f= 1.0GHz		8.5		dB
NF	Noise Figure	I _C = 50mA ; V _{CE} = 5V;f= 1.0GHz		2.3	3.5	dB
IM ₂	2nd Intermodulation Distortion	V _{CE} = 5V, I _C = 50mA, V _O = 105 dB μ V/75 Ω , f =190 MHz – 90 MHz		-55		dB
		V _{CE} = 10V, I _C = 50mA, V _O = 105 dB μ V/75 Ω , f =190 MHz – 90 MHz		-63		
IM ₃	3rd Intermodulation Distortion	V _{CE} = 5V, I _C = 50mA, V _O = 105 dB μ V/75 Ω , f =2× 190 MHz – 200 MHz		-76		dB
		V _{CE} = 10V, I _C = 50mA, V _O = 105 dB μ V/75 Ω , f =2× 190 MHz – 200 MHz		-81		

◆ h_{FE} Classification

Class	SH	SF	SE
Marking	SH	SF	SE
h _{FE}	50-100	80-160	125-250

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.