

isc Silicon NPN Power Transistor

2SC5887

DESCRIPTION



- Collector-Emitter Breakdown Voltage-
: $V_{(BR)CEO} = 50V(\text{Min})$
- High Speed Switching
- Low Saturation Voltage
- Complement to Type 2SA2098
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Relay drivers, lamp drivers, motor drivers.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	60	V
V_{CEO}	Collector-Emitter Voltage	50	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current-Continuous	15	A
I_{CM}	Collector Current-Pulse	20	A
I_B	Base Current-Continuous	3	A
P_T	Total Power Dissipation @ $T_c=25^\circ\text{C}$	30	W
	Total Power Dissipation @ $T_a=25^\circ\text{C}$	2.0	
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature	-55~150	$^\circ\text{C}$



isc Silicon NPN Power Transistor

2SC5887

ELECTRICAL CHARACTERISTICS

T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 1mA; R _{BE} = ∞	50			V
V _{(BR)CBO}	Collector-Base Breakdown Voltage	I _C = 0.1mA; I _E = 0	60			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	I _E = 0.1mA; I _C = 0	6			V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 7A; I _B = 0.35A			0.4	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C = 7A; I _B = 0.35A			1.4	V
I _{CBO}	Collector Cutoff Current	V _{CB} = 40V; I _E = 0			10	μ A
I _{EBO}	Emitter Cutoff Current	V _{EB} = 4V; I _C = 0			10	μ A
h _{FE}	DC Current Gain	I _C = 1A; V _{CE} = 2V	180		560	
C _{OB}	Output Capacitance	I _E = 0; V _{CB} = 10V; f= 1.0MHz		100		pF
f _T	Current-Gain—Bandwidth Product	I _C = 1A; V _{CE} = 10V		300		MHz

Switching times

t _{on}	Turn-on Time	I _C = 5A, I _{B1} = -I _{B2} = 0.25A, V _{CC} = 20V		50		ns
t _{stg}	Storage Time			700		ns
t _f	Fall Time			40		ns

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.