

**isc Silicon NPN Power Transistor**
**2SD1307**
**DESCRIPTION**

- Collector-Emitter Sustaining Voltage-  
 $V_{CE0(SUS)} = 350V(\text{Min})$
- High DC current gain
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**APPLICATIONS**



- High ruggedness electronic ignitions
- High voltage ignition coil driver

**Absolute maximum ratings( $T_a = 25^\circ\text{C}$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CBO}$	Collector-Base Voltage	350	V
$V_{CEO}$	Collector-Emitter Voltage	350	V
$V_{EBO}$	Emitter-Base Voltage	5	V
$I_C$	Collector Current- Continuous	6	A
$I_{CM}$	Collector Current-Peak	15	A
$P_C$	Collector Power Dissipation @ $T_C = 25^\circ\text{C}$	35	W
$T_j$	Junction Temperature	150	$^\circ\text{C}$
$T_{stg}$	Storage Temperature Range	-65~150	$^\circ\text{C}$

**THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.2	$^\circ\text{C/W}$



**isc Silicon NPN Power Transistor****2SD1307****ELECTRICAL CHARACTERISTICS****T<sub>c</sub>=25°C unless otherwise specified**

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
V <sub>CEO(SUS)</sub>	Collector-Emitter Sustaining Voltage	I <sub>C</sub> = 50mA; I <sub>B</sub> = 0	350			V
V <sub>CE(sat)</sub>	Collector-Emitter Saturation Voltage	I <sub>C</sub> = 4 A; I <sub>B</sub> = 400mA			2.0	V
V <sub>BE(sat)</sub>	Base-Emitter Saturation Voltage	I <sub>C</sub> = 4 A; I <sub>B</sub> = 400mA			2.5	V
I <sub>CBO</sub>	Collector Cutoff Current	V <sub>CB</sub> = 500V; I <sub>E</sub> = 0			0.1	mA
I <sub>CEO</sub>	Collector Cutoff Current	V <sub>CE</sub> = 450V; I <sub>B</sub> = 0			0.1	mA
I <sub>EBO</sub>	Emitter Cutoff Current	V <sub>EB</sub> = 5V; I <sub>C</sub> = 0			5	mA
h <sub>FE-1</sub>	DC Current Gain	I <sub>C</sub> = 2A ; V <sub>CE</sub> = 2V	1500			
h <sub>FE-2</sub>	DC Current Gain	I <sub>C</sub> = 2A ; V <sub>CE</sub> = 2V	200			
C <sub>OB</sub>	Output Capacitance	I <sub>E</sub> = 0 ; V <sub>CB</sub> = 50V, f <sub>test</sub> = 1MHz		35		pF

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.