

isc Silicon NPN Power Transistor
2SD1445
DESCRIPTION



- Low Collector Saturation Voltage
: $V_{CE(sat)} = 0.6V(\text{Max}) @ I_C = 10A$
- Collector-Emitter Breakdown Voltage-
: $V_{(BR)CEO} = 20V(\text{Min})$
- Fast Switching Speed
- Complement to Type 2SB948
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Designed for power amplifier and low-speed switching applications

ABSOLUTE MAXIMUM RATINGS($T_a = 25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	40	V
V_{CEO}	Collector-Emitter Voltage	20	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current-Continuous	10	A
I_{CM}	Collector Current-Peak	20	A
P_C	Collector Power Dissipation @ $T_a = 25^\circ\text{C}$	2	W
	Collector Power Dissipation @ $T_c = 25^\circ\text{C}$	40	
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^\circ\text{C}$



isc Silicon NPN Power Transistor
2SD1445
ELECTRICAL CHARACTERISTICS

 T_c=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _c = 10mA; I _B = 0	20			V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _c = 10A; I _B = 0.33A			0.6	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _c = 10A; I _B = 0.33A			1.5	V
I _{CBO}	Collector Cutoff Current	V _{CB} = 40V; I _E = 0			50	μ A
I _{EBO}	Emitter Cutoff Current	V _{EB} = 5V; I _C = 0			50	μ A
h _{FE-1}	DC Current Gain	I _c = 0.1A; V _{CE} = 2V	45			
h _{FE-2}	DC Current Gain	I _c = 3A; V _{CE} = 2V	90		260	
C _{OB}	Output Capacitance	I _E = 0; V _{CB} = 10V, f _{test} = 1MHz		200		pF
f _T	Current-Gain—Bandwidth Product	I _c = 0.5A; V _{CE} = 10V		120		MHz

Switching Times

t _{on}	Turn-on Time			0.3		μ s
t _{stg}	Storage Time	I _c = 3A; I _{B1} = I _{B2} = 0.1A; V _{CC} = 20V		0.4		μ s
t _f	Fall Time			0.1		μ s

◆ h_{FE-2} classifications

Q	P
90-180	130-260

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.