

isc Silicon NPN Power Transistor
2SD1763A
DESCRIPTION



- High Collector-Emitter Breakdown Voltage-
: $V_{(BR)CEO} = 160V(\text{Min.})$
- Good Linearity of h_{FE}
- Complement to Type 2SB1186A
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Power amplifier applications.
- Driver stage amplifier applications.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	160	V
V_{CEO}	Collector-Emitter Voltage	160	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current-Continuous	1.5	A
I_{CM}	Collector Current-Peak	3	A
P_C	Collector Power Dissipation @ $T_a=25^\circ\text{C}$	2	W
	Collector Power Dissipation @ $T_c=25^\circ\text{C}$	20	
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^\circ\text{C}$



isc Silicon NPN Power Transistor

2SD1763A

ELECTRICAL CHARACTERISTICS

T_c=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 1mA; I _B = 0	160			V
V _{(BR)CBO}	Collector-Base Breakdown Voltage	I _C = 50 μA; I _E = 0	160			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	I _E = 50 μA; I _C = 0	5			V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 1A; I _B = 0.1A			2.0	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C = 1A; I _B = 0.1A			1.5	V
I _{CBO}	Collector Cutoff Current	V _{CB} = 120V; I _E = 0			1	μA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 4V; I _C = 0			1	μA
h _{FE}	DC Current Gain	I _C = 0.1A; V _{CE} = 5V	60		200	
C _{OB}	Output Capacitance	I _E = 0; V _{CB} = 10V; f _{test} =1MHz		20		pF
f _T	Current-Gain—Bandwidth Product	I _E = -0.1A; V _{CE} = 5V; f _{test} = 30MHz		80		MHz

◆ h_{FE} Classifications

D	E
60-120	100-200

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.