

**DESCRIPTION**



- Darlington connection for high DC current gain
- Built in resistor between base and emitter
- Built in damper diode
- Complementary PNP types:2SB1316
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**APPLICATIONS**

- Motor drivers,LED driver,Power supply

**ABSOLUTE MAXIMUM RATINGS( $T_a=25^{\circ}\text{C}$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CBO}$	Collector-Base Voltage	100	V
$V_{CEO}$	Collector-Emitter Voltage	100	V
$V_{EBO}$	Emitter-Base Voltage	6	V
$I_C$	Collector Current-Continuous	2.0	A
$I_{CM}$	Collector Current-Peak	3.0	A
$P_C$	Collector Power Dissipation @ $T_C=25^{\circ}\text{C}$	10	W
$T_J$	Junction Temperature	150	$^{\circ}\text{C}$
$T_{stg}$	Storage Temperature Range	-55~150	$^{\circ}\text{C}$



## isc Silicon NPN Power Transistor

2SD1980

## ELECTRICAL CHARACTERISTICS

T<sub>c</sub>=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
BV <sub>CBO</sub>	Collector-Base breakdown voltage	I <sub>C</sub> =50μA	100			V
BV <sub>CEO</sub>	Collector-Emitter breakdown voltage	I <sub>C</sub> =5mA	100			V
BV <sub>EBO</sub>	Emitter-Base breakdown voltage	I <sub>E</sub> =5mA	6			V
V <sub>CE(sat)</sub>	Collector-Emitter Saturation Voltage	I <sub>C</sub> = 1A; I <sub>B</sub> = 1mA			1.5	V
I <sub>CBO</sub>	Collector Cutoff Current	V <sub>CB</sub> = 100V; I <sub>E</sub> = 0			10	μA
I <sub>EBO</sub>	Emitter Cutoff Current	V <sub>EB</sub> = 5V; I <sub>C</sub> = 0			3.0	mA
h <sub>FE</sub>	DC Current Gain	I <sub>C</sub> = 1A; V <sub>CE</sub> = 2V	1000		10000	
C <sub>OB</sub>	Output Capacitance	I <sub>E</sub> = 0; V <sub>CB</sub> = 10V; f= 1.0MHz		25		pF
f <sub>T</sub>	Current-Gain—Bandwidth Product	I <sub>C</sub> = 0.1A; V <sub>CE</sub> = 5V, f= 100MHz		80		MHz

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.