

isc Silicon NPN Power Transistor

2SD2118

DESCRIPTION


- High current capacity
- Small and slim package making it easy to make 2SD2118-used set smaller
- Low collector-to-emitter saturation voltage
- Fast switching speed
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Strokes, voltage regulators, relay drivers, lamp drivers

ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	50	V
V_{CEO}	Collector-Emitter Voltage	20	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current-Continuous	5	A
I_{CM}	Collector Current-Peak	10	A
P_C	Collector Power Dissipation	10	W
T_J	Junction Temperature	150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^{\circ}\text{C}$



isc Silicon NPN Power Transistor**2SD2118****ELECTRICAL CHARACTERISTICS****T_C=25°C unless otherwise specified**

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 4A; I _B = 100mA			1.0	V
V _{(BR)CBO}	Collector-Base Breakdown Voltage	I _C = 50uA; I _B = 0	50			V
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 1mA; I _B = 0	20			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	I _E = 50uA; I _C = 0	6			V
I _{CBO}	Collector Cutoff Current	V _{CB} = 40V; I _E = 0			0.5	uA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 5V; I _C = 0			0.5	uA
h _{FE}	DC Current Gain	I _C = 0.5A; V _{CE} = 2V	120		390	
C _{OB}	Output Capacitance	I _E = 0; V _{CB} = 20V; f= 1.0MHz		30		pF
f _T	Current-Gain—Bandwidth Product	I _C = 50mA; V _{CE} = 6V		150		MHz



◆ h_{FE} Classifications

Q	R
120-270	180-390

isc Silicon NPN Power Transistor

2SD2118

Outline Drawing



NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.