

isc Silicon NPN Darlington Power Transistor

2SD985

DESCRIPTION



- Collector–Emitter Breakdown Voltage–
: $V_{(BR)CEO} = 60V(\text{Min.})$
- DC Current Gain–
: $h_{FE} = 2000(\text{Min}) @ I_C = 1A$
- Low Collector Saturation Voltage
- Complement to Type 2SB794
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- They are suitable for use to operate from IC without predriver, such as hammer driver.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	150	V
V_{CEO}	Collector-Emitter Voltage	60	V
V_{EBO}	Emitter-Base Voltage	8	V
I_C	Collector Current-Continuous	1.5	A
I_{CM}	Collector Current-Pulse	3.0	A
I_B	Base Current	0.15	A
P_C	Collector Power Dissipation $T_a=25^\circ\text{C}$	1.0	W
	Collector Power Dissipation $T_C=25^\circ\text{C}$	10	
T_j	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^\circ\text{C}$



isc Silicon NPN Darlington Power Transistor

2SD985

ELECTRICAL CHARACTERISTICS

T_c=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 1A; I _B = 1mA			1.5	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C = 1A; I _B = 1mA			2.0	V
I _{CBO}	Collector Cutoff Current	V _{CB} = 60V; I _E = 0			10	μ A
I _{EBO}	Emitter Cutoff Current	V _{EB} = 5V; I _C = 0			1.0	mA
h _{FE-1}	DC Current Gain	I _C = 0.5A; V _{CE} = 2V	1000			
h _{FE-2}	DC Current Gain	I _C = 1A; V _{CE} = 2V	2000		30000	

Switching Times

t _{on}	Turn-on Time			0.5		μ s
t _{stg}	Storage Time	I _C =1.0A; I _{B1} =I _{B2} =1.0mA V _{CC} =50V; R _L =50 Ω		1.0		μ s
t _f	Fall Time			1.0		μ s

◆ h_{FE-2} Classifications

M	L	K
2000-5000	4000-10000	8000-30000

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.