



No.4744

2SJ255

## P-Channel MOS Silicon FET

## Very High-Speed Switching Applications

## Features

- Low ON resistance.
  - Very high-speed switching.
  - Low-voltage drive.
  - Micaless package facilitating easy mounting.


#### Absolute Maximum Ratings at Ta = 25°C

Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$		Unit
Drain-to-Source Voltage	$V_{DSS}$	-30 V
Gate-to-Source Voltage	$V_{GSS}$	$\pm 20$ V
Drain Current(DC)	$I_D$	-10 A
Drain Current(Pulse)	$I_{DP}$	PW $\leq 10\ \mu\text{s}$ , duty cycle $\leq 1\%$ -40 A
Allowable Power Dissipation	$P_D$	2.0 W
		25 W
Channel Temperature	$T_{ch}$	150 $^\circ\text{C}$
Storage Temperature	$T_{stg}$	-55 to +150 $^\circ\text{C}$


### Electrical Characteristics at Ta = 25°C

Electrical Characteristics at TA = 25°C			Min	Typ	Max	Units
D-S Breakdown Voltage	V <sub>(BR)DSS</sub>	I <sub>D</sub> = -1mA, V <sub>GS</sub> = 0	-30			V
G-S Breakdown Voltage	V <sub>(BR)GSS</sub>	I <sub>G</sub> = ±100μA, V <sub>DS</sub> = 0	±20			V
Zero-Gate Voltage	I <sub>DSS</sub>	V <sub>DS</sub> = -30V, V <sub>GS</sub> = 0			-100	μA
Drain Current						
Gate-to-Source Leakage Current	I <sub>GSS</sub>	V <sub>GS</sub> = ±16V, V <sub>DS</sub> = 0		±10		μA
Cutoff Voltage	V <sub>GS(off)</sub>	V <sub>DS</sub> = -10V, I <sub>D</sub> = -1mA	-1.0		-2.0	V
Forward Transfer Admittance	V <sub>fs</sub>	V <sub>DS</sub> = -10V, I <sub>D</sub> = -6A	5	8		S
Static Drain-to-Source	R <sub>DS(on)</sub>	I <sub>D</sub> = -6A, V <sub>GS</sub> = -10V		0.07	0.095	Ω
ON-State Resistance	R <sub>DS(on)</sub>	I <sub>D</sub> = -6A, V <sub>GS</sub> = -4V		0.095	0.13	Ω
Input Capacitance	C <sub>iss</sub>	V <sub>DS</sub> = -10V, f = 1MHz		1300		pF
Output Capacitance	C <sub>oss</sub>	V <sub>DS</sub> = -10V, f = 1MHz		780		pF
Reverse Transfer Capacitance	C <sub>rss</sub>	V <sub>DS</sub> = -10V, f = 1MHz		290		pF
Turn-ON Delay Time	t <sub>d(on)</sub>	See specified Test Circuit.		16		ns
Rise Time	t <sub>r</sub>	"		60		ns
Turn-OFF Delay Time	t <sub>d(off)</sub>	"		300		ns
Fall Time	t <sub>f</sub>	"		250		ns
Diode Forward Voltage	V <sub>SD</sub>	I <sub>S</sub> = -10A, V <sub>GS</sub> = 0	-1.0	-1.5		V

### **Switching Time Test Circuit**






**Package Dimensions 2063A**  
(unit: mm)



3730

**SANYO Electric Co.,Ltd. Semiconductor Business Headquarters**  
TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
  - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
  - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.