


isc N-Channel MOSFET Transistor

2SK1478

DESCRIPTION


- Drain Current –I_D=8A@ T_C=25 °C
- · Drain Source Voltage-
 - : V_{DSS}=250V(Min)
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

ABSOLUTE MAXIMUM RATINGS(Ta=25°C)



APPLICATIONS

· High speed power switching



SYMBOL	ARAMETER	VALUE	UNIT
V _{DSS}	Drain-Source Voltage (V _S =0)	250	V
V_{GS}	Gate-Source Voltage	±20	V
l _D	Drain Current-continuous@ TC=25°C	8	Α
P _{tot}	Total Dissipation@TC=25℃	40	W
Tj	Max. Operating Junction Temperature	150	$^{\circ}\mathbb{C}$
T_{stg}	Storage Temperature Range	-55~150	$^{\circ}\mathbb{C}$

DIM	mm		1
	MIN	MAX	
A	16.85	17.15	
В	9.90	10.10	
C	4.35	4.65	
D	0.75	0.80	
F	3.20	3.40	
G	6.90	7.10	3
н	5.15	5.45	
J	0.45	0.75	1
K	13.35	13.65	
L	1.10	1.30	
N	4.98	5.18	9
Q	4.85	5.15	
R	2.95	3.25	
S	2.70	2.90	-
U	1.75	2.05	
٧	1.30	1.50	



isc N-Channel Mosfet Transistor

2SK1478

• ELECTRICAL CHARACTERISTICS (Tc=25°C)

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V _{GS} =0; I _D = 1mA	250			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =25V; I _D =1mA	1.0		5.0	V
R _{DS(on)}	Drain-Source On-stage Resistance	V _{GS} =10V; I _D =5A		0.4	0.6	Ω
I _{GSS}	Gate Source Leakage Current	V _{GS} = ±20V;V _{DS} = 0			±1	uA
IDSS	Zero Gate Voltage Drain Current	V _{DS} =200V; V _{GS} = 0			0.1	mA
ton	Turn-on time	V_{GS} =10V; I_D =5A; R_L =20 Ω		72		ns
toff	Turn-off time			180		ns



ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

2