isc N-Channel MOSFET Transistor 2SK1635



DESCRIPTION

- Drain Current –I_D= 50A@ T_C=25℃
- Drain Source Voltage-
  : V_{DSS}=60V(Min)
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- High current,
- low voltage

ABSOLUTE MAXIMUM RATINGS(T_a=25℃)

SYMBOL	ARAMETER	VALUE	UNIT
V_{DSS}	Drain-Source Voltage (V_{GS}=0)	60	V
V_{GS}	Gate-Source Voltage	±30	V
I_D	Drain Current-continuous@ TC=25℃	50	A
P_{tot}	Total Dissipation@TC=25℃	130	W
T_j	Max. Operating Junction Temperature	150	℃
T_{stg}	Storage Temperature Range	-55~150	℃



DIM	mm MIN	MAX
A	25.50	26.50
B	19.80	20.20
C	4.50	5.50
D	0.90	1.10
E	2.80	3.20
F	2.40	2.60
G	10.80	11.00
H	3.10	3.30
J	0.50	0.70
K	20.00	21.00
N	3.90	4.50
P	2.40	2.60
Q	3.10	3.50
R	1.90	2.60
U	3.90	4.10
W	2.90	3.25

isc N-Channel Mosfet Transistor 2SK1635

• **ELECTRICAL CHARACTERISTICS (T_C=25℃)**

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V_{GS}=0; I_D= 10mA	60			V
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=10 V_{GS}; I_D=1mA	1.0		5.0	V
$R_{DS(on)}$	Drain-Source On-stage Resistance	V_{GS}=10V; I_D=25A			0.03	Ω
I_{GSS}	Gate Source Leakage Current	V_{GS}= ±30V;V_{DS}= 0			±100	nA
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=60V; V_{GS}= 0			500	uA