


MOS Field Effect Transistor

2SK3571

■ Features

- 4.5V drive available.
- Low on-state resistance,
 $R_{DS(on)1} = 9\text{m}\Omega$ MAX. ($V_{GS} = 10\text{V}$, $I_D = 24\text{A}$)
- Low gate charge
 $Q_G = 21\text{nC}$ TYP. ($V_{DD} = 16\text{V}$, $V_{GS} = 10\text{V}$, $I_D = 48\text{A}$)
- Built-in gate protection diode
- Surface mount device available



■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Drain to source voltage	V_{DS}	20	V
Gate to source voltage	V_{GS}	± 20	V
Drain current	I_D	± 48	A
	I_{DP}^*	± 192	A
Power dissipation	P_D	40	W
		1.5	
Channel temperature	T_{ch}	150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to +150	$^\circ\text{C}$

* $PW \leq 10\mu\text{s}$, Duty Cycle $\leq 1\%$

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Testconditions	Min	Typ	Max	Unit
Drain cut-off current	I_{DSS}	$V_{DS}=20\text{V}, V_{GS}=0$			10	μA
Gate leakage current	I_{GSS}	$V_{GS}=\pm 20\text{V}, V_{DS}=0$			± 10	μA
Gate cut off voltage	$V_{GS(off)}$	$V_{DS}=10\text{V}, I_D=1\text{mA}$	1.5		2.5	V
Forward transfer admittance	$ Y_{fs} $	$V_{DS}=10\text{V}, I_D=24\text{A}$	11			S
Drain to source on-state resistance	$R_{DS(on)1}$	$V_{GS}=10\text{V}, I_D=24\text{A}$		7.0	9.0	$\text{m}\Omega$
	$R_{DS(on)2}$	$V_{GS}=4.5\text{V}, I_D=18\text{A}$		10	16	$\text{m}\Omega$
Input capacitance	C_{iss}	$V_{DS}=10\text{V}, V_{GS}=0, f=1\text{MHz}$		1100		pF
Output capacitance	C_{oss}			450		pF
Reverse transfer capacitance	C_{rss}			160		pF
Turn-on delay time	t_{on}	$I_D=24\text{A}, V_{GS(on)}=10\text{V}, R_G=10\Omega, V_{DD}=10\text{V}$		13		ns
Rise time	t_r			5		ns
Turn-off delay time	t_{off}			40		ns
Fall time	t_f			9		ns
Total Gate Charge	Q_G	$V_{DD} = 16\text{V}$ $V_{GS} = 10\text{V}$ $I_D = 48\text{A}$		21		nC
Gate to Source Charge	Q_{GS}			4.2		nC
Gate to Drain Charge	Q_{GD}			5		nC