

2STA1962

High power PNP epitaxial planar bipolar transistor

Preliminary Data

Features

- High breakdown voltage V_{CEO} > -230V
- Complementary to 2STC5242
- Fast-switching speed
- Typical f_T= 30MHz

Application

Audio power amplifier

Description

This device is a PNP transistor manufactured using new BiT-LA (Bipolar Transistor for linear amplifier) technology. The resulting transistor shows good gain linearity behaviour.




Figure 1. Internal schematic diagram




Table 1.	Device	summary
	Device	Summary

Order code	Marking	Package	Packaging
2STA1962	2STA1962	TO-3P	Tube

1 Electrical ratings

Table 2.	Absolute	maximum	ratings
	Absolute	maximum	raungs

Symbol	Parameter	Value	Unit
V _{CBO}	Collector-base voltage (I _E =0)	-230	V
V _{CEO}	Collector-emitter voltage $(I_B = 0)$	-230	V
V _{EBO}	Emitter-base voltage $(I_C = 0)$	-5	V
۱ _C	Collector current	-15	А
I _{CM}	Collector peak current	-30	А
P _{tot}	Total dissipation at $T_C = 25^{\circ}C$	130	W
T _{stg}	Storage temperature	-55 to 150	°C
TJ	Operating junction temperature	150	°C

Table 3.Thermal data

Symbol	Parameter	Value	Unit
R _{thJ-case}	Thermal resistance junction-case Max	0.96	°C/W



2 Electrical characteristics

(T_{CASE}=25°C unless otherwise specified)

Table 4.	Electrical	characteristics
----------	------------	-----------------

Symbol	Parameter	Test co	nditions	Min.	Тур.	Max.	Unit
I _{CBO}	Collector cut-off current $(I_E = 0)$	V _{CB} = -230V				-5	μA
I _{EBO}	Emitter cut-off current (I _C = 0)	V _{EB} = -5V				-5	μA
V _{(BR)CEO} ⁽¹⁾	Collector-emitter breakdown voltage ($I_B = 0$)	I _C = -50mA		-230			۷
V _{(BR)CBO}	Collector-base breakdown voltage (I _E = 0)	I _C = -100μA		-230			V
V _{(BR)EBO} ⁽¹⁾	Emitter-base breakdown voltage (I _C = 0)	I _E = -1mA		-5			V
V _{CE(sat)} ⁽¹⁾	Collector-emitter saturation voltage	I _C = -8A;	I _B = -800mA			-3	V
V_{BE}	Base-emitter voltage	I _C = -7A;	$V_{CE} = -5V$			-1.5	V
h _{FE}	DC current gain	I _C = -1A; I _C = -7A;	V _{CE} = -5V V _{CE} = -5V	80 35		160	
f _T	Transition frequency	I _C = -1A;	$V_{CE} = -5V$		30		MHz
C _{CBO}	Collector-base capacitance $I_E = 0$	V _{CB} = -10V;	f = 1MHz		225		pF

1. Pulsed: pulse duration = 300 μ s, duty cycle \leq 1.5%

57

2.1 Electrical characteristics (curves)

HV39480 DG11570 Ic(A) Ic(A) Ic(A) Ic(A) Ic(A) PULSE OPERATION for PULSED Single non repetitive pulse Single non repetitive pulse P_{tot} (%) 10 6 I_C MAX CONT 100 4 3 2 80 1 0.6 0.4 0.3 0.2 1ms 60 ls∕в 10ms D.C. OPERATION 40 0.1 0.06 0.04 0.03 0.02 100m 20 4 6 10 20 40 0.01^L 1 0 75 25 50 100 125 T_{case}(°C) 100 200 2 $V_{CE}(V)$

Figure 2. Safe operating area

Figure 3. Derating curve


3 Package mechanical data

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a Lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: *www.st.com*



DIM.		mm.	
	MIN.	ТҮР	MAX.
A	4.6		5
A1	1.45	1.50	1.65
A2	1.20	1.40	1.60
b	0.80	1	1.20
b1	1.80		2.20
b2	2.80		3.20
С	0.55	0.60	0.75
D	19.70	19.90	20.10
D1		13.90	
E	15.40		15.80
E1		13.60	
E2		9.60	
е	5.15	5.45	5.75
L	19.50	20	20.50
L1		3.50	
L2	18.20	18.40	18.60
Р	3.10		3.30
Q		5	
Q1		3.80	





4 Revision history

Table 5. Document revision history

Date	Revision	Changes
28-Sep-2007	1	Initial release



Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2007 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

