



TO-92 Plastic-Encapsulate Transistors


3DG3332 TRANSISTOR (NPN)

FEATURES

- Low Current
- High Voltage

APPLICATIONS

- Video
- Telephony
- Professional Communication Equipment



MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

| Symbol | Parameter | Value | Unit |
|-----------------|---|----------|-----------------------------|
| V_{CBO} | Collector-Base Voltage | 180 | V |
| V_{CEO} | Collector-Emitter Voltage | 160 | V |
| V_{EBO} | Emitter-Base Voltage | 6 | V |
| I_C | Collector Current | 0.7 | A |
| P_C | Collector Power Dissipation | 625 | mW |
| $R_{\theta JA}$ | Thermal Resistance From Junction To Ambient | 200 | $^{\circ}\text{C}/\text{W}$ |
| T_j | Junction Temperature | 150 | $^{\circ}\text{C}$ |
| T_{stg} | Storage Temperature | -55~+150 | $^{\circ}\text{C}$ |

ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$ unless otherwise specified)

| Parameter | Symbol | Test conditions | Min | Typ | Max | Unit |
|--------------------------------------|------------------|---|-----|-----|-----|---------------|
| Collector-base breakdown voltage | $V_{(BR)CBO}$ | $I_C=0.01\text{mA}, I_E=0$ | 180 | | | V |
| Collector-emitter breakdown voltage | $V_{(BR)CEO}$ | $I_C=1\text{mA}, I_B=0$ | 160 | | | V |
| Emitter-base breakdown voltage | $V_{(BR)EBO}$ | $I_E=0.01\text{mA}, I_C=0$ | 6 | | | V |
| Collector cut-off current | I_{CBO} | $V_{CB}=120\text{V}, I_E=0$ | | | 0.1 | μA |
| Emitter cut-off current | I_{EBO} | $V_{EB}=4\text{V}, I_C=0$ | | | 0.1 | μA |
| DC current gain | $h_{FE(1)}$ | $V_{CE}=5\text{V}, I_C=100\text{mA}$ | 100 | | 400 | |
| | $h_{FE(2)}$ | $V_{CE}=5\text{V}, I_C=10\text{mA}$ | 80 | | | |
| Collector-emitter saturation voltage | $V_{CE(sat)(1)}$ | $I_C=250\text{mA}, I_B=25\text{mA}$ | | | 0.4 | V |
| Base-emitter saturation voltage | $V_{BE(sat)}$ | $I_C=250\text{mA}, I_B=25\text{mA}$ | | | 1.2 | V |
| Transition frequency | f_T | $V_{CE}=10\text{V}, I_C=50\text{mA}$ | | 120 | | MHz |
| Collector output capacitance | C_{ob} | $V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$ | | 8 | | pF |

CLASSIFICATION OF $h_{FE(1)}$

| RANK | R | S | T |
|-------|---------|---------|---------|
| RANGE | 100-200 | 140-280 | 200-400 |