

## General Description



These P-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

| BVDSS | RDSON | ID   |
|-------|-------|------|
| -30V  | 13mΩ  | -30A |

## Features

- -30V, -30A,  $R_{DS(ON)} = 13m\Omega @ V_{GS} = -10V$
- Fast switching
- Green Device Available

## PDFN3x3 Pin Configuration



## Applications

- MB / VGA / Vcore
- POL Applications
- Load Switch
- LED Application

## Absolute Maximum Ratings $T_c=25^\circ\text{C}$ unless otherwise noted

| Symbol    | Parameter  | Rating     | Units               |
|-----------|--|------------|---------------------|
| $V_{DS}$  | Drain-Source Voltage                                   | -30        | V                   |
| $V_{GS}$  | Gate-Source Voltage                                    | $\pm 20$   | V                   |
| $I_D$     | Drain Current – Continuous ( $T_c=25^\circ\text{C}$ )  | -30        | A                   |
|           | Drain Current – Continuous ( $T_c=100^\circ\text{C}$ ) | -17        | A                   |
| $I_{DM}$  | Drain Current – Pulsed <sup>1</sup>                    | -120       | A                   |
| $P_D$     | Power Dissipation ( $T_c=25^\circ\text{C}$ )           | 27         | W                   |
|           | Power Dissipation – Derate above $25^\circ\text{C}$    | 0.22       | W/ $^\circ\text{C}$ |
| $T_{STG}$ | Storage Temperature Range                              | -55 to 150 | $^\circ\text{C}$    |
| $T_J$     | Operating Junction Temperature Range                   | -55 to 150 | $^\circ\text{C}$    |

## Thermal Characteristics

| Symbol          | Parameter                              | Typ. | Max. | Unit               |
|-----------------|--|------|------|--------------------|
| $R_{\theta JA}$ | Thermal Resistance Junction to ambient | ---  | 62   | $^\circ\text{C/W}$ |
| $R_{\theta JC}$ | Thermal Resistance Junction to Case    | ---  | 4.6  | $^\circ\text{C/W}$ |

**Electrical Characteristics (T<sub>J</sub>=25 °C, unless otherwise noted)**
**Off Characteristics**

| Symbol                              | Parameter                                 | Conditions  | Min. | Typ.  | Max. | Unit |
|-------------------------------------|---|---|------|-------|------|------|
| BV <sub>DSS</sub>                   | Drain-Source Breakdown Voltage            | V <sub>GS</sub> =0V, I <sub>D</sub> =-250uA                       | -30  | ---   | ---  | V    |
| △BV <sub>DSS</sub> /△T <sub>J</sub> | BV <sub>DSS</sub> Temperature Coefficient | Reference to 25°C, I <sub>D</sub> =-1mA                           | ---  | -0.03 | ---  | V/°C |
| I <sub>DSS</sub>                    | Drain-Source Leakage Current              | V <sub>DS</sub> =-27V, V <sub>GS</sub> =0V, T <sub>J</sub> =25°C  | ---  | ---   | -1   | uA   |
|                                     |   | V <sub>DS</sub> =-24V, V <sub>GS</sub> =0V, T <sub>J</sub> =125°C | ---  | ---   | -10  | uA   |
| I <sub>GSS</sub>                    | Gate-Source Leakage Current               | V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V                        | ---  | ---   | ±100 | nA   |

**On Characteristics**

|                      |   |   |      |      |      |       |
|----------------------|---|---|------|------|------|-------|
| R <sub>DS(ON)</sub>  | Static Drain-Source On-Resistance           | V <sub>GS</sub> =-10V, I <sub>D</sub> =-8A                | ---  | 13   | 18   | mΩ    |
|                      |   | V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-6A               | ---  | 18   | 23   | mΩ    |
| V <sub>GS(th)</sub>  | Gate Threshold Voltage                      | V <sub>GS</sub> =V <sub>DS</sub> , I <sub>D</sub> =-250uA | -1.0 | -1.5 | -2.5 | V     |
| △V <sub>GS(th)</sub> | V <sub>GS(th)</sub> Temperature Coefficient |   | ---  | 4    | ---  | mV/°C |
| g <sub>fs</sub>      | Forward Transconductance                    | V <sub>DS</sub> =-10V, I <sub>D</sub> =-8A                | ---  | 6.8  | ---  | S     |

**Dynamic and switching Characteristics**







|                     |                                     |   |     |      |     |    |
|---------------------|-------------------------------------|---|-----|------|-----|----|
| Q <sub>g</sub>      | Total Gate Charge <sup>2, 3</sup>   | V <sub>DS</sub> =-15V, V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-5A                      | --- | 15   | --- | nC |
| Q <sub>gs</sub>     | Gate-Source Charge <sup>2, 3</sup>  |   | --- | 4.2  | --- |    |
| Q <sub>gd</sub>     | Gate-Drain Charge <sup>2, 3</sup>   |   | --- | 6.5  | --- |    |
| T <sub>d(on)</sub>  | Turn-On Delay Time <sup>2, 3</sup>  | V <sub>DD</sub> =-15V, V <sub>GS</sub> =-10V, R <sub>G</sub> =6Ω<br>I <sub>D</sub> =-1A | --- | 9.1  | --- | ns |
| T <sub>r</sub>      | Rise Time <sup>2, 3</sup>           |   | --- | 22.1 | --- |    |
| T <sub>d(off)</sub> | Turn-Off Delay Time <sup>2, 3</sup> |   | --- | 59.5 | --- |    |
| T <sub>f</sub>      | Fall Time <sup>2, 3</sup>           |   | --- | 14.5 | --- |    |
| C <sub>iss</sub>    | Input Capacitance                   | V <sub>DS</sub> =-15V, V <sub>GS</sub> =0V, F=1MHz                                      | --- | 1750 | --- | pF |
| C <sub>oss</sub>    | Output Capacitance                  |   | --- | 180  | --- |    |
| C <sub>rss</sub>    | Reverse Transfer Capacitance        |   | --- | 125  | --- |    |


**Drain-Source Diode Characteristics and Maximum Ratings**

| Symbol          | Parameter                 | Conditions   | Min. | Typ. | Max. | Unit |
|-----------------|---------------------------|--|------|------|------|------|
| I <sub>S</sub>  | Continuous Source Current | V <sub>G</sub> =V <sub>D</sub> =0V, Force Current              | ---  | ---  | -30  | A    |
| I <sub>SM</sub> | Pulsed Source Current     |  | ---  | ---  | -60  | A    |
| V <sub>SD</sub> | Diode Forward Voltage     | V <sub>GS</sub> =0V, I <sub>S</sub> =-1A, T <sub>J</sub> =25°C | ---  | ---  | -1.2 | V    |


Note :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. The data tested by pulsed, pulse width ≤ 300us, duty cycle ≤ 2%.
3. Essentially independent of operating temperature.


**Fig.1 Continuous Drain Current vs.  $T_c$** 

**Fig.2 Normalized  $R_{DS(on)}$  vs.  $T_J$** 

**Fig.3 Normalized  $V_{th}$  vs.  $T_J$** 

**Fig.4 Gate Charge Waveform**

**Fig.5 Normalized Transient Impedance**

**Fig.6 Maximum Safe Operation Area**




**Fig.7 Switching Time Waveform**



**Fig.8 Gate Charge Waveform**

## PDFN3x3 PACKAGE INFORMATION



| Symbol | Dimensions In Millimeters |       | Dimensions In Inches |       |
|--------|---------------------------|-------|----------------------|-------|
|        | MAX                       | MIN   | MAX                  | MIN   |
| A      | 0.900                     | 0.700 | 0.035                | 0.028 |
| b      | 0.350                     | 0.250 | 0.014                | 0.010 |
| c      | 0.250                     | 0.100 | 0.010                | 0.004 |
| D      | 3.500                     | 3.050 | 0.138                | 0.120 |
| D1     | 3.200                     | 2.900 | 0.126                | 0.114 |
| D2     | 1.950                     | 1.350 | 0.077                | 0.053 |
| E      | 3.400                     | 3.000 | 0.134                | 0.118 |
| E1     | 3.300                     | 2.900 | 0.130                | 0.114 |
| E2     | 2.600                     | 2.350 | 0.102                | 0.093 |
| e      | 0.65BSC                   |       | 0.026BSC             |       |
| H      | 0.750                     | 0.300 | 0.030                | 0.012 |
| L      | 0.600                     | 0.300 | 0.024                | 0.012 |
| L1     | 0.200                     | 0.060 | 0.008                | 0.002 |
| θ      | 14°                       | 6°    | 14°                  | 6°    |

## Attention

1, Any and all JGSEMI products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical or material damage. Consult with your JGSEMI representative nearest you before using any JGSEMI products described or contained herein in such applications.

2, JGSEMI assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all JGSEMI products described or contained herein.

3, Specifications of any and all JGSEMI products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

4, In the event that any or all JGSEMI products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

5, No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of JGSEMI Semiconductor CO., LTD.

6, Any and all information described or contained herein are subject to change without notice due to product technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the JGSEMI product that you intend to use.