



**4N80-FC****Power MOSFET****4.0A, 800V N-CHANNEL  
POWER MOSFET****■ DESCRIPTION**

The UTC **4N80-FC** provide excellent  $R_{DS(ON)}$ , low gate charge and operation with low gate voltages. This device is suitable for use as a load switch or in PWM applications.

**■ FEATURES**

- \*  $R_{DS(ON)} \leq 3.7 \Omega$  @  $V_{GS}=10V$ ,  $I_D=2.0A$
- \* Low Reverse Transfer Capacitance
- \* Fast Switching Capability
- \* Avalanche Energy Specified
- \* Improved dv/dt Capability, High Ruggedness


**■ SYMBOL****■ ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
4N80L-TA3-T	4N80G-TA3-T	TO-220	G	D	S	Tube
4N80L-TF1-T	4N80G-TF1-T	TO-220F1	G	D	S	Tube
4N80L-TF2-T	4N80G-TF2-T	TO-220F2	G	D	S	Tube
4N80L-TF3-T	4N80G-TF3-T	TO-220F	G	D	S	Tube
4N80L-TM3-T	4N80G-TM3-T	TO-251	G	D	S	Tube
4N80L-TN3-R	4N80G-TN3-R	TO-252	G	D	S	Tape Reel
4N80L-T2Q-T	4N80G-T2Q-T	TO-262	G	D	S	Tube
4N80L-TQ2-T	4N80G-TQ2-T	TO-263	G	D	S	Tube
4N80L-TQ2-R	4N80G-TQ2-R	TO-263	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

<p>(1)Packing Type (2)Package Type (3)Green Package</p>	<p>(1) T: Tube, R: Tape Reel (2) TA3: TO-220, TF1: TO-220F1, TF2: TO-220F2 TF3: TO-220F, TM3: TO-251, TN3: TO-252 T2Q: TO-262, TQ2: TO-263 (3) G: Halogen Free and Lead Free, L: Lead Free</p>
---	--

## ■ MARKING



■ ABSOLUTE MAXIMUM RATINGS ( $T_c=25^\circ\text{C}$ , unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		$V_{DSS}$	800	V
Gate-Source Voltage		$V_{GSS}$	$\pm 30$	V
Drain Current	Continuous	$I_D$	4	A
	Pulsed (Note 2)	$I_{DM}$	12	A
	TO-220/TO-263 TO-251/TO-252		8	A
	TO-220F/TO-220F1 TO-220F2			
Avalanche Energy	Single Pulsed (Note 3)	$E_{AS}$	132	mJ
Peak Diode Recovery $dv/dt$ (Note 4)		$dv/dt$	2.45	V/ns
Power Dissipation	TO-220/TO-262/TO-263	$P_D$	108	W
	TO-220F/TO-220F1/TO-220F2		28	W
	TO-251/TO-252		47	W
Junction Temperature		$T_J$	+150	$^\circ\text{C}$
Storage Temperature		$T_{STG}$	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3.  $L=30\text{mH}$ ,  $I_{AS}=4.0\text{A}$ ,  $V_{DD}=25\text{V}$ ,  $R_G=25\Omega$ , Starting  $T_J = 25^\circ\text{C}$

4.  $I_{SD} \leq 4.0\text{A}$ ,  $di/dt \leq 200\text{A}/\mu\text{s}$ ,  $V_{DD} \leq BV_{DSS}$ , Starting  $T_J = 25^\circ\text{C}$

■ THERMAL DATA

PARAMETER		SYMBOL	RATING	UNIT
Junction to Ambient	TO-220/TO-220F/TO-220F1 TO-220F2/TO-262/TO-263	$\theta_{JA}$	62.5	$^\circ\text{C/W}$
	TO-251/TO-252		110	$^\circ\text{C/W}$
	TO-220/TO-262/TO-263	$\theta_{JC}$	1.18	$^\circ\text{C/W}$
Junction to Case	TO-220F/TO-220F1/TO-220F2	$\theta_{JC}$	4.46	$^\circ\text{C/W}$
	TO-251/TO-252		2.65 (Note)	$^\circ\text{C/W}$

Note: Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.


■ ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
<b>OFF CHARACTERISTICS</b>						
Drain-Source Breakdown Voltage	$\text{BV}_{\text{DSS}}$	$\text{V}_{\text{GS}}=0\text{V}, \text{I}_D=250\mu\text{A}$	800			V
Drain-Source Leakage Current	$\text{I}_{\text{DSS}}$	$\text{V}_{\text{DS}}=800\text{V}, \text{V}_{\text{GS}}=0\text{V}$			10	$\mu\text{A}$
Gate-Source Leakage Current	$\text{I}_{\text{GSS}}$	$\text{V}_{\text{GS}}=\pm 30\text{V}, \text{V}_{\text{DS}}=0\text{V}$			$\pm 100$	nA
<b>ON CHARACTERISTICS</b>						
Gate Threshold Voltage	$\text{V}_{\text{GS}(\text{TH})}$	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}, \text{I}_D=250\mu\text{A}$	3.0		5.0	V
Static Drain-Source On-State Resistance	$\text{R}_{\text{DS}(\text{ON})}$	$\text{V}_{\text{GS}}=10\text{V}, \text{I}_D=2.0\text{A}$			3.7	$\Omega$
<b>DYNAMIC CHARACTERISTICS</b>						
Input Capacitance	$\text{C}_{\text{ISS}}$	$\text{V}_{\text{DS}}=25\text{V}, \text{V}_{\text{GS}}=0\text{V}, f=1\text{MHz}$		600		pF
Output Capacitance	$\text{C}_{\text{OSS}}$			62		pF
Reverse Transfer Capacitance	$\text{C}_{\text{RSS}}$			2		pF
<b>SWITCHING CHARACTERISTICS</b>						
Total Gate Charge (Note 1)	$\text{Q}_G$	$\text{V}_{\text{DS}}=640\text{V}, \text{V}_{\text{GS}}=10\text{V}, \text{I}_D=4\text{A}$ (Note 1, 2)		10		nC
Gate-Source Charge	$\text{Q}_{\text{GS}}$			5		nC
Gate-Drain Charge	$\text{Q}_{\text{GD}}$			1		nC
Turn-On Delay Time (Note 1)	$t_{\text{D}(\text{ON})}$	$\text{V}_{\text{DD}}=100\text{V}, \text{V}_{\text{GS}}=10\text{V}, \text{I}_D=4\text{A},$ $\text{R}_G=25\Omega$ (Note 1, 2)		9.6		ns
Turn-On Rise Time	$t_R$			15.4		ns
Turn-Off Delay Time	$t_{\text{D}(\text{OFF})}$			21.6		ns
Turn-Off Fall Time	$t_F$			26.5		ns
<b>SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS</b>						
Maximum Continuous Drain-Source Diode Forward Current	$\text{I}_S$				4	A
Maximum Pulsed Drain-Source Diode Forward Current	$\text{I}_{\text{SM}}$				8	A
Drain-Source Diode Forward Voltage (Note 1)	$\text{V}_{\text{SD}}$	$\text{I}_S=4\text{A}, \text{V}_{\text{GS}}=0\text{V}$			1.4	V
Body Diode Reverse Recovery Time (Note 1)	$t_{\text{rr}}$	$\text{I}_S=4\text{A}, \text{V}_{\text{GS}}=0\text{V},$ $d\text{I}_F/dt=100\text{A}/\mu\text{s}$		430		nS
Body Diode Reverse Recovery Charge	$\text{Q}_{\text{rr}}$			6.8		$\mu\text{C}$




Notes: 1. Pulse Test: Pulse width  $\leq 300\mu\text{s}$ , Duty cycle  $\leq 2\%$ .

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery  $dv/dt$  Test Circuit




Peak Diode Recovery  $dv/dt$  Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms


■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



- TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.