



50SQ Series

INTERNATIONAL RECTIFIER 

4855452 INTERNATIONAL RECTIFIER

55C 05052 D

VOLTAGE RATINGS

Part Numbers	$V_{RWM}$ - Max. Working Peak Reverse Voltage (V) ①	$V_{RRM}$ - Max. Repetitive Peak Reverse Voltage (V) ② (200 ns Max. Pulse Width)	$V_R$ - Max. Direct Reverse Voltage (V) ③
50SQ030	30	36	30
50SQ035	35	42	35
50SQ040	40	48	40
50SQ045	45	54	45
50SQ060	60	72	60
50SQ080	80	96	80
50SQ090	90	108	90
50SQ100	100	120	100

T-03-17

ELECTRICAL SPECIFICATIONS

	50SQ	Units	Conditions
$I_{F(AV)}$ Maximum average forward current	5	A	180° conduction @ $T_L = -65$ to $92^\circ\text{C}$ rectangular waveform ① ③
	4.5		180° conduction @ $T_L = -65$ to $96^\circ\text{C}$ sinusoidal waveform ① ③
$I_{FSM}$ Maximum peak one cycle, non-repetitive surge current	215	A	Half cycle 60 Hz sine wave or 6 ms rectangular pulse Following any rated load condition and with rated $V_{RWM}$ reapplied.
	225		Half cycle 60 Hz sine wave or 5 ms rectangular pulse
	255		Half cycle 60 Hz sine wave or 6 ms rectangular pulse Following any rated load condition and with $V_{RWM} = 0$ following surge.
	270		Half cycle 60 Hz sine wave or 5 ms rectangular pulse
$I^2t$ Maximum $I^2t$ (for fusing)	230	A <sup>2</sup> s	$t = 10$ ms With rated $V_{RWM}$ following surge, initial $T_J \leq 150^\circ\text{C}$ .
	210		$t = 8.3$ ms
	325		$t = 10$ ms With $V_{RWM} = 0$ following surge, initial $T_J \leq 150^\circ\text{C}$ .
	300		$t = 8.3$ ms
$I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for individual device fusing ①	3250	A <sup>2</sup> $\sqrt{s}$	$t = 0.1$ to $10$ ms, initial $T_J \leq 150^\circ\text{C}$ , $V_{RWM} = 0$ following surge.
$V_{FM}$ Maximum peak forward voltage	0.79	V	$T_J = 25^\circ\text{C}$ Rated $I_{F(AV)}$ (10A peak) 180° conduction, rectangular waveform
	0.65		$T_J = 150^\circ\text{C}$
	0.67		$T_J = 25^\circ\text{C}$ 1/2 Rated $I_{F(AV)}$ (5A peak)
$I_{RM}$ Maximum peak reverse current	5	mA	50SQ030 through 50SQ045 $T_J = 25^\circ\text{C}$ , rated $V_{RWM}$
	1		50SQ060 through 50SQ100
	13		50SQ030 through 50SQ045 $T_J = 125^\circ\text{C}$ , rated $V_{RWM}$
	7		50SQ060 through 50SQ100
$I_{RRM}$ Maximum repetitive peak reverse current	0.5 ⑦	A	$T_C = 25^\circ\text{C}$ , $f = 1$ kHz, see fig. 9 for test circuit
$C_t$ Maximum capacitance	1000	pF	50SQ030 through 50SQ045 $T_C = 25^\circ\text{C}$ , $V_R = 5$ Vdc (Test signal in the range of 100 kHz to 1 MHz)
	600		50SQ060 through 50SQ100
dv/dt Maximum rate of reverse voltage application	1000	V/ $\mu\text{s}$	$T_C = 25^\circ\text{C}$ , $V_{RM} = \text{rated } V_{RWM}$

THERMAL-MECHANICAL SPECIFICATIONS

$T_J$ Maximum operating junction temperature range	-65 to 150	°C	
$T_{stg}$ Maximum storage temperature range	-65 to 150	°C	
$R_{thL}$ Maximum thermal resistance, dc operation, junction-to-leads, double side cooling (composite values)	Lead Length = 3.2mm (1/8 in.)	11.0	deg C/W
	= 9.5mm (3/8 in.)	14.7	
	= 19.0mm (3/4 in.)	20.0	
wt Approximate weight	1.5 (0.053)	g (oz.)	
Case Style	C-24		

①  $T_L = -65$  to  $141^\circ\text{C}$ , 180° conduction. ②  $T_L = 0$  to  $141^\circ\text{C}$ , 180° conduction.

③  $T_L = -65$  to  $126^\circ\text{C}$  for lead length ( $l$ ) = 1/8" (3.2 mm) ⑤  
 $T_L = -65$  to  $118^\circ\text{C}$  for lead length ( $l$ ) = 3/8" (9.5 mm) ⑤  
 $T_L = -65$  to  $106^\circ\text{C}$  for lead length ( $l$ ) = 3/4" (19.0 mm) ⑤

④  $l = 9.5$  mm (3/8 in.)  
 ⑤ Length of leads to temperature measurement points (heat sinks).  
 ⑥  $I^2t$  for time  $t_x = I^2\sqrt{t} \cdot \sqrt{t_x}$ .  
 ⑦  $I_{RRM} = 1.0A$  for devices rated 45V or less.

4855452 INTERNATIONAL RECTIFIER  
**IOR** INTERNATIONAL RECTIFIER

55C 05053 D  
 50SQ Series  
 T-03-17




Fig. 1 - Maximum Allowable Lead Temperature Vs. Average Forward Current




Fig. 2 - Maximum Forward Power Loss Vs. Average Forward Current




Fig. 3 - Maximum Instantaneous Forward Voltage Vs. Instantaneous Forward Current




Fig. 4 - Maximum Non-Repetitive Surge Current Vs. Number of Current Pulses




Fig. 5 - Typical Capacitance Vs. Reverse Voltage




Fig. 6 - Maximum Transient Thermal Impedance, Junction-to-Lead Vs. Square Wave Duration

4855452 INTERNATIONAL RECTIFIER  
50SQ Series

55C 05054 D  
INTERNATIONAL RECTIFIER IOR

T-03-17





Fig. 7 - Typical Variation of Reverse Current Vs. Junction Temperature and Reverse Voltage




Fig. 8 - Thermal Nomogram

Notes: A. Maximum allowable heatsink thermal resistance,  $R_{thLA}$ , equals the graph value minus the  $\Delta R_{th}$  factor which allows for instantaneous  $T_J$  excursion. At frequencies above 5000 Hz,  $\Delta R_{th}$  becomes essentially zero and can be ignored.

B. The total power dissipation curves assume the worst case reverse conditions of half wave (180°) rectangular reverse voltage, full rated  $V_{RWM}$ , and  $T_J = 150^\circ\text{C}$ . Lower reverse power losses allow higher operating ambient, smaller heatsinks or larger operating safety margin.

C. Caution: Data assumes that the rectifier is mounted with heatsinks attached to the leads at a maximum of 3/8 of an inch (9.5 mm) from the ends of the body of the rectifier.




Fig. 9 -  $I_{RRM}$  Test Circuit