

Technical Data:


Insertion/withdrawal force per contact: $\leq 10N / \leq 1.6N$
 Mechanical operations: ≥ 500
 Contact resistance: $\leq 1\text{ m}\Omega$
 Operation Temperature: $-55^\circ\text{C} - +125^\circ\text{C}$
 Solder temperature: according JEDEC 020C
 Suitable assembly process: leadfree wave / reflow soldering
 RoHS compliance: yes (6/6)
 Designed for use with: straight female DIN, female 2mm HM connector
 Packaging: antistatic plastic bag
 Packaging unit: 100 pieces per bag
 Marking of packaging: label or direct printed on bag
 required date see ERNI labeling spec. 254792

Current	Cable cross area	AWG
10 A	1.5 mm ²	16
20 A	4 mm ²	12
30 A	6 mm ²	10
40 A	10 mm ²	8

594176	1	40 A	2-4 $\mu\text{mNiP}+$ 0.15 $\mu\text{m Au}$	4.8	5.6	5.2
594174	1	20 A		2.8 -0.5	3.7	4.0
594172	1	10 A		1.8	2.5+0.3	3.0
294761	1	40 A	2 - 3 $\mu\text{m Ni}$ min. 1.3 $\mu\text{m Au}$	4.8	5.6	5.2
053456	1	30 A		3.45+0.1	4.5	4.7+0.6
294760	1	20 A		2.8 -0.5	3.7	4.0
294759	1	10 A		1.8	2.5+0.3	3.0
Part-No.	Class	Current	Plating	Ø A	Ø B	C

Missing informations and dimensions see at DIN 41626

M 2:1



Information:		Tolerances		Scale	5:1
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation	
		www.ERNI.com		High Current Female Contact Hand Solder Termination	
				053316	
H	03.06.2008			I	
Index	Date			A3	
				Class	
				STVSKO	