

REVISIONS

| LTR | DESCRIPTION | DATE (YR-MO-DA) | APPROVED |
|-----|-------------|-----------------|----------|
| | | | |

| | | | | | | | | | | | | | | | | | | | | |
|-------|----|----|----|----|----|----|----|----|----|--|--|--|--|--|--|--|--|--|--|--|
| REV | | | | | | | | | | | | | | | | | | | | |
| SHEET | | | | | | | | | | | | | | | | | | | | |
| REV | | | | | | | | | | | | | | | | | | | | |
| SHEET | | | | | | | | | | | | | | | | | | | | |
| REV | | | | | | | | | | | | | | | | | | | | |
| SHEET | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | | | | | | | | | | | |


| | | | | | | | | | | | | | | | | | | | | |
|----------------------|-------|---|---|---|---|---|---|---|---|---|----|----|----|----|----|--|--|--|--|--|
| REV STATUS OF SHEETS | REV | | | | | | | | | | | | | | | | | | | |
| | SHEET | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | | | | | |

| | | | | | | | | | | | | | | | | | | | |
|--|-----------------------------------|--|--------------------|------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| PMIC N/A | PREPARED BY Thomas M. Hess | DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | | | | | | | | | | | | | | | | | |
| STANDARDIZED MILITARY DRAWING THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE AMSC N/A | CHECKED BY Thomas M. Hess | MICROCIRCUIT, DIGITAL, CMOS, HIGH INTEGRATION EMBEDDED PROCESSOR, MONOLITHIC SILICON | | | | | | | | | | | | | | | | | |
| | APPROVED BY Monica L. Poelking | | | | | | | | | | | | | | | | | | |
| | DRAWING APPROVAL DATE 93-05-12 | SIZE A | CAGE CODE 67268 | 5962-93109 | | | | | | | | | | | | | | | |
| | REVISION LEVEL | SHEET 1 | OF | 23 | | | | | | | | | | | | | | | |

1. SCOPE

1.1 Scope. This drawing forms a part of a one part - one part number documentation system (see 6.6 herein). Two product assurance classes consisting of military high reliability (device classes B, Q, and M) and space application (device classes S and V), and a choice of case outlines and lead finishes are available and are reflected in the Part or Identifying Number (PIN). Device class M microcircuits represent non-JAN class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices". When available, a choice of Radiation Hardness Assurance (RHA) Levels are reflected in the PIN.

1.2 PIN. The PIN shall be as shown in the following example:



1.2.1 RHA designator. Device classes M, B, and S RHA marked devices shall meet the MIL-M-38510 specified RHA levels and shall be marked with the appropriate RHA designator. Device classes Q and V RHA marked devices shall meet the MIL-I-38535 specified RHA levels and shall be marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device.

1.2.2 Device type(s). The device type(s) shall identify the circuit function as follows:

| <u>Device type</u> | <u>Generic number</u> | <u>Circuit function</u> |
|--------------------|-----------------------|-------------------------------------|
| 01 | 80C186EB-8 | High integration embedded processor |
| 02 | 80C186EB-13 | High integration embedded processor |
| 03 | 80C186EB-16 | High integration embedded processor |

1.2.3 Device class designator. The device class designator shall be a single letter identifying the product assurance level as follows:

| <u>Device class</u> | <u>Device requirements documentation</u> |
|---------------------|---|
| M | Vendor self-certification to the requirements for non-JAN class B microcircuits in accordance with 1.2.1 of MIL-STD-883 |
| B or S | Certification and qualification to MIL-M-38510 |
| Q or V | Certification and qualification to MIL-I-38535 |

1.2.4 Case outline(s). The case outline(s) shall be as designated in MIL-STD-1835 and as follows:

| <u>Outline letter</u> | <u>Descriptive designator</u> | <u>Terminals</u> | <u>Package style</u> |
|-----------------------|-------------------------------|------------------|-------------------------|
| X | CMGA5-P88 | 88 | Ceramic, pin grid array |

1.2.5 Lead finish. The lead finish shall be as specified in MIL-M-38510 for classes M, B, and S or MIL-I-38535 for classes Q and V. Finish letter "X" shall not be marked on the microcircuit or its packaging. The "X" designation is for use in specifications when lead finishes A, B, and C are considered acceptable and interchangeable without preference.

| | | | |
|---|-----------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-93109 |
| | | REVISION LEVEL | SHEET 2 |

1.3 Absolute maximum ratings. 1/

| | |
|--|------------------------|
| Storage temperature range | -65°C to +150°C |
| Supply voltage with respect to ground range | -1.0 V dc to +7.0 V dc |
| Voltage on any pin with respect to ground | -1.0 V dc to +7.0 V dc |
| Maximum power dissipation (P _D) | 0.5 W |
| Lead temperature (soldering 10 seconds) | 300°C |
| Thermal resistance, junction-to-case (θ _{JC}): | |
| Case X | See MIL-STD-1835 |
| Maximum junction temperature | 150°C |

1.4 Recommended operating conditions.

| | |
|--|---------------------------------------|
| Case operating temperature range | -55°C to +125°C |
| Supply voltage, V _{CC} | 4.5 V dc ≤ V _{CC} ≤ 5.5 V dc |

1.5 Digital logic testing for device classes Q and V.

| | |
|---|------------|
| Fault coverage measurement of manufacturing logic tests (MIL-STD-883, test method 5012) | 2/ percent |
|---|------------|

2. APPLICABLE DOCUMENTS

2.1 Government specifications, standards, bulletin, and handbook. Unless otherwise specified, the following specifications, standards, bulletin, and handbook of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATIONS

MILITARY

- MIL-M-38510 - Microcircuits, General Specification for.
- MIL-I-38535 - Integrated Circuits, Manufacturing, General Specification for.

STANDARDS

MILITARY

- MIL-STD-480 - Configuration Control-Engineering Changes, Deviations and Waivers.
- MIL-STD-883 - Test Methods and Procedures for Microelectronics.
- MIL-STD-1835 - Microcircuit Case Outlines.

BULLETIN

MILITARY

- MIL-BUL-103 - List of Standardized Military Drawings (SMD's).

HANDBOOK

MILITARY

- MIL-HDBK-780 - Standardized Military Drawings.

(Copies of the specifications, standards, bulletin, and handbook required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.
 2/ Values will be added when they become available.

| | | | |
|---|-----------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-93109 |
| | | REVISION LEVEL | SHEET 3 |

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device class M shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein. The individual item requirements for device classes B and S shall be in accordance with MIL-M-38510 and as specified herein. For device classes B and S, a full electrical characterization table for each device type shall be included in this SMD. The individual item requirements for device classes Q and V shall be in accordance with MIL-I-38535, the device manufacturer's Quality Management (QM) plan, and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 for device classes M, B, and S and MIL-I-38535 for device classes Q and V and herein.

3.2.1 Case outline(s). The case outline(s) shall be in accordance with 1.2.4 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.3 Block diagram. The block diagram(s) shall be as specified on figure 2.

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and postirradiation parameter limits are as specified in table I and shall apply over the full case operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are defined in table I.

3.5 Marking. The part shall be marked with the PIN listed in 1.2 herein. Marking for device class M shall be in accordance with MIL-STD-883 (see 3.1 herein). In addition, the manufacturer's PIN may also be marked as listed in MIL-BUL-103. Marking for device classes B and S shall be in accordance with MIL-M-38510. Marking for device classes Q and V shall be in accordance with MIL-I-38535.

3.5.1 Certification/compliance mark. The compliance mark for device class M shall be a "C" as required in MIL-STD-883 (see 3.1 herein). The certification mark for device classes B and S shall be a "J" or "JAN" as required in MIL-M-38510. The certification mark for device classes Q and V shall be a "QML" as required in MIL-I-38535.

3.6 Certificate of compliance. For device class M, a certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-BUL-103 (see 6.7.3 herein). For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.7.2 herein). The certificate of compliance submitted to DESC-EC prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device class M, the requirements of MIL-STD-883 (see 3.1 herein), or for device classes Q and V, the requirements of MIL-I-38535 and the requirements herein.

3.7 Certificate of conformance. A certificate of conformance as required for device class M in MIL-STD-883 (see 3.1 herein) or device classes B and S in MIL-M-38510 or for device classes Q and V in MIL-I-38535 shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change for device class M. For device class M, notification to DESC-EC of change of product (see 6.2 herein) involving devices acquired to this drawing is required for any change as defined in MIL-STD-480.

3.9 Verification and review for device class M. For device class M, DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

3.10 Microcircuit group assignment for device classes M, B, and S. Device classes M, B, and S devices covered by this drawing shall be in microcircuit group number 105 (see MIL-M-38510, appendix E).

3.11 Serialization for device class S. All device class S devices shall be serialized in accordance with MIL-M-38510.

| | | | |
|---|-----------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-93109 |
| | | REVISION LEVEL | SHEET 4 |

TABLE I. Electrical performance characteristics.

| Test | Symbol | Conditions 1/ -55°C ≤ T _C ≤ +125°C 4.5 V ≤ V _{CC} ≤ 5.5 V unless otherwise specified | Group A subgroups | Device type | Limits | | Unit |
|----------------------------------|------------------|---|----------------------|----------------|---------------------|-----------------------------------|------|
| | | | | | Min | Max | |
| Input low voltage <u>3/</u> | V _{IL} | | 1,2,3 | ALL | -0.5 <u>2/</u> | 0.3 V _{CC} | V |
| Input high voltage | V _{IH} | | 1,2,3 | ALL | .7 V _{CC} | V _{CC} +0.5 <u>2/</u> | V |
| Input hysteresis on RESIN | V _{HYS} | | 1,2,3 | ALL | 0.5 | | V |
| Output low voltage | V _{OL} | I _{OL} = 3.0 mA V _{CC} = 4.5 V | 1,2,3 | ALL | | 0.45 | V |
| Output high voltage | V _{OH} | I _{OH} = -2.0 mA V _{CC} = 4.5 V | 1,2,3 | ALL | V _{CC} -.5 | | V |
| Input Leakage current | I _{LI} | 0 V ≤ V _{IN} ≤ V _{CC} V _{CC} = 5.5 V PIN = CLKIN | 1,2,3 | ALL | | +50 | μA |
| | | V _{IN} = 0 V PIN = ERROR V _{CC} = 5.5 V | 1,2,3 | ALL | -7 | -.275 | mA |
| | | V _{IN} = V _{CC} PIN = PEREQ V _{CC} = 5.5 V | 1,2,3 | ALL | .275 | 7 | mA |
| | | V _{IN} = .7V _{CC} PINS = A19/ONCE A16-A18, LOCK V _{CC} = 5.5 V <u>11/</u> | 1,2,3 | ALL | -.275 | - 5 | mA |
| | | 0 V ≤ V _{IN} ≤ V _{CC} ALL OTHER INPUTS V _{CC} = 5.5 V | 1,2,3 | ALL | | +15 | μA |
| Output leakage current <u>4/</u> | I _{LO} | .45 V ≤ V _{IN} ≤ V _{CC} V _{CC} = 5.5 V | 1,2,3 | ALL | -15 | +15 | μA |

See footnotes at end of table.

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-93109

REVISION LEVEL

SHEET

5

TABLE I. Electrical performance characteristics - Continued.

| Test | Symbol | Conditions ^{1/} -55°C ≤ T _C ≤ +125°C 4.5 V ≤ V _{CC} ≤ 5.5 V unless otherwise specified | Group A subgroups | Device type | Limits | | Unit |
|---------------------------------------|-----------------|--|----------------------|----------------|--------------------------|-------------------|------|
| | | | | | Min | Max | |
| Supply current cold (RESET) <u>5/</u> | I _{CC} | V _{CC} = 5.5 V | 1,2,3 | 01 02 03 | | 45 73 90 | mA |
| Supply current idle <u>6/</u> | I _{ID} | V _{CC} = 5.5 V | 1,2,3 | 01 02 03 | | 31 48 63 | mA |
| Supply current power down <u>7/</u> | I _{PD} | V _{CC} = 5.5 V | 1,2,3 | ALL | | 100 | μA |
| Input capacitance | C _{IN} | Frequency = 1 MHz See 4.4.1c | 4 | ALL | | 15 | pF |
| Input/output capacitance | C _O | Frequency = 1 MHz See 4.4.1c | 4 | ALL | | 15 | pF |
| Functional test | | See 4.4.1b | 7,8 | ALL | | | |
| CLKIN frequency | t _F | | 9,10,11 | 01 02 03 | 0 0 0 <u>2/</u> | 16 26.08 32 | MHz |
| CLKIN period | t _C | See figure 3 V _{CC} = 4.5 V | 9,10,11 | 01 02 03 | 62.5 38.34 31.25 | | ns |
| CLKIN high time | t _{CH} | At V _{IH} See figure 3 V _{CC} = 4.5 V | 9,10,11 | 01 02 03 | 15 12 10 | | ns |
| CLKIN low time | t _{CL} | At V _{IL} See figure 3 V _{CC} = 4.5 V | 9,10,11 | 01 02 03 | 15 12 10 | | ns |
| CLKIN rise time <u>2/</u> | t _{CR} | See figure 3 V _{CC} = 4.5 V | 9,10,11 | ALL | 1 | 8 | ns |
| CLKIN fall time <u>2/</u> | t _{CF} | V _{CC} = 4.5 V See figure 3 | 9,10,11 | ALL | 1 | 8 | ns |

See footnotes at end of table.

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-93109

REVISION LEVEL

SHEET

6

TABLE I. Electrical performance characteristics - Continued.

| Test | Symbol | Conditions 1/ -55°C ≤ T _C ≤ +125°C 4.5 V ≤ V _{CC} ≤ 5.5 V unless otherwise specified | Group A subgroups | Device type | Limits | | Unit | |
|---|--------------------|---|----------------------|----------------|--------|-------------|------------------|----|
| | | | | | Min | Max | | |
| CLKIN to CLKOUT delay | t _{CD} | See figure 3 V _{CC} = 4.5 V | 9,10,11 | 01 | 0 | 27 | ns | |
| | | | | 02 | 0 | 23 | | |
| | | | | 03 | 0 | 20 | | |
| CLKOUT period | t | | | 9,10,11 | ALL | | 2*t _c | ns |
| CLKOUT high time | t _{PH} | | | 9,10,11 | ALL | (t/2) -5 | (t/2) +5 | ns |
| CLKOUT low time | t _{PL} | | | 9,10,11 | ALL | (t/2) -5 | (t/2) +5 | ns |
| CLKOUT rise time | t _{PR} | | | 9,10,11 | ALL | | 6 | ns |
| CLKOUT fall time | t _{PF} | | | 9,10,11 | ALL | | 6 | ns |
| CLKOUT high to output valid ALE, S2:0, DEN, DT/R, BHE, LOCK, A19:16 8/ | t _{CHOV1} | | | 9,10,11 | 01 | 1 | 30 | ns |
| | | | 02 | | 1 | 25 | | |
| | | 03 | 1 | | 22 | | | |
| CLKOUT high to output valid GCSO:7, LCS, UCS, NCS, RD, WR 9/ | t _{CHOV2} | | 9,10,11 | 01 | 1 | 35 | ns | |
| | | 02 | | 1 | 30 | | | |
| | | 03 | | 1 | 27 | | | |
| CLKOUT low to output valid BHE, DEN, LOCK, RESOUT, HLDA, TQOUT, TOUT, A19:16 | t _{CLOV1} | | 9,10,11 | 01 | 1 | 30 | ns | |
| | | 02 | | 1 | 25 | | | |
| | | 03 | | 1 | 22 | | | |
| CLKOUT low to output valid RD, WR, GCSO:7, LCS, UCS, AD15:0, NCS, INTA1:0, S2:0 | t _{CLOV2} | | 9,10,11 | 01 | 1 | 35 | ns | |
| | | 02 | | 1 | 30 | | | |
| | | 03 | | 1 | 27 | | | |
| CLKOUT high to output float RD, WR, BHE, DT/R, LOCK, S2:0, A9:16 2/ | t _{CHOF} | | 9,10,11 | 01 | 0 | 30 | ns | |
| | | 02 | | 0 | 25 | | | |
| | | 03 | | 0 | 25 | | | |

See footnotes at end of table.

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-93109

REVISION LEVEL

SHEET

7

TABLE I. Electrical performance characteristics - Continued.

| Test | Symbol | Conditions 1/ -55°C ≤ T _C ≤ +125°C 4.5 V ≤ V _{CC} ≤ 5.5 V unless otherwise specified | Group A subgroups | Device type | Limits | | Unit |
|---|-------------------|---|----------------------|----------------|--------------|----------------|------|
| | | | | | Min | Max | |
| CLKOUT low to output float DEN, AD15:0 2/ | t _{CLOF} | See figure 3 V _{CC} = 4.5 V | 9,10,11 | 01 02 03 | 0 0 0 | 35 25 25 | ns |
| CLKOUT high to input setup test, NMI, INT4:0, BCLK1:0, T1:0IN, READY, CTS1:0, P2.6, P2.7 | t _{CHIS} | | 9,10,11 | ALL | 10 | | ns |
| CLKOUT high to input hold test, NMI, INT4:0, BCLK1:0, T1:0IN, READY, CTS1:0 | t _{CHIH} | | 9,10,11 | ALL | 3 | | ns |
| CLKOUT low to input setup AD15:0, READY, HOLD, PEREQ, ERROR | t _{CLIS} | | 9,10,11 | ALL | 10 | | ns |
| CLKOUT high to input hold AD15:0, READY, HOLD, PEREQ, ERROR | t _{CLIH} | | 9,10,11 | ALL | 3 | | ns |
| ALE high to ALE low | t _{LHLL} | | 9,10,11 | ALL | t-15 | | ns |
| ADD valid to ALE low | t _{AVLL} | | 9,10,11 | ALL | (t/2) -10 | | ns |
| CHIP selects valid to ALE low | t _{PLLL} | | 9,10,11 | ALL | (t/2) -10 | | ns |
| ADD hold from ALE low | t _{LLAX} | | 9,10,11 | ALL | (t/2) -10 | | ns |
| ALE low to WR low | t _{LLWL} | | 9,10,11 | ALL | (t/2) -15 | | ns |
| ALE low to RD low | t _{LLRL} | | 9,10,11 | ALL | (t/2) -15 | | ns |

See footnotes at end of table.

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-93109

REVISION LEVEL

SHEET

8

TABLE I. Electrical performance characteristics - Continued.

| Test | Symbol | Conditions 1/ -55°C ≤ T _C ≤ +125°C 4.5 V ≤ V _{CC} ≤ 5.5 V unless otherwise specified | Group A subgroups | Device type | Limits | | Unit |
|---------------------------------|-------------------|---|----------------------|----------------|--------------|------|------|
| | | | | | Min | Max | |
| WR high to ALE high | t _{WHLH} | See figure 3 V _{CC} = 4.5 V | 9,10,11 | ALL | (t/2) -10 | | ns |
| Add float to RD low 2/ | t _{AFRL} | | 9,10,11 | ALL | 0 | | ns |
| RD low to RD high | t _{RLRH} | | 9,10,11 | ALL | (2t)-5 | | ns |
| WR low to WR high | t _{WLWH} | | 9,10,11 | ALL | (2t)-5 | | ns |
| RD high to add ACTIVE | t _{RHAV} | | 9,10,11 | ALL | t-15 | | ns |
| DATA out hold after WR high | t _{WHDX} | | 9,10,11 | ALL | t-15 | | ns |
| WR high to CS high | t _{WHPH} | | 9,10,11 | ALL | (t/2) -10 | | ns |
| RD high to CS high | t _{RHPH} | | 9,10,11 | ALL | (t/2) -10 | | ns |
| CS active to CS active | t _{PHPL} | | 9,10,11 | ALL | (t/2) -10 | | ns |
| ONCE active to RESIN high 2/ | t _{OVRH} | | 9,10,11 | ALL | t | | ns |
| ONCE hold from RESIN high 2/ | t _{RHOX} | | 9,10,11 | ALL | t | | ns |
| TXD clock period 10/ | t _{XLXL} | | 9,10,11 | ALL | t*(n+1) | | ns |
| TXD CLK low to high (n > 1) 10/ | t _{XLXH} | | 9,10,11 | ALL | t-35 | t+35 | ns |
| TXD CLK low to high (n = 1) 10/ | t _{XLXH} | | 9,10,11 | ALL | t-35 | t+35 | ns |

See footnotes at end of table.

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-93109

REVISION LEVEL

SHEET

9

TABLE I. Electrical performance characteristics - Continued.

| Test | Symbol | Conditions ^{1/} -55°C ≤ T _C ≤ +125°C 4.5 V ≤ V _{CC} ≤ 5.5 V unless otherwise specified | Group A subgroups | Device type | Limits | | Unit |
|--|-------------------|--|----------------------|----------------|----------------|---------|------|
| | | | | | Min | Max | |
| TXD CLK high to low (n > 1) <u>10/</u> | t _{XHXL} | See figure 3 V _{CC} = 4.5 V | 9,10,11 | ALL | (n-1)*t | (n-1)*t | ns |
| TXD CLK high to low (n = 1) <u>10/</u> | t _{XHXL} | | 9,10,11 | ALL | t-35 | t+35 | ns |
| RXD output data setup to TXD CLK high (n > 1) <u>10/</u> | t _{QVXH} | | 9,10,11 | ALL | (n-1)*t -35 | | ns |
| RXD output data setup to TXD CLK high (n = 1) <u>10/</u> | t _{QVXH} | | 9,10,11 | ALL | t-35 | | ns |
| RXD output data hold after TXD CLK high (n > 1) <u>10/</u> | t _{XHQX} | | 9,10,11 | ALL | 2t-35 | | ns |
| RXD output data hold after TXD CLK high (n = 1) <u>10/</u> | t _{XHQX} | | 9,10,11 | ALL | t-35 | | ns |
| RXD output data float after last TXD CLK high <u>2/</u> | t _{XHQZ} | | 9,10,11 | ALL | | t+20 | ns |
| RXD output data setup to TXD CLK high | t _{DVXH} | | 9,10,11 | ALL | t+20 | | ns |
| RXD input data hold after TXD CLK high <u>2/</u> | t _{XHDX} | | 9,10,11 | ALL | 0 | | ns |

1/ All testing to be performed to worst-case test conditions unless otherwise specified. All timings are measured at 50% of V_{CC}, except rise and fall times, which are measured between 20% and 80% of V_{CC}. All pins are loaded to 50 pF. The following pins are active low: DEN, SO, S1, S2, BHE, WR, RD, ERROR, NCS, CTS1(P2.4/CTS1), CTS0, RESIN, UCS, LCS, GCS0(P1.0/GCS0), GCS1(P1.1/GCS1), GCS3(P1.2/GCS3), GCS3(P1.3/GCS3), GCS4(P1.4/GCS4), GCS5(P1.0/GCS5), GCS6(P1.1/GCS6), GCS7(P1.2/GCS7), R(DRT/R), LOCK, and TEST(TEST/BUSY).

2/ Guaranteed by design characterization but not tested.

3/ A16-A18, A19/ONCE, LOCK are not tested or guaranteed at this level.

4/ Pins being floated by invoking the ONCE mode or by asserting HOLD. OSCOUT is not tested.

5/ Measured with device in reset and at worst case frequency, V_{CC}, and with all outputs loaded to 50 pF. All floating outputs are driven to V_{CC} or ground.

6/ Device in HALT (idle mode active) and worst case frequency, V_{CC}, and temperature with all outputs loaded to 50 pF. All floating outputs are driven to V_{CC} or ground.

7/ Device in HALT (power down mode active) and worst case frequency, V_{CC}, and temperature with all outputs loaded to 50 pF. All floating outputs are driven to V_{CC} or ground.

8/ t_{CHOV1} applies to BHE, LOCK, and A19:16 only after a HOLD release.

9/ t_{CHOV2} applies to RD and WR only after a HOLD release.

10/ n is the value of the BxCMP register ignoring the I_{CLK} Bit (i.e., I_{CLK} = 0).

11/ These pins have an internal pull-up device that is active while RESIN is low and ONCE mode is not active. Sourcing more current than specified (on any of these pins) may invoke a factory tested mode.

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-93109

REVISION LEVEL

SHEET

10

| Pin | Name | Pin | Name | Pin | Name | Pin | Name |
|-----|-----------------|-----|-----------------|-----|-----------------|-----|-----------------|
| 1A | DEN# | 1M | AD5 | 12N | N/C | 13B | N/C |
| 2B | SO# | 1N | AD12 | 13N | RXD0 | 13A | INT1 |
| 1B | S1# | 2N | AD4 | 13M | TXD0 | 12A | INT0 |
| 2C | S2# | 3M | AD11 | 12L | CTS0# | 11B | UCS# |
| 1C | BHE# | 3N | AD3 | 13L | P2.6 | 11A | LCS# |
| 2D | ALE | 4M | AD10 | 12K | P2.7 | 10B | P1.0/GCS0# |
| 1D | WR# | 4N | AD2 | 13K | T1IN | 10A | P1.1/GCS1# |
| 2E | RD# | 5M | AD9 | 12J | T1OUT | 9B | P1.2/GCS2# |
| 1E | ERROR# | 5N | AD1 | 13J | T0IN | 9A | P1.3/GCS3# |
| 2F | V _{SS} | 6M | V _{SS} | 12H | T0OUT | 8B | P1.4/GCS4# |
| 1F | V _{CC} | 6N | V _{CC} | 13H | CLKOUT | 8A | V _{CC} |
| 2G | V _{SS} | 7M | V _{SS} | 12G | V _{SS} | 7B | V _{SS} |
| 1G | A19 /ONCE# | 7N | N/C | 13G | V _{CC} | 7A | P1.5/GCS5# |
| 2H | A18 | 8M | AD8 | 12F | CLKIN | 6B | P1.6/GCS6# |
| 1H | A17 | 8N | AD0 | 13F | OSCOU | 6A | P1.7/GCS7# |
| 2J | A16 | 9M | NCS# | 12E | PEREQ | 5B | READY |
| 1J | AD15 | 9N | P2.2/B CLK1 | 13E | RESOUT | 5A | NMI |
| 2K | AD7 | 10M | P2.1/T XD1 | 12D | RESIN# | 4B | DRT/R# |
| 1K | AD14 | 10N | P2.0/R XD1 | 13D | PDTMR | 4A | LOCK# |
| 2L | AD6 | 11M | P2.4/C TS1# | 12C | INT4 | 3B | TEST#/BUSY |
| 1L | AD13 | 11N | P2.3/S INT1 | 13C | INT3 | 3A | HOLD |
| 2M | N/C | 12M | P2.5/B LCKO | 12B | INT2 | 2A | HLDA |

- Indicates an active low signal

FIGURE 1. Terminal connections.

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-93109

REVISION LEVEL

SHEET

11




FIGURE 2. Block diagram.

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444


SIZE
A

5962-93109

REVISION LEVEL

SHEET

12



$C_L = 50 \text{ pF}$ for all signals





FIGURE 3. Timing waveforms.

| | | | |
|---|-----------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-93109 |
| | | REVISION LEVEL | SHEET 13 |

Output delay and float waveform



NOTE: $20\% V_{CC} < \text{FLOAT} < 80\% V_{CC}$.

Input setup and hold




FIGURE 3. Timing waveforms - Continued.

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-93109

REVISION LEVEL

SHEET www.DataSheet4U.com

14





FIGURE 3. Timing waveforms - Continued.

| | | | |
|---|-----------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-93109 |
| | | REVISION LEVEL | SHEET 15 |

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. For device class M, sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein). For device classes B and S, sampling and inspection procedures shall be in accordance with MIL-M-38510 and method 5005 of MIL-STD-883, except as modified herein. For device classes Q and V, sampling and inspection procedures shall be in accordance with MIL-I-38535 and the device manufacturer's QM plan.

4.2 Screening. For device class M, screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. For device classes B and S, screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to qualification and quality conformance inspection. For device classes Q and V, screening shall be in accordance with MIL-I-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection.

4.2.1 Additional criteria for device classes M, B, and S.

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition D. For device class M, the test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. For device classes B and S, the test circuit shall be submitted to the qualifying activity. For device classes M, B, and S, the test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015.

(2) $T_A = +125^\circ\text{C}$, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein.

4.2.2 Additional criteria for device classes Q and V.

a. The burn-in test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-I-38535. The burn-in test circuit shall be maintained under document revision level control of the device manufacturer's Technology Review Board (TRB) in accordance with MIL-I-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015.

b. Interim and final electrical test parameters shall be as specified in table II herein.

c. Additional screening for device class V beyond the requirements of device class Q shall be as specified in appendix B of MIL-I-38535.

4.3 Qualification inspection.

4.3.1 Qualification inspection for device classes B and S. Qualification inspection for device classes B and S shall be in accordance with MIL-M-38510. Inspections to be performed shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.5).

4.3.2 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-I-38535. Inspections to be performed shall be those specified in MIL-I-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.5).

4.4 Conformance inspection. Quality conformance inspection for device class M shall be in accordance with MIL-STD-883 (see 3.1 herein) and as specified herein. Quality conformance inspection for device classes B and S shall be in accordance with MIL-M-38510 and as specified herein. Inspections to be performed for device classes M, B, and S shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.5). Technology conformance inspection for classes Q and V shall be in accordance with MIL-I-38535 including groups A, B, C, D, and E inspections and as specified herein except where option 2 of MIL-I-38535 permits alternate in-line control testing.

| | | | |
|---|-----------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-93109 |
| | | REVISION LEVEL | SHEET 16 |

4.4.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. For device class M, subgroups 7 and 8 tests shall be sufficient to verify the functionality of the device. For device classes B and S, subgroups 7 and 8 tests shall be sufficient to verify the truth table as approved by the qualifying activity. For device classes Q and V, subgroups 7 and 8 shall include verifying the functionality of the device. These tests shall have been fault graded in accordance with MIL-STD-883, test method 5012 (see 1.5 herein).
- c. Subgroup 4 (C_{IN} and C_O) shall be measured only for the initial test and after process or design changes which may affect capacitance. A minimum sample size of 5 devices with zero rejects shall be required.

TABLE II. Electrical test requirements.

| Test requirements | Subgroups (in accordance with MIL-STD-883, method 5005, table I) | | | Subgroups (in accordance with MIL-I-38535, table III) | |
|--|--|---------------------------------|---------------------------------|---|---------------------------------|
| | Device class M | Device class B | Device class S | Device class Q | Device class V |
| Interim electrical parameters (see 4.2) | | | | | |
| Final electrical parameters (see 4.2) | 1,2,3,7,8,9 10,11 <u>1/</u> | 1,2,3,7,8, 9,10,11 <u>1/</u> | 1,2,3,7,8, 9,10,11 <u>2/</u> | 1,2,3,7,8, 9,10,11 <u>1/</u> | 1,2,3,7,8, 9,10,11 <u>2/</u> |
| Group A test requirements (see 4.4) | 1,2,3,4,7,8 9,10,11 | 1,2,3,4,7,8 9,10,11 | 1,2,3,4,7,8 9,10,11 | 1,2,3,4,7,8 9,10,11 | 1,2,3,4,7,8 9,10,11 |
| Group B end-point electrical parameters (see 4.4) | | | 2,8A,10 | | |
| Group C end-point electrical parameters (see 4.4) | 2,8A,10 | 2,8A,10 | | 2,8A,10 | 2,8A,10 |
| Group D end-point electrical parameters (see 4.4) | 2,8A,10 | 2,8A,10 | 2,8A,10 | 2,8A,10 | 2,8A,10 |
| Group E end-point electrical parameters (see 4.4) | | | | | |

1/ PDA applies to subgroup 1.

2/ PDA applies to subgroups 1 and 7.

4.4.2 Group B inspection. The group B inspection end-point electrical parameters shall be as specified in table II herein. For device class S steady-state life tests, the test circuit shall be submitted to the qualifying activity.

4.4.3 Group C inspection. The group C inspection end-point electrical parameters shall be as specified in table II herein.

| | | | |
|---|-----------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-93109 |
| | | REVISION LEVEL | SHEET 17 |

4.4.3.1 Additional criteria for device classes M and B. Steady-state life test conditions, method 1005 of MIL-STD-883:

- a. Test condition D. For device class M, the test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. For device class B, the test circuit shall be submitted to the qualifying activity. For device classes M and B, the test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005.
- b. $T_A = +125^\circ\text{C}$, minimum.
- c. Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

4.4.3.2 Additional criteria for device classes Q and V. The steady-state life test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-I-38535. The test circuit shall be maintained under document revision level control by the device manufacturer's TRB in accordance with MIL-I-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005.

4.4.4 Group D inspection. The group D inspection end-point electrical parameters shall be as specified in table II herein.

4.4.5 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein). RHA levels for device classes B, S, Q, and V shall be M, D, R, and H and for device class M shall be M and D.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. For device classes M, B, and S, the devices shall be subjected to radiation hardness assured tests as specified in MIL-M-38510 for the RHA level being tested. For device classes Q and V, the devices or test vehicle shall be subjected to radiation hardness assured tests as specified in MIL-I-38535 for the RHA level being tested. All device classes must meet the postirradiation end-point electrical parameter limits as defined in table I at $T_A = +25^\circ\text{C} \pm 5^\circ\text{C}$, after exposure, to the subgroups specified in table II herein.
- c. When specified in the purchase order or contract, a copy of the RHA delta limits shall be supplied.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510 for device classes M, B, and S and MIL-I-38535 for device classes Q and V.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.1.2 Substitutability. Device classes B and Q devices will replace device class M devices.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished in accordance with MIL-STD-481 using DD Form 1693, Engineering Change Proposal (Short Form).

6.3 Record of users. Military and industrial users shall inform Defense Electronics Supply Center when a system application requires configuration control and which SMD's are applicable to that system. DESC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DESC-EC, telephone (513) 296-6047.

6.4 Comments. Comments on this drawing should be directed to DESC-EC, Dayton, Ohio 45444, or telephone (513) 296-5377.

| | | | |
|---|-----------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-93109 |
| | | REVISION LEVEL | SHEET 18 |

6.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-M-38510 and MIL-STD-1331.

TABLE III. Pin descriptions.

| Name | Type | Description |
|-------------------------------|--------------------------------------|--|
| V_{CC} | | Power connections consist of four pins which must be shorted externally to a V_{CC} board plane. |
| V_{SS} | | Ground connections consist of six pins which must be shorted externally to a V_{SS} board plane. |
| CLKIN | 1 | Clock input is an input for an external clock. An external oscillator operating at two times the required M80C186EB operating frequency can be connected to CLKIN. For crystal operation, CLKIN (along with OSCOUT) are the crystal connections to an internal Pierce oscillator. |
| CLKIN | I A(E) | Clock input is an input for an external clock. An external oscillator operating at two times the required M80C186EB operating frequency can be connected to CLKIN. For crystal operation, CLKIN (along with OSCOUT) are the crystal connections to an internal Pierce oscillator. |
| OSCOUT | 0 H(Q) R(Q) P(Q) | Oscillator output is only used when using a crystal to generate the external clock. OSCOUT (along with CLKIN) are the crystal connections to an internal Pierce oscillator. This pin is not to be used as 2X clock output for non-crystal applications (i.e., this pin is N.C. for non-crystal applications). OSCOUT does not float in ONCE mode. |
| CLKOUT | 0 H(Q) R(Q) P(Q) | Clock output provides a timing reference for inputs and outputs of the processor, and is one-half the input clocks (CLKIN) frequency. CLKOUT has a 50% duty cycle and transitions every falling edge of CLKIN. |
| $\overline{\text{RESIN}}$ | I A(L) | Reset in causes the M80C186EB to immediately terminate any bus cycle in progress and assume an initialized state. All pins will be driven to a known state, and RESOUT will also be driven active. The rising edge (low-to-high) transition synchronizes CLKOUT when CLKIN before the M80C186EB begins fetching opcodes at memory location OFFFOH. |
| RESOUT | 0 H(O) R(1) P(O) | Reset output that indicates the M80C186EB is currently in the reset state. RESOUT will remain active as long as RESIN remains active. |
| PDTMR | I/O A(L) H(WH) R(Z) P(1) | Power-down timer pin (normally connected to an external capacitor) that determines the amount of time the M80C186EB waits after an exit from power down before resuming normal operation. The duration of time required will depend on the startup characteristics of the crystal oscillator. |
| NMI | I A(E) | Non-maskable interrupt input causes a type-2 interrupt to be serviced by the CPU. NMI is latched internally. |
| $\overline{\text{TEST/BUSY}}$ | I | TEST is used during the execution of the WAIT instruction to suspend CPU operation until the pin is sampled active (LOW). $\overline{\text{TEST}}$ is alternately known as BUSY when interfacing with an M80C187 numerics coprocessor. |

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-93109

REVISION LEVEL

SHEET www.DataSheet4U.com

19

TABLE III. Pin descriptions - Continued.

| Name | Type | Description | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------------------|-------------------------------------|---|---------------------------|-----|----------|-----------|---|---------------|---|---------------------|--------------------|---|---|-----------------------|---|---|-------------------|----------|---|---|---|-----------|---|---|---|----------------|---|---|---|-------------------------|---|---|---|-------------|---|---|---|--------------|---|---|---|---------------------------|
| AD15:0 | I/O S(L) H(Z) R(Z) P(X) | These pins provide a multiplexed Address and Data bus. During the address phase of the bus cycle, address bits 0 through 15 are presented on the bus and can be latched using ALE. 8- or 16-bit data information is transferred during the data phase of the bus cycle. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A18:16 A19/ONCE | H(Z) R(WH) P(X) | These pins provide multiplexed Address during the address phase of the bus cycle. Address bits 16 through 19 are presented on these pins and can be latched using ALE. These pins are driven to a logic 0 during the data phase of the bus cycle. During a processor reset (RESIN) active, A19/ONCE is used to enable ONCE mode. A18:16 must not be driven low during reset or improper M80C186EB. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| $\overline{S2:0}$ | 0 H(Z) R(Z) P(1) | Bus cycle Status are encoded on these pins to provide bus transaction information. $\overline{S2:0}$ are encoded as follows: <table border="1"> <thead> <tr> <th>S2</th> <th>S1</th> <th>S0</th> <th>Bus Cycle</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0</td> <td>0</td> <td>Bus Cycle initiated</td> </tr> <tr> <td>0</td> <td>0</td> <td>1</td> <td>Interrupt Acknowledge</td> </tr> <tr> <td>0</td> <td>1</td> <td>0</td> <td>Read I/O</td> </tr> <tr> <td>0</td> <td>1</td> <td>1</td> <td>Write I/O</td> </tr> <tr> <td>1</td> <td>0</td> <td>0</td> <td>Processor HALT</td> </tr> <tr> <td>1</td> <td>0</td> <td>1</td> <td>Queue Instruction Fetch</td> </tr> <tr> <td>1</td> <td>1</td> <td>0</td> <td>Read Memory</td> </tr> <tr> <td>1</td> <td>1</td> <td>1</td> <td>Write Memory</td> </tr> <tr> <td>1</td> <td>1</td> <td>1</td> <td>Passive (no bus activity)</td> </tr> </tbody> </table> | S2 | S1 | S0 | Bus Cycle | 0 | 0 | 0 | Bus Cycle initiated | 0 | 0 | 1 | Interrupt Acknowledge | 0 | 1 | 0 | Read I/O | 0 | 1 | 1 | Write I/O | 1 | 0 | 0 | Processor HALT | 1 | 0 | 1 | Queue Instruction Fetch | 1 | 1 | 0 | Read Memory | 1 | 1 | 1 | Write Memory | 1 | 1 | 1 | Passive (no bus activity) |
| S2 | S1 | S0 | Bus Cycle | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 0 | 0 | Bus Cycle initiated | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 0 | 1 | Interrupt Acknowledge | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 1 | 0 | Read I/O | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 1 | 1 | Write I/O | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 0 | 0 | Processor HALT | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 0 | 1 | Queue Instruction Fetch | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 1 | 0 | Read Memory | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 1 | 1 | Write Memory | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 1 | 1 | Passive (no bus activity) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ALE | 0 H(O) R(O) P(O) | Address Latch Enable output is used to strobe address information into a transparent type latch during the address phase of the bus cycle. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| \overline{BHE} | 0 H(Z) R(Z) P(X) | Byte High Enable output to indicate that the bus cycle in progress is transferring data over the upper half of the data bus. BHE and A0 have the following logical encoding: <table border="1"> <thead> <tr> <th>A0</th> <th>BHE</th> <th>Encoding</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0</td> <td>Word Transfer</td> </tr> <tr> <td>0</td> <td>1</td> <td>Even Byte Transfer</td> </tr> <tr> <td>1</td> <td>0</td> <td>Odd Byte Transfer</td> </tr> <tr> <td>1</td> <td>1</td> <td>Refresh Operation</td> </tr> </tbody> </table> | A0 | BHE | Encoding | 0 | 0 | Word Transfer | 0 | 1 | Even Byte Transfer | 1 | 0 | Odd Byte Transfer | 1 | 1 | Refresh Operation | | | | | | | | | | | | | | | | | | | | | | | | | |
| A0 | BHE | Encoding | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 0 | Word Transfer | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 1 | Even Byte Transfer | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 0 | Odd Byte Transfer | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 1 | Refresh Operation | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| \overline{RD} | 0 H(Z) R(Z) P(1) | READ output signals that the accessed memory or I/O device must drive data information onto the data bus. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| \overline{WR} | 0 H(Z) R(Z) P(1) | WRITE output signals that data available on the data bus are to be written into the accessed memory or I/O device. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| READY | I A(L) S(L) | READY input to signal the completion of a bus cycle. READY must be active to terminate any M80C186EB bus cycle, unless it is ignored by correctly programming the Chip-Select Unit. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| \overline{DEN} | 0 H(Z) R(Z) P(1) | Data Enable output to control the enable of bi-directional transceivers when buffering a M80C186EB system. DEN is active only when data is to be transferred on the bus. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-93109

REVISION LEVEL

SHEET

20

TABLE III. Pin descriptions - Continued.

| Name | Type | Description |
|--|-------------------------------------|--|
| DT/ \bar{R} | 0 H(Z) R(Z) P(X) | Data Transmit/Receive output controls the direction of a bi-directional buffer when buffering an M80C186EB system. |
| \bar{LOCK} | I/O H(Z) R(WH) P(1) | LOCK output indicates that the bus cycle in progress is not to be interrupted. The M80C186EB will not service other bus requests (such as HOLD) while LOCK is active. This pin is configured as a weakly held high input while RESIN is active and must not be driven low. |
| HOLD | I A(L) | HOLD request input to signal that an external bus master wishes to gain control of the local bus. The M80C186EB will relinquish control of the local bus between instruction boundaries not conditioned by a LOCK prefix. |
| HLDA | 0 H(1) R(O) P(O) | Hold Acknowledge output to indicate that the M80C186EB has relinquish control of the local bus. When HLDA is asserted, the M80C186EB will (or has) floated its data bus and control signals allowing another bus master to drive the signal directly. |
| \bar{NCS} | 0 H(1) R(1) P(1) | Numerics Coprocessor Select output is generated when accessing a numerics coprocessor. |
| \bar{ERROR} | I A(L) | ERROR input that indicates the last numerics coprocessor operation resulted in an exception condition. An interrupt TYPE 16 is generated if ERROR is sampled active at the beginning of a numerics operation. |
| PEREQ | I A(L) | Co-Process Request signals that a data transfer between an External Numerics Coprocessor and Memory is pending. |
| \bar{UCS} | 0 H(1) R(1) P(1) | Upper Chip Select will go active whenever the address of a memory or I/O bus cycle is within the address limitations programmed by the user. After reset, UCS is configured to be active for memory accesses between OFFC00H and OFFFFH. |
| \bar{LCS} | Q H(1) R(1) P(1) | Lower Chip Select will go active whenever the address of a memory bus cycle is within the address limitations programmed by the user. LCS is inactive after a reset. |
| P1.0/ $\bar{GCS0}$ P1.1/ $\bar{GCS1}$ P1.2/ $\bar{GCS2}$ P1.3/ $\bar{GCS3}$ P1.4/ $\bar{GCS4}$ P1.5/ $\bar{GCS5}$ P1.6/ $\bar{GCS6}$ P1.7/ $\bar{GCS7}$ | 0 H(X)/H(1) R(1) P(X)/P(1) | These pins provide a multiplexed function. If enabled, each pin can provide a Generic Chip Select output which will go active whenever the address of a memory or I/O bus cycle is within the address limitations programmed by the user. When not programmed as a Chip Select, each pin may be used as a general purpose output Port. As an output port pin, the value of the pin can be read internally. |
| T0OUT T1OUT | 0 H(Q) R(1) P(Q) | Timer Output pins can be programmed to provide a single clock or continuous waveform generation, depending on the time mode selected. |

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-93109

REVISION LEVEL

SHEET www.DataSheet4U.com
21

TABLE III. Pin descriptions - Continued.

| Name | Type | Description |
|--|---|--|
| TOIN T1IN | I A(L) A(E) | Timer Input is used either as clock or control signals, depending on the timer mode selected. |
| INT0 INT1 INT4 | I A(E,L) | Maskable Interrupt input will cause a vector to a specific type interrupt routine. To allow interrupt expansion. INT0 and/or INT1 can be used with INTA0 and INTA1 to interface with an external slave controller. |
| INT2/ <u>INTA0</u> INT3/ <u>INTA1</u> | I/O A(E,L) /H(1) R(Z) /P(1) | These pins provide a multiplexed function. As inputs, they provide a maskable interrupt that will cause the CPU to vector to a specific type interrupt routine. As outputs, each is programmatically controlled to provide an INTERRUPT ACKNOWLEDGE handshake signal to allow interrupt expansion. |
| P2.7 P2.6 | I/O A(L) H(X) R(Z) P(X) | Bi-directional, open-drain Port pins. |
| <u>CTS0</u> P2.4/ <u>CTS1</u> | I A(L) | Clear-To-Send input is used to prevent the transmission of serial data on their respective TXD signal pin. CTS1 is multiplexed with an input only port function. |
| TXD0 P2.1/ <u>TXD1</u> | O H(X)/H(Q) R(1) P(X)/P(Q) | Transmit Data output provides serial data information. TXD1 is multiplexed with an output only Port function. During synchronous serial communications, TXD will function as a clock output. |
| RXD0 P2.0/ <u>RXD1</u> | I/O A(L) R(Z) H(Q) P(X) | Receive Data input accepts serial data information. RXD1 is multiplexed with an input only Port function. During synchronous serial communications, RXD is bi-directional and will become an output for transmission or data (TXD becomes the clock). |
| P2.5/ <u>BCLK0</u> P2.2/ <u>BCLK1</u> | I A(L)/A(E) | Baud Clock input can be used as an alternate clock source for each of the integrated serial channels. BCLKx is multiplexed with an input only Port function, and cannot exceed a clock rate greater than one-half the operating frequency of the M80C186EB. |
| P2.3/ <u>SINT1</u> | O H(X)/H(Q) R(O) P(X)/P(Q) | Serial Interrupt output will go active to indicate serial channel 1 requires service. SINT1 is multiplexed with an output only Port function. |

STANDARDIZED
MILITARY DRAWING
DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-93109

REVISION LEVEL

SHEET

22

6.6 One part - one part number system. The one part - one part number system described below has been developed to allow for transitions between identical generic devices covered by the four major microcircuit requirements documents (MIL-M-38510, MIL-H-38534, MIL-I-38535, and 1.2.1 of MIL-STD-883) without the necessity for the generation of unique PIN's. The four military requirements documents represent different class levels, and previously when a device manufacturer upgraded military product from one class level to another, the benefits of the upgraded product were unavailable to the Original Equipment Manufacturer (OEM), that was contractually locked into the original unique PIN. By establishing a one part number system covering all four documents, the OEM can acquire to the highest class level available for a given generic device to meet system needs without modifying the original contract parts selection criteria.

| <u>Military documentation format</u> | <u>Example PIN under new system</u> | <u>Manufacturing source listing</u> | <u>Document Listing</u> |
|--|-------------------------------------|-------------------------------------|-------------------------|
| New MIL-M-38510 Military Detail Specifications (in the SMD format) | 5962-XXXXZZ(B or S)YY | QPL-38510 (Part 1 or 2) | MIL-BUL-103 |
| New MIL-H-38534 Standardized Military Drawings | 5962-XXXXZZ(H or K)YY | QML-38534 | MIL-BUL-103 |
| New MIL-I-38535 Standardized Military Drawings | 5962-XXXXZZ(Q or V)YY | QML-38535 | MIL-BUL-103 |
| New 1.2.1 of MIL-STD-883 Standardized Military Drawings | 5962-XXXXZZ(M)YY | MIL-BUL-103 | MIL-BUL-103 |

6.7 Sources of supply.

6.7.1 Sources of supply for device classes B and S. Sources of supply for device classes B and S are listed in QPL-38510.

6.7.2 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in QML-38535. The vendors listed in QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DESC-EC and have agreed to this drawing.

6.7.3 Approved sources of supply for device class M. Approved sources of supply for class M are listed in MIL-BUL-103. The vendors listed in MIL-BUL-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DESC-EC.

| | | | |
|---|-----------|----------------|------------|
| STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444 | SIZE A | | 5962-93109 |
| | | REVISION LEVEL | SHEET 23 |

STANDARDIZED MILITARY DRAWING SOURCE APPROVAL BULLETIN

DATE: 93-05-12

Approved sources of supply for SMD 5962-93105 are listed below for immediate acquisition only and shall be added to MIL-BUL-103 during the next revision. MIL-BUL-103 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DESC-EC. This bulletin is superseded by the next dated revision of MIL-BUL-103.

| Standardized military drawing PIN | Vendor CAGE number | Vendor similar PIN <u>1/</u> |
|-----------------------------------|--------------------|------------------------------|
| 5962-9310901MXX | 34649 | MG80C186EB-8/B |
| 5962-9310902MXX | 34649 | MG80C186EB-13/B |
| 5962-9310903MXX | 34649 | MG80C186EB-16/B |

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE number

34649

Vendor name and address

Intel Corporation
Robert Noyce Building FS001
2200 Mission College Blvd.
PO Box 58119
Santa Clara, CA 95052-8119

Point of Contact: 5000 W. Chandler Blvd
Chandler, AZ 85226

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in this information bulletin.