


TUNG-SOL

DIODE




GLASS BULB
BUTTON
12 PIN BASE E12-70
OUTLINE DRAWING
JEDEC 9-59

COATED UNIPOTENTIAL CATHODE

FOR
DAMPING DIODE APPLICATIONS
IN TV RECEIVERS

AC OR DC
ANY MOUNTING POSITION



BOTTOM VIEW

BASING DIAGRAM
JEDEC 12BL

THE 6AX3 IS A HEATER-CATHODE SINGLE DIODE IN THE COMPACT 12 PIN T-9 CONSTRUCTION. ITS HIGH HEATER AND CATHODE INSULATION IS DESIGNED FOR USE AS A DAMPING DIODE IN T.V. RECEIVERS.

DIRECT INTERELECTRODE CAPACITANCES

WITHOUT EXTERNAL SHIELD

CATHODE TO PLATE AND HEATER: K TO (P+H)	7.5	pf
PLATE TO CATHODE AND HEATER: P TO (K+H)	5.5	pf
HEATER TO CATHODE: (H TO K)	2.8	pf

HEATER CHARACTERISTICS AND RATINGS

DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239

AVERAGE CHARACTERISTICS	6.3 VOLTS	1200	MA.
HEATER SUPPLY LIMITS: VOLTAGE OPERATION ^A		6.3±0.6	VOLTS
MAXIMUM HEATER-CATHODE VOLTAGE:			
HEATER NEGATIVE WITH RESPECT TO CATHODE			
DC COMPONENT		900	VOLTS
TOTAL DC AND PEAK		5000	VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE			
DC COMPONENT		100	VOLTS
TOTAL DC AND PEAK		300	VOLTS

^ATHE EQUIPMENT DESIGNER SHALL DESIGN THE EQUIPMENT SO THAT THE HEATER VOLTAGE IS CENTERED AT THE SPECIFIED BOGEY VALUE, WITH HEATER SUPPLY VARIATIONS RESTRICTED TO MAINTAIN HEATER VOLTAGE WITHIN THE SPECIFIED TOLERANCE.

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

MAXIMUM RATINGS^B

DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239

TV DAMPER SERVICE

PEAK INVERSE PLATE VOLTAGE	5000	VOLTS
PLATE DISSIPATION	5.3	WATTS
STEADY-STATE PEAK PLATE CURRENT	1000	MA.
DC OUTPUT	165	MA.

AVERAGE CHARACTERISTICS

TUBE VOLTAGE DROP		
$I_b = 250$ MILLIAMPERES DC	32	VOLTS

^BFOR OPERATION IN A 525-LINE, 30-FRAME SYSTEM AS DESCRIBED IN "STANDARDS OF GOOD ENGINEERING PRACTICE FOR TELEVISION BROADCAST STATIONS: FEDERAL COMMUNICATIONS COMMISSION", THE DUTY CYCLE OF THE VOLTAGE PULSE MUST NOT EXCEED 35% OF ONE SCANNING CYCLE.

