

6CU5

Beam Power Tube

7-PIN MINIATURE TYPE

GENERAL DATA


Electrical:

Heater, for Unipotential Cathode:		
Voltage (AC or DC)	6.3 ± 10%	volts
Current at 6.3 volts	1.2	amp
Direct Interelectrode Capacitances (Approx.): ^a		
Grid No.1 to plate	0.6	μf
Grid No.1 to cathode & grid No.3, grid No.2, and heater	13	μf
Plate to cathode & grid No.3, grid No.2, and heater	8.5	μf

Mechanical:

Operating Position	Any
Maximum Overall Length	2-5/8"
Maximum Seated Length	2-3/8"
Length, Base Seat to Bulb Top (Excluding tip)	2" ± 3/32"
Diameter	0.650" to 0.750"
Dimensional Outline	See <i>General Section</i>
Bulb	T5-1/2
Base	Small-Button Miniature 7-Pin (JEDEC No.E7-1)
Basing Designation for BOTTOM VIEW	7CV

Pin 1 - Cathode,
Grid No.3
Pin 2 - Grid No.1
Pin 3 - Heater



Pin 4 - Heater
Pin 5 - Grid No.1
Pin 6 - Grid No.2
Pin 7 - Plate

AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE	150 max.	volts
GRID-No.2 (SCREEN-GRID) VOLTAGE	130 max.	volts
GRID-No.1 (CONTROL-GRID) VOLTAGE:		
Positive-bias value	0 max.	volts
PLATE DISSIPATION	7 max.	watts
GRID-No.2 INPUT	1.4 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode	200 max.	volts
Heater positive with respect to cathode	200 ^b max.	volts
BULB TEMPERATURE (At hottest point on bulb surface)	220 max.	°C

← Indicates a change.



RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA
I-62

6CU5

Typical Operation and Characteristics:

Plate Voltage	120	volts	—
Grid-No.2 Voltage	110	volts	—
Grid-No.1 Voltage	-8	volts	—
Peak AF Grid-No.1 Voltage	8	volts	—
Zero-Signal Plate Current	49	ma	—
Max.-Signal Plate Current	50	ma	—
Zero-Signal Grid-No.2 Current	4	ma	—
Max.-Signal Grid-No.2 Current	8.5	ma	—
Plate Resistance (Approx.)	10000	ohms	—
Transconductance	7500	μ mhos	—
Load Resistance	2500	ohms	—
Total Harmonic Distortion	10	%	—
Max.-Signal Power Output	2.3	watts	—

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:			—
For fixed-bias operation	0.1 max.	megohm	—
For cathode-bias operation	0.5 max.	megohm	—

- a** Without external shield.
- b** The dc component must not exceed 100 volts.





6CU5

AVERAGE CHARACTERISTICS

6CU5




PLATE (I_b) OR GRID-№2 (I_{c2}) MILLIAMPERES

TUBE DIVISION

92CM-8908RI

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

6CU5



6CU5

OPERATION CHARACTERISTICS

