

Surface Mount Type

POSCAP

Series : TPU



Features

- Small size, Low profile (L2.0 × W 1.25 × H 0.9 mm)
- Face down terminal type
- RoHS compliance, Halogen free

Specifications

Size code	S09	B09
Category temperature range	-55 °C to +85 °C	
Rated voltage range	2.5 V.DC to 10 V.DC	6.3 V.DC
Category voltage range	2.5 V.DC to 10 V.DC	6.3 V.DC
Rated capacitance range	4.7 μF to 100 μF	150 μF
Capacitance tolerance	±20 % (120 Hz / + 20 °C)	
Leakage current	Please see the attached characteristics list	
Dissipation factor (tan δ)	Please see the attached characteristics list	
Surge voltage (V.DC)	Rated voltage × 1.15	
Endurance	+85 °C, 1000 h, rated voltage applied	
	Capacitance change	Within ±20 % of the initial value
	tan δ	≤ 1.5 times of the initial limit
	DC leakage current	Within the initial limit
Damp heat (Steady State)	+60 °C, 90 % to 95 %, 500 h, No-applied voltage	
	Capacitance change	Within +40 %, -20 % of the initial value
	tan δ	≤ 1.5 times of the initial limit
	DC leakage current	≤ 3 times of the initial limit

Marking

S09 Size		B09 Size	
Polarity marking(+)	R.Cap. code	Polarity marking(+)	R.Cap. code
R. Voltage code	Lot. No.	R. Voltage code	Lot. No.
R. Voltage (V.DC)	2.5 4.0 6.3 10.0		
Code	e g j A		
S09 Size			
R. Cap. (μF)	4.7 10 22 47 68 100		
Code	s A J S W A		
B09 Size			
R. Cap. (μF)	150		
Code	E8		

Dimensions (not to scale)

Size code	L±0.1*1	W±0.1*1	H±0.1	S±0.1*1	W1±0.1
S09	2.0	1.25	0.9	0.5	0.9
B09	3.5	2.8	0.9	0.8	2.2

Unit : mm

* Externals of figure are the reference. *1 ±0.2 : B09

Characteristics list

Series	Rated voltage (V.DC)	Rated temp. (°C)	Category voltage (V.DC)	Category temp. (°C)	Rated capacitance (μF)	Case size (mm)			Size code	Specifications				Standard		
						L	W	H		Ripple*1 (mAr.m.s.)	ESR*2 (mΩ max.)	tan δ*3	LC*4 (μA)	Part number	Min. Packaging Qty (pcs)	
TPU	2.5	85	2.5	85	47	2.0	1.25	0.9	S09	510	150	0.10	23.5	2R5TPU47MSI	3000	
		85	2.5	85	100	2.0	1.25	0.9		510	150	0.10	50.0	ETPU100MSI	3000	
	6.3	85	4.0	85	68	2.0	1.25	0.9		510	150	0.10	54.4	4TPU68MSI	3000	
		85	6.3	85	10	2.0	1.25	0.9		400	250	0.10	6.3	6TPU10MSI	3000	
		85	6.3	85	22	2.0	1.25	0.9		510	150	0.10	27.7	6TPU22MSI	3000	
		85	6.3	85	47	2.0	1.25	0.9		510	150	0.10	59.2	6TPU47MSI	3000	
		85	6.3	85	150	3.5	2.8	0.9		B09	670	100	0.10	94.5	6TPU150MBI	3000
		85	6.3	85	4.7	2.0	1.25	0.9		S09	360	300	0.10	4.7	10TPU4R7MSI	3000

*1 Ripple current (100 kHz/ +45 °C) *2 ESR (100 kHz/+20 °C) *3 tan δ (120 Hz/+20 °C) *4 After 5 minutes

◆ Please refer to each page in this catalog for "Reflow conditions" and "Taping specifications".