


70N03G


70 Amps,30 Volts N-CHANNEL MOSFET

Features

- 70A,30V, $R_{DS(ON)MAX}=6.5m\Omega @V_{GS}=10V/20A$
- Low gate charge
- Low C_{iss}
- Fast switching
- 100% avalanche tested
- Improved dv/dt capability



TO-252



Absolute Maximum Ratings ($T_c=25^\circ\text{C}$, unless otherwise noted)

Parameter	Symbol	70N03G	UNIT
Drain-Source Voltage	V_{DSS}	30	V
Gate-Source Voltage	V_{GSS}	± 20	
Continuous Drain Current	I_D	70	A
Pulsed Drain Current(Note1)	I_{DM}	210	
Single Pulse Avalanche Energy (Note 2)	E_{AS}	200	mJ
Avalanche Current(Note1)	I_{AR}	70	A
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 to +150	$^\circ\text{C}$
Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds	T_L	260	$^\circ\text{C}$

Thermal Characteristics

Parameter	Symbol	TO-263	Units
Thermal resistance , Junction to Case	$R_{th(j-c)}$	1.8	$^\circ\text{C}/\text{W}$
Maximum Power Dissipation	P_D	83	W

Electrical Characteristics (T _c =25°C, unless otherwise noted)						
Parameter	Symbol	Test Conditions	Mix	Typ	Max	Units
Off Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	30	—	—	V
Breakdown Temperature Coefficient	ΔBV _{DSS} /ΔT _J	Reference to 25°C , I _D =250uA	—	0.021	—	V/°C
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =30V, V _{GS} =0V	—	—	1	uA
Gate-Body Leakage Current, Forward	I _{GSSF}	V _{GS} =20V, V _{DS} =0V	—	—	100	nA
Gate-Body Leakage Current, Reverse	I _{GSSR}	V _{GS} =-20V, V _{DS} =0V	—	—	-100	nA
On Characteristics						
Gate-Source Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250uA	0.5	—	2.5	V
Drain-Source On-State Resistance	R _{DS(on)}	V _{GS} =10V, I _D =30A	—	5.5	6.5	m Ω
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{DS} =15V, V _{GS} =0V, f=1.0MHZ	—	3075	—	pF
Output Capacitance	C _{oss}		—	400	—	pF
Reverse Transfer Capacitance	C _{rss}		—	315	—	pF
Switching Characteristics						
Turn-On Delay Time	t _{d(on)}	V _{DD} =15V, I _D =20A R _G =1.5 Ω	—	11.2	—	ns
Turn-On Rise Time	t _r		—	49	—	ns
Turn-Off Delay Time	t _{d(off)}	V _{GS} =10V (Note4,5)	—	35	—	ns
Turn-Off Fall Time	t _f		—	7.8	—	ns
Total Gate Charge	Q _g	V _{DS} =20V, I _D =12A, V _{GS} =4.5V, (Note4,5)	—	31.6	—	nC
Gate-Source Charge	Q _{gs}		—	6.07	—	nC
Gate-Drain Charge	Q _{gd}		—	13.8	—	nC
Drain-Source Body Diode Characteristics and Maximum Ratings						
Continuous Diode Forward Current	I _S		—	—	70	A
Pulsed Diode Forward Current	I _{SM}		—	—	210	A
Diode Forward Voltage	V _{SD}	I _S =1A, V _{GS} =0V	—	—	1	V
Reverse Recovery Time	t _{rr}	V _{GS} =0V, I _S =70A, dI _F /dt=100A/us, (Note4,5)	—	32	—	ns
Reverse Recovery Charge	Q _{rr}		—	12	—	uC


Notes

1. Repetitive Rating: pulse width limited by maximum junction temperature.
2. L=0.1mH, R_g=25 Ω, I_{AS}=70A, starting T_J=25°C.
3. I_{SD} ≤ I_D, dI/dt=200A/us, V_{DD} ≤ BV_{DSS}, starting T_J=25°C.
4. Pulse width ≤ 300us; duty cycle ≤ 2%.
5. Repetitive rating; pulse width limited by maximum junction temperature.


TEST CIRCUIT AND WAVEFORM




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform














Unclamped Inductive Switching Test Circuit



Unclamped Inductive Switching Waveforms


RATING AND CHARACTERISTIC CURVES





PACKAGE OUTLINE DIMENSIONS

TO-252



TO-252		
Dim	Min	Max
A	.230 (5.85)	.246 (6.25)
B	.250 (6.35)	.264 (6.75)
C	.207 (5.27)	.218 (5.54)
D	.037 (0.93)	.045 (1.14)
E	.106 (2.70)	.138 (3.50)
F	.028 (0.72)	.033 (0.84)
G	.024 (0.60)	.041 (1.05)
H	.028 (0.72)	.043 (1.10)
I	.085 (2.15)	.096 (2.45)
J	.037 (0.95)	.047 (1.20)
K	.018 (0.45)	.026 (0.65)
L	.018 (0.45)	.024 (0.60)
P	.081 (2.05)	.094 (2.40)
M	.000 (0.00)	.006 (0.15)
N	--	.008 (0.20)
a	0°	10°

Dimensions in inches and (millimeters)