

## 600V N-Channel MOSFET



### GENERAL DESCRIPTION

This Power MOSFET is produced using advanced planar stripe DMOS technology.

This latest technology has been especially designed to minimize on-state resistance,

Have a high rugged avalanche characteristics. These devices are well suited for high efficiency switched mode power supplies, active power factor correction. electronic lamp ballasts based on half bridge topology.

$V_{DSS}$	$R_{DS(ON)}$	$I_D$
600V	1.3Ω	7A



### Features

- 7A, 600V,  $R_{DS(on)} = 1.3\Omega$  @ $V_{GS} = 10$  V
- Low gate charge ( typical 29nC)
- Fast switching
- 100% avalanche tested
- Improved dv/dt capability

### Ordering Information

PART NUMBER	PACKAGE	BRAND
7N60/7N60F	TO-220/220F	GFD

## Absolute Maximum Ratings

TC = 25°C unless otherwise noted

Symbol	Parameter	7N60	7N60F	Units
V <sub>DSS</sub>	Drain-Source Voltage	600		V
I <sub>D</sub>	Drain Current - Continuous (TC = 25°C) - Continuous (TC = 100°C)	7.0	7.0	A
		4.2	4.2	A
I <sub>DM</sub>	Drain Current- Pulsed (Note 1)	28	28	A
V <sub>GSS</sub>	Gate-Source Voltage	± 30		V
E <sub>AS</sub>	Single Pulsed Avalanche Energy (Note 2)	245		mJ
E <sub>AR</sub>	Repetitive Avalanche Energy (Note 1)	14.7		mJ
dV/dt	Peak Diode Recovery dV/dt (Note 3)	4.5		V/ns
P <sub>D</sub>	Power Dissipation (TC = 25°C)	147	48	W
	Derate above 25°C	1.17	0.38	W/°C
T <sub>J</sub> , T <sub>STG</sub>	Operating and Storage Temperature Range	-55 to +150		°C
T <sub>L</sub>	Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds	300		°C

## Thermal Characteristics

Symbol	Parameter	7N60	7N60F	Units
R <sub>θJC</sub>	Thermal Resistance, Junction-to-Case	0.85	2.6	°C/W
R <sub>θCS</sub>	Thermal Resistance, Case-to-Sink Typ.	0.5	--	°C/W
R <sub>θJA</sub>	Thermal Resistance, Junction-to-Ambient	62.5	62.5	°C/W

## Electrical Characteristics

TC = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
--------	-----------	-----------------	-----	-----	-----	-------

## Off Characteristics

BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA	600	--	--	V
ΔBV <sub>DSS</sub> /ΔT <sub>J</sub>	Breakdown Voltage Temperature Coefficient	I <sub>D</sub> = 250 μA, Referenced to 25°C	--	0.7	--	V/°C
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> = 600 V, V <sub>GS</sub> = 0 V	--	--	1	μA
		V <sub>DS</sub> = 480 V, T <sub>C</sub> = 125°C	--	--	10	μA
I <sub>GSSF</sub>	Gate-Body Leakage Current, Forward	V <sub>GS</sub> = 30 V, V <sub>DS</sub> = 0 V	--	--	100	nA
I <sub>GSSR</sub>	Gate-Body Leakage Current, Reverse	V <sub>GS</sub> = -30 V, V <sub>DS</sub> = 0 V	--	--	-100	nA

## On Characteristics

V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA	2.0	--	4.5	V
R <sub>DS(on)</sub>	Static Drain-Source On-Resistance	V <sub>GS</sub> = 10 V, I <sub>D</sub> = 3.5 A	--	1.05	1.3	Ω

## Dynamic Characteristics

C <sub>iss</sub>	Input Capacitance	V <sub>DS</sub> = 25 V, V <sub>GS</sub> = 0 V, f = 1.0 MHz	--	1000	--	pF
C <sub>oss</sub>	Output Capacitance		--	110	--	pF
C <sub>rss</sub>	Reverse Transfer Capacitance		--	12.6	--	pF

## Switching Characteristics

$t_{d(on)}$	Turn-On Delay Time	$V_{DD} = 300 \text{ V}$ , $I_D = 7 \text{ A}$ , $R_G = 25 \Omega$  (Note 4, 5)	--	20	--	ns
$t_r$	Turn-On Rise Time		--	50	--	ns
$t_{d(off)}$	Turn-Off Delay Time		--	80	--	ns
$t_f$	Turn-Off Fall Time		--	70	--	ns
$Q_g$	Total Gate Charge	$V_{DS} = 480 \text{ V}$ , $I_D = 7 \text{ A}$ , $V_{GS} = 10 \text{ V}$  (Note 4, 5)	--	29	--	nC
$Q_{gs}$	Gate-Source Charge		--	4.7	--	nC
$Q_{gd}$	Gate-Drain Charge		--	12.5	--	nC


## Drain-Source Diode Characteristics and Maximum Ratings

$I_s$	Maximum Continuous Drain-Source Diode Forward Current	--	--	7.0	A
$I_{SM}$	Maximum Pulsed Drain-Source Diode Forward Current	--	--	28	A
$V_{SD}$	Drain-Source Diode Forward Voltage	$V_{GS} = 0 \text{ V}$ , $I_s = 7 \text{ A}$	--	--	1.5 V
$t_{rr}$	Reverse Recovery Time	$V_{GS} = 0 \text{ V}$ , $I_s = 7 \text{ A}$ , $dI_F / dt = 100 \text{ A}/\mu\text{s}$  (Note 4)	--	320	-- ns
$Q_{rr}$	Reverse Recovery Charge		--	3.0	-- $\mu\text{C}$


### Notes:

1. Repetitive Rating : Pulse width limited by maximum junction temperature
2. L = 10 mH, IAS = 7 A, VDD = 50V, RG = 25 Ω, Starting TJ = 25°C
3. ISD ≤ 7 A, di/dt ≤ 200A/μs, VDD ≤ BVDSS, Starting TJ = 25°C
4. Pulse Test : Pulse width ≤ 300μs, Duty cycle ≤ 2%
5. Essentially independent of operating temperature


## Typical Characteristics




**Figure 1. On-Region Characteristics**




**Figure 2. Transfer Characteristics**




**Figure 3. On-Resistance Variation vs  
Drain Current and Gate Voltage**



**Figure 4. Body Diode Forward Voltage  
Variation with Source Current  
and Temperature**




**Figure 5. Capacitance Characteristics**




**Figure 6. Gate Charge Characteristics**


## Typical Characteristics (Continued)




**Figure 7. Breakdown Voltage Variation vs Temperature**




**Figure 8. On-Resistance Variation vs Temperature**



**Figure 9-1. Maximum Safe Operating Area for TSP7N60M**




**Figure 9-2. Maximum Safe Operating Area for TSF7N60M**




**Figure 10. Maximum Drain Current vs Case Temperature**




## Typical Characteristics (Continued)



**Figure 11-1. Transient Thermal Response Curve  
for TSP7N60M**



**Figure 11-2. Transient Thermal Response Curve  
for TSF7N60M**

**Gate Charge Test Circuit & Waveform**

**Resistive Switching Test Circuit & Waveforms**

**Unclamped Inductive Switching Test Circuit & Waveforms**


**Peak Diode Recovery dv/dt Test Circuit & Waveforms**
