



DESCRIPTION

The A6501 series are highly precise, low power consumption, positive voltage regulators manufactured using CMOS and laser trimming technologies. The series provides large currents with a significantly small dropout voltage. The A6501 consists of a current limiter circuit, a driver transistor, a precision reference voltage and an error amplifier. Output voltage is selectable in 0.1V steps between 1.5V~6.0V.

The A6501 is available in SOT-89-3, SOT-26 and SOT-223 packages.

ORDERING INFORMATION

Package Type	Part Number	
SOT-89-3	K3	A6501K3R-XXB
		A6501K3VR-XXB
SOT-26	E6	A6501E6R-XX
		A6501E6VR-XX
SOT-223	N	A6501NR-XX
		A6501NVR-XX
Note	XX: Output Voltage 30=3.0V, 50=5.0V V: Halogen Free Package R: Tape & Reel B: Pin Type B	
AiT provides all RoHs products Suffix "V" means Halogen Free Package		


FEATURES

- Output Voltage Range: 1.5V to 6.0V (selectable in 100mV steps)
- Highly Accurate: $\pm 2\%$
- Dropout Voltage : 500mV @ 500mA (3.3V type)
- Low Power Consumption: 8.0 μ A (TYP.)
- Maximum Output Current : 500mA ($V_{IN} \geq V_{OUT} + 1V$)
- Internal protector: current limiter and short protector
- Maximum Operating voltage: 10V
- Available in SOT-89-3, SOT-26 and SOT-223 packages.

APPLICATION

- DVD, CD-ROM, HDD drive equipment
- Wireless Communication equipment (Mobile & Cordless phone, etc.)
- Network equipment (Wireless LAN etc.)
- Desktop computers, Note book computer, PDAs
- Portable AV equipment
- Reference voltage
- Battery powered equipment




TYPICAL APPLICATION



The above connection diagram and constant will not guarantee successful operation. Perform thorough evaluation using the actual application to set the constant.



PIN DESCRIPTION

 <p>Top View</p>	 <p>Top View</p>	 <p>Top View</p>																												
<table border="1"><thead><tr><th colspan="3">Pin #</th><th rowspan="2">Symbol</th><th rowspan="2">Function</th></tr><tr><th>SOT-89-3</th><th>SOT-26</th><th>SOT-223</th></tr></thead><tbody><tr><td>3</td><td>6</td><td>3</td><td>V_{OUT}</td><td>Output</td></tr><tr><td>1</td><td>2,4,5</td><td>1</td><td>V_{SS}</td><td>Ground</td></tr><tr><td>2</td><td>1</td><td>2</td><td>V_{IN}</td><td>Power Input</td></tr><tr><td>-</td><td>3</td><td>-</td><td>NC</td><td>No Connection</td></tr></tbody></table>			Pin #			Symbol	Function	SOT-89-3	SOT-26	SOT-223	3	6	3	V _{OUT}	Output	1	2,4,5	1	V _{SS}	Ground	2	1	2	V _{IN}	Power Input	-	3	-	NC	No Connection
Pin #			Symbol	Function																										
SOT-89-3	SOT-26	SOT-223																												
3	6	3	V _{OUT}	Output																										
1	2,4,5	1	V _{SS}	Ground																										
2	1	2	V _{IN}	Power Input																										
-	3	-	NC	No Connection																										



ABSOLUTE MAXIMUM RATINGS

V_{IN} , Input Voltage	$V_{SS}-0.3V \sim V_{SS}+10V$	
V_{OUT} , Output Voltage	$V_{SS}-0.3V \sim V_{IN}+0.3V$	
I_{OUT} , Output Current	800mA <small>NOTE1</small>	
P_D , Power Dissipation	SOT-89-3	500mW
	SOT-26	500mW
	SOT-223	1500mW
TOPR, Operating Ambient Temperature	$-40^{\circ}C \sim +85^{\circ}C$	
TSTG, Storage Temperature	$-55^{\circ}C \sim +125^{\circ}C$	

Stresses above may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated in the Electrical Characteristics are not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

NOTE1: $I_{OUT} \geq P_D/(V_{IN}-V_{OUT})$.



ELECTRICAL CHARACTERISTICS


Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit	Circuit	
Output Voltage	$V_{OUT(E)}$	$V_{IN} = V_{OUT(S)} + 1.0V$, $I_{OUT} = 50mA$		$V_{OUT(S)} \times 0.98$	$V_{OUT(S)}$	$V_{OUT(S)} \times 1.02$	V	1	
Output Current	I_{OUT}	$V_{IN} \geq V_{OUT(S)} + 1.0V$		500	-	-	mA		
Dropout Voltage	V_{DROP}	$I_{OUT} = 500mA$	2.2V ≤ $V_{OUT(S)}$ ≤ 2.5V	-	0.65	1.05	V		
			2.6V ≤ $V_{OUT(S)}$ ≤ 3.3V		0.55	0.82			
			3.4V ≤ $V_{OUT(S)}$ ≤ 5.5V		0.48	0.76			
Line Regulations	$\frac{\Delta V_{OUT1}}{\Delta V_{IN} \times V_{OUT}}$	$V_{OUT(S)} + 0.5V \leq V_{IN} \leq 9V$ $I_{OUT} = 80mA$		-	0.05	0.3	%/V	1	
Input Voltage	ΔV_{OUT2}	$V_{IN} = V_{OUT(S)} + 1.0V$ $1.0mA \leq I_{OUT} \leq 200mA$		-	20	50	mV		
Output Voltage Temperature Characteristics	$\frac{\Delta V_{OUT}}{\Delta T_A \times V_{OUT}}$	$V_{IN} = V_{OUT(S)} + 1.0V$, $I_{OUT} = 10mA$ $-40^\circ C \leq T_A \leq 85^\circ C$		-	±100	-	ppm/ $^\circ C$		
Supply Current	I_{SS1}	$V_{IN} = V_{OUT(S)} + 1.0V$		-	8	15	µA	2	
Input Voltage	V_{IN}			1.8	-	9	V	-	
Ripple-Rejection	$ IRR $	$V_{IN} = V_{OUT(S)} + 1.0V$, $f = 1.0kHz$ $V_{rip} = 0.5V_{rms}$, $I_{OUT} = 80mA$		-	50		dB	1	
Short current	I_{SHORT}	$V_{IN} = V_{OUT(S)} + 1.5V$		-	50	-	mA	1	
Current Limiter	I_{LIM}	$V_{IN} = V_{OUT(S)} + 1.5V$		-	800	-	mA		




TYPICAL PERFORMANCE CHARACTERISTICS

3.3V Output


1. Output Voltage vs. Output Current




2. Output Voltage vs. Input Voltage (Contd.)



3. Dropout Voltage vs. Output Current




4. Supply Current vs. Input Voltage






5. Output Voltage vs. Ambient Temperature



7. Transient Response Input Transient Response




Input capacitor (C_{IN}): 1.0μF or more


Output capacitor (C_L): 0.1μF or more (tantalum capacitor)

Caution A general series regulator may oscillate, depending on the external components selected. Check that no oscillation occurs with the application using the above capacitor.

6. Ripple Rejection Rate




8. Load Transient Response






TYPICAL PERFORMANCE CHARACTERISTICS

Circuit 1




Circuit 2






BLOCK DIAGRAM





PACKAGE INFORMATION


Dimension in SOT-89-3 (Unit: mm)



Symbol	Min	Max
A	1.400	1.600
b	0.320	0.520
b1	0.400	0.580
c	0.350	0.440
D	4.400	4.600
D1	1.550 REF	
E	2.300	2.600
E1	3.940	4.250
e	1.500 TYP	
e1	3.000 TYP	
L	0.900	1.200




Dimension in SOT-26 Package (Unit: mm)



SYMBOL	MIN	MAX
A	1.050	1.250
A1	0.000	0.100
A2	1.050	1.150
b	0.300	0.500
c	0.100	0.200
D	2.820	3.020
E	1.500	1.700
E1	2.650	2.950
e	0.950(BSC)	
e1	1.800	2.000
L	0.300	0.600
θ	0°	8°



Dimension in SOT-223 (Unit: mm)



Symbol	Min	Max
A	1.520	1.800
A1	0.000	0.100
A2	1.500	1.700
b	0.660	0.820
c	0.250	0.350
D	6.200	6.400
D1	2.900	3.100
E	3.300	3.700
E1	6.830	7.070
e	2.300(BSC)	
e1	4.500	4.700
L	0.900	1.150
θ	0°	10°



IMPORTANT NOTICE

AiT Semiconductor Inc. (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Semiconductor Inc.'s integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Semiconductor Inc. assumes no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.