


N-Channel Enhancement Mode Field Effect Transistor**PRODUCT SUMMARY**

V _{DSS}	I _D	R _{DS(ON)} (mΩ)
60V	3.0A	105mΩ

**Absolute Maximum Ratings (TA = 25°C unless otherwise specified)**

Symbol	Parameter	Ratings	Unit
Common Ratings			
V _{DSS}	Drain-Source Voltage	60	V
V _{GSS}	Gate-Source Voltage	±20	
T _J	Maximum Junction Temperature	150	°C
T _{STG}	Storage Temperature Range	-55 to 150	°C
I _S	Diode Continuous Forward Current (3)	T _C =25°C 3	A
Mounted on Large Heat Sink			
I _{DM}	300μs Pulse Drain Current Tested(1)	T _C =25°C 10	A
I _D	Continuous Drain Current	T _C =25°C 3	A
P _D	Maximum Power Dissipation (3)	1.7	W

1. Pulse width limited by maximum junction temperature.

Thermal Characteristics

Symbol	Parameter	Ratings	Unit
R _{thJA}	Thermal resistance junction-ambient max (3)	73.5	°C/W

Electrical Characteristics (TA=25°C Unless Otherwise Noted)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
On/off Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =250uA	60	65	--	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 60V, V _{GS} =0V	--	--	1	uA
		V _{DS} =60V, V _{GS} =0V T _J =55°C	--	--	10	
V _{G(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250uA	0.8	1.1	1.4	V
I _{GSS}	Gate Leakage Current	V _{GS} =±20V, V _{DS} =0V	--	--	±100	nA
R _{D(on)}	Drain-SourceOn-stateResistance ⁽²⁾	V _{GS} = 10V, I _{DS} =3A	--	78	105	mΩ
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} = 3V, Frequency=1.0MHz	--	247	--	pF
C _{oss}	Output Capacitance		--	34	--	
C _{rss}	Reverse Transfer Capacitance		--	19.5	--	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time ⁽¹⁾	V _{DD} =30V, I _D = 1.5A, V _{GS} = 10V, R _{GEN} =1 Ω	--	6	--	ns
t _r	Turn-on Rise Time ⁽¹⁾		--	15	--	
t _{d(OFF)}	Turn-off Delay Time ⁽¹⁾		--	15	--	
t _f	Turn-off Fall Time ⁽¹⁾		--	10	--	
Q _g	Total Gate Charge ⁽¹⁾	V _{DS} =30V, V _{GS} = 4.5V, I _{DS} =3A	--	6	--	nC
Q _{gs}	Gate-Source Charge ⁽¹⁾		--	1	--	
Q _{gd}	Gate-Drain Charge ⁽¹⁾		--	1.3	--	
Diode Characteristics						
V _{SD}	Diode Forward Voltage ⁽²⁾	I _{SD} = 3A, V _{GS} = 0	--	--	1.2	V

NOTES:

1. Independent of operating temperature.
2. Pulse Test : Pulse width $\leq 300 \mu s$, Duty cycle $\leq 2\%$
3. Surface Mounted on FR4 Board, t < 10 sec.

Typical Performance Characteristics

Figure 1: Output Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance Variation with Drain Current and Gate Voltage.




Figure 5: On-Resistance Variation with Temperature.




Figure 4: On-Resistance Variation with Temperature




Figure 6: Body Diode Forward Voltage Variation with Source Current










Figure 7: Gate Charge**Figure 8: Maximum Safe Operating Area****Figure 9: Capacitance Characteristics.****Figure 10: Normalized Maximum Transient Thermal Impedance**

Test circuits and Waveforms


EAS test circuits:




Gate charge test circuit:




Switch Time Test Circuit:



Switch Waveforms:



PACKAGE MECHANICAL DATA
SOT-23 Package Dimension



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°