

Description:

Fastener Length: 1/2"

AF3522-4-02 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

Gov. Issued Name:	Rivet, Blind
NSN:	5320-01-150-2738
NIIN:	011502738
FSC:	Rivets / 5320
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc
Manufacturer Country:	United States

AF3522-4-02 Specifications

Countersink Angle:	100.0 Degrees Nominal
Expansion Device:	Serrated Stem-type W
Fastener Length:	0.451 Inches Nominal
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Head Major Diameter:	0.225 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Material Document And Classification:	Qq-n-281 Fed Spec 2nd Material Response Sleeve
Material:	Nickel Alloy Sleeve
Material:	Steel Corrosion Resisting Locking Ring
Material:	Steel Corrosion Resisting Stem
Lubrication:	Dry Film
Material Document And Classification:	Ams5657 Assn Std 3rd Material Response Stem
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Locking Ring
Shank Diameter:	0.126 Inches Nominal
Shank Style:	Self-plugging High Clinch Shank

How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind-rivets/AF3522-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.