

# Field Stop Trench IGBT

## 650 V, 75 A

### AFGHL75T65SQD

Using the novel field stop 4th generation high speed IGBT technology, AFGHL75T65SQD which is AEC Q101 qualified offers the optimum performance for both hard and soft switching topology in automotive application.

#### Features

- AEC-Q101 Qualified
- Maximum Junction Temperature:  $T_J = 175^{\circ}\text{C}$
- Positive Temperature Co-efficient for Easy Parallel Operating
- High Current Capability
- Low Saturation Voltage:  $V_{CE(\text{Sat})} = 1.6 \text{ V (Typ.) @ } I_C = 75 \text{ A}$
- 100% of the Parts are Tested for  $I_{LM}$  (Note 2)
- Fast Switching
- Tight Parameter Distribution
- RoHS Compliant

#### Typical Applications

- Automotive HEV-EV Onboard Chargers
- Automotive HEV-EV DC-DC Converters
- Totem Pole Bridgeless PFC

#### MAXIMUM RATINGS

| Rating                                                                                      | Symbol               | Value                | Unit               |
|---------------------------------------------------------------------------------------------|----------------------|----------------------|--------------------|
| Collector-to-Emitter Voltage                                                                | $V_{CES}$            | 650                  | V                  |
| Gate-to-Emitter Voltage<br>Transient Gate-to-Emitter Voltage                                | $V_{GES}$            | $\pm 20$<br>$\pm 30$ | V                  |
| Collector Current (Note 1)<br>@ $T_C = 25^{\circ}\text{C}$<br>@ $T_C = 100^{\circ}\text{C}$ | $I_C$                | 80<br>75             | A                  |
| Pulsed Collector Current (Note 2)                                                           | $I_{LM}$             | 300                  | A                  |
| Pulsed Collector Current (Note 3)                                                           | $I_{CM}$             | 300                  | A                  |
| Diode Forward Current<br>@ $T_C = 25^{\circ}\text{C}$<br>@ $T_C = 100^{\circ}\text{C}$      | $I_F$                | 80<br>50             | A                  |
| Pulsed Diode Maximum Forward Current                                                        | $I_{FM(2)}$          | 300                  | A                  |
| Maximum Power Dissipation<br>@ $T_C = 25^{\circ}\text{C}$<br>@ $T_C = 100^{\circ}\text{C}$  | $P_D$                | 375<br>188           | W                  |
| Operating Junction<br>/ Storage Temperature Range                                           | $T_J$ ,<br>$T_{STG}$ | -55 to<br>+175       | $^{\circ}\text{C}$ |
| Maximum Lead Temp. for Soldering<br>Purposes, 1/8" from case for 5 seconds                  | $T_L$                | 300                  | $^{\circ}\text{C}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



1. Value limit by bond wire
2.  $V_{CC} = 400 \text{ V}$ ,  $V_{GE} = 15 \text{ V}$ ,  $I_C = 300 \text{ A}$ ,  $R_G = 15 \Omega$ , Inductive Load
3. Repetitive Rating: pulse width limited by max. Junction temperature



ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)

75 A, 650 V  
 $V_{CESat} = 1.6 \text{ V}$



#### MARKING DIAGRAM



&Y = ON Semiconductor Logo  
&Z = Assembly Plant Code  
&3 = 3-Digit Data Code  
&K = 2-Digit Lot Traceability Code  
AFGHL75T65SQD = Specific Device Code

#### ORDERING INFORMATION

| Device        | Package   | Shipping        |
|---------------|-----------|-----------------|
| AFGHL75T65SQD | TO-247-3L | 30 Units / Rail |

# AFGHL75T65SQD

## THERMAL CHARACTERISTICS

| Rating                                         | Symbol          | Value | Unit |
|------------------------------------------------|-----------------|-------|------|
| Thermal resistance junction-to-case, for IGBT  | $R_{\theta JC}$ | 0.4   | °C/W |
| Thermal resistance junction-to-case, for Diode | $R_{\theta JC}$ | 0.65  | °C/W |
| Thermal resistance junction-to-ambient         | $R_{\theta JA}$ | 40    | °C/W |

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Parameter | Test Conditions | Symbol | Min | Typ | Max | Unit |
|-----------|-----------------|--------|-----|-----|-----|------|
|-----------|-----------------|--------|-----|-----|-----|------|

### OFF CHARACTERISTICS

|                                                                   |                                                   |                                      |     |     |      |      |
|-------------------------------------------------------------------|---------------------------------------------------|--------------------------------------|-----|-----|------|------|
| Collector-emitter breakdown voltage, gate-emitter short-circuited | $V_{GE} = 0\text{ V},$<br>$I_C = 1\text{ mA}$     | $BV_{CES}$                           | 650 | –   | –    | V    |
| Temperature Coefficient of Breakdown Voltage                      | $V_{GE} = 0\text{ V},$<br>$I_C = 1\text{ mA}$     | $\frac{\Delta BV_{CES}}{\Delta T_J}$ | –   | 0.6 | –    | V/°C |
| Collector-emitter cut-off current, gate-emitter short-circuited   | $V_{GE} = 0\text{ V},$<br>$V_{CE} = 650\text{ V}$ | $I_{CES}$                            | –   | –   | 250  | μA   |
| Gate leakage current, collector-emitter short-circuited           | $V_{GE} = 20\text{ V},$<br>$V_{CE} = 0\text{ V}$  | $I_{GES}$                            | –   | –   | ±400 | nA   |

### ON CHARACTERISTICS

|                                      |                                                                                                                 |               |     |             |          |   |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------|---------------|-----|-------------|----------|---|
| Gate-emitter threshold voltage       | $V_{GE} = V_{CE}, I_C = 75\text{ mA}$                                                                           | $V_{GE(th)}$  | 3.4 | 4.9         | 6.4      | V |
| Collector-emitter saturation voltage | $V_{GE} = 15\text{ V}, I_C = 75\text{ A}$<br>$V_{GE} = 15\text{ V}, I_C = 75\text{ A}, T_J = 175^\circ\text{C}$ | $V_{CE(sat)}$ | –   | 1.6<br>1.95 | 2.1<br>– | V |

### DYNAMIC CHARACTERISTICS

|                              |                                                                            |           |   |      |   |    |
|------------------------------|----------------------------------------------------------------------------|-----------|---|------|---|----|
| Input capacitance            | $V_{CE} = 30\text{ V},$<br>$V_{GE} = 0\text{ V},$<br>$f = 1\text{ MHz}$    | $C_{ies}$ | – | 4617 | – | pF |
| Output capacitance           |                                                                            | $C_{oes}$ | – | 152  | – |    |
| Reverse transfer capacitance |                                                                            | $C_{res}$ | – | 13   | – |    |
| Gate charge total            | $V_{CE} = 400\text{ V},$<br>$I_C = 75\text{ A},$<br>$V_{GE} = 15\text{ V}$ | $Q_g$     | – | 136  | – | nC |
| Gate-to-emitter charge       |                                                                            | $Q_{ge}$  | – | 25   | – |    |
| Gate-to-collector charge     |                                                                            | $Q_{gc}$  | – | 32   | – |    |

### SWITCHING CHARACTERISTICS, INDUCTIVE LOAD

|                         |                                                                                                                                                      |              |   |      |   |    |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|---|------|---|----|
| Turn-on delay time      | $T_C = 25^\circ\text{C},$<br>$V_{CC} = 400\text{ V},$<br>$I_C = 37.5\text{ A},$<br>$R_G = 4.7\ \Omega,$<br>$V_{GE} = 15\text{ V},$<br>Inductive Load | $t_{d(on)}$  | – | 23   | – | ns |
| Rise time               |                                                                                                                                                      | $t_r$        | – | 17   | – |    |
| Turn-off delay time     |                                                                                                                                                      | $t_{d(off)}$ | – | 112  | – |    |
| Fall time               |                                                                                                                                                      | $t_f$        | – | 8    | – |    |
| Turn-on switching loss  |                                                                                                                                                      | $E_{on}$     | – | 0.61 | – | mJ |
| Turn-off switching loss |                                                                                                                                                      | $E_{off}$    | – | 0.21 | – |    |
| Total switching loss    |                                                                                                                                                      | $E_{ts}$     | – | 0.82 | – |    |
| Turn-on delay time      | $T_C = 25^\circ\text{C},$<br>$V_{CC} = 400\text{ V},$<br>$I_C = 75\text{ A},$<br>$R_G = 4.7\ \Omega,$<br>$V_{GE} = 15\text{ V},$<br>Inductive Load   | $t_{d(on)}$  | – | 25   | – | ns |
| Rise time               |                                                                                                                                                      | $t_r$        | – | 46   | – |    |
| Turn-off delay time     |                                                                                                                                                      | $t_{d(off)}$ | – | 106  | – |    |
| Fall time               |                                                                                                                                                      | $t_f$        | – | 67   | – |    |
| Turn-on switching loss  |                                                                                                                                                      | $E_{on}$     | – | 1.86 | – | mJ |
| Turn-off switching loss |                                                                                                                                                      | $E_{off}$    | – | 1.13 | – |    |
| Total switching loss    |                                                                                                                                                      | $E_{ts}$     | – | 2.99 | – |    |

# AFGHL75T65SQD

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Parameter | Test Conditions | Symbol | Min | Typ | Max | Unit |
|-----------|-----------------|--------|-----|-----|-----|------|
|-----------|-----------------|--------|-----|-----|-----|------|

### SWITCHING CHARACTERISTICS, INDUCTIVE LOAD

|                         |                                                                                                                                                            |              |   |      |   |    |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|---|------|---|----|
| Turn-on delay time      | $T_C = 175^\circ\text{C}$ ,<br>$V_{CC} = 400\text{ V}$ ,<br>$I_C = 37.5\text{ A}$ ,<br>$R_G = 4.7\ \Omega$ ,<br>$V_{GE} = 15\text{ V}$ ,<br>Inductive Load | $t_{d(on)}$  | – | 21   | – | ns |
| Rise time               |                                                                                                                                                            | $t_r$        | – | 19   | – |    |
| Turn-off delay time     |                                                                                                                                                            | $t_{d(off)}$ | – | 126  | – |    |
| Fall time               |                                                                                                                                                            | $t_f$        | – | 7    | – |    |
| Turn-on switching loss  |                                                                                                                                                            | $E_{on}$     | – | 1.20 | – | mJ |
| Turn-off switching loss |                                                                                                                                                            | $E_{off}$    | – | 0.41 | – |    |
| Total switching loss    |                                                                                                                                                            | $E_{ts}$     | – | 1.61 | – |    |
| Turn-on delay time      | $T_C = 175^\circ\text{C}$ ,<br>$V_{CC} = 400\text{ V}$ ,<br>$I_C = 75\text{ A}$ ,<br>$R_G = 4.7\ \Omega$ ,<br>$V_{GE} = 15\text{ V}$ ,<br>Inductive Load   | $t_{d(on)}$  | – | 24   | – | ns |
| Rise time               |                                                                                                                                                            | $t_r$        | – | 46   | – |    |
| Turn-off delay time     |                                                                                                                                                            | $t_{d(off)}$ | – | 115  | – |    |
| Fall time               |                                                                                                                                                            | $t_f$        | – | 72   | – |    |
| Turn-on switching loss  |                                                                                                                                                            | $E_{on}$     | – | 2.84 | – | mJ |
| Turn-off switching loss |                                                                                                                                                            | $E_{off}$    | – | 1.35 | – |    |
| Total switching loss    |                                                                                                                                                            | $E_{ts}$     | – | 4.20 | – |    |

### DIODE CHARACTERISTICS

|                               |                                                                              |           |   |      |     |               |
|-------------------------------|------------------------------------------------------------------------------|-----------|---|------|-----|---------------|
| Diode Forward Voltage         | $I_F = 50\text{ A}$ , $T_C = 25^\circ\text{C}$                               | $V_{FM}$  | – | 2.0  | 2.6 | V             |
|                               | $I_F = 50\text{ A}$ , $T_C = 175^\circ\text{C}$                              |           | – | 1.64 | –   |               |
| Reverse Recovery Energy       | $I_F = 50\text{ A}$ , $di_F/dt = 200\text{ A/s}$ , $T_C = 175^\circ\text{C}$ | $E_{rec}$ | – | 52   | –   | $\mu\text{J}$ |
| Diode Reverse Recovery Time   | $I_F = 50\text{ A}$ , $di_F/dt = 200\text{ A/s}$ , $T_C = 25^\circ\text{C}$  | $T_{rr}$  | – | 36   | –   | ns            |
|                               | $I_F = 50\text{ A}$ , $di_F/dt = 200\text{ A/s}$ , $T_C = 175^\circ\text{C}$ |           | – | 200  | –   |               |
| Diode Reverse Recovery Charge | $I_F = 50\text{ A}$ , $di_F/dt = 200\text{ A/s}$ , $T_C = 25^\circ\text{C}$  | $Q_{rr}$  | – | 54   | –   | nC            |
|                               | $I_F = 50\text{ A}$ , $di_F/dt = 200\text{ A/s}$ , $T_C = 175^\circ\text{C}$ |           | – | 954  | –   |               |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

TYPICAL CHARACTERISTICS




Figure 1. Typical Output Characteristics  
( $T_J = 25^\circ\text{C}$ )




Figure 2. Typical Output Characteristics  
( $T_J = 175^\circ\text{C}$ )




Figure 3. Typical Saturation Voltage  
Characteristics




Figure 4. Saturation Voltage vs. Case Temperature  
at Variant Current Level




Figure 5. Saturation Voltage vs.  $V_{GE}$  ( $T_J = 25^\circ\text{C}$ )




Figure 6. Saturation Voltage vs.  $V_{GE}$  ( $T_J = 175^\circ\text{C}$ )

TYPICAL CHARACTERISTICS (continued)




Figure 7. Capacitance Characteristics




Figure 8. Gate Charge Characteristics




Figure 9. Turn-On Characteristics vs. Gate Resistance




Figure 10. Turn-Off Characteristics vs. Gate Resistance




Figure 11. Turn-On Characteristics vs. Collector Current




Figure 12. Turn-Off Characteristics vs. Collector Current

Typical Characteristics (continued)




Figure 13. Switching Loss vs. Gate Resistance




Figure 14. Switching Loss vs. Collector Current




Figure 15. SOA Characteristics




Figure 16. Forward Characteristics




Figure 17. Reverse Recovery Current




Figure 18. Reverse Recovery Time Stored Charge

# AFGHL75T65SQD

## TYPICAL CHARACTERISTICS (continued)




Figure 19. Stored Charge




Figure 20. Transient Thermal Impedance of IGBT




Figure 21. Transient Thermal Impedance of Diode

# MECHANICAL CASE OUTLINE





## PACKAGE DIMENSIONS

ON Semiconductor®



### TO-247-3LD CASE 340CX ISSUE A

DATE 06 JUL 2020



NOTES: UNLESS OTHERWISE SPECIFIED.

- A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
- B. ALL DIMENSIONS ARE IN MILLIMETERS.
- C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
- D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
- E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

### GENERIC MARKING DIAGRAM\*



XXXXX = Specific Device Code  
A = Assembly Location  
Y = Year  
WW = Work Week  
G = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

| DIM | MILLIMETERS |       |       |
|-----|-------------|-------|-------|
|     | MIN         | NOM   | MAX   |
| A   | 4.58        | 4.70  | 4.82  |
| A1  | 2.20        | 2.40  | 2.60  |
| A2  | 1.40        | 1.50  | 1.60  |
| D   | 20.32       | 20.57 | 20.82 |
| E   | 15.37       | 15.62 | 15.87 |
| E2  | 4.96        | 5.08  | 5.20  |
| e   | ~           | 5.56  | ~     |
| L   | 19.75       | 20.00 | 20.25 |
| L1  | 3.69        | 3.81  | 3.93  |
| ØP  | 3.51        | 3.58  | 3.65  |
| Q   | 5.34        | 5.46  | 5.58  |
| S   | 5.34        | 5.46  | 5.58  |
| b   | 1.17        | 1.26  | 1.35  |
| b2  | 1.53        | 1.65  | 1.77  |
| b4  | 2.42        | 2.54  | 2.66  |
| c   | 0.51        | 0.61  | 0.71  |
| D1  | 13.08       | ~     | ~     |
| D2  | 0.51        | 0.93  | 1.35  |
| E1  | 12.81       | ~     | ~     |
| ØP1 | 6.60        | 6.80  | 7.00  |

|                  |             |                                                                                                                                                                                     |
|------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98AON93302G | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | TO-247-3LD  | PAGE 1 OF 1                                                                                                                                                                         |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.



**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Email Requests to: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**onsemi Website:** [www.onsemi.com](http://www.onsemi.com)

### TECHNICAL SUPPORT

**North American Technical Support:**

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

**Europe, Middle East and Africa Technical Support:**

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative