

スパークギャップ SPARK GAPS

OPERATING TEMP. -30~+85°C



特長 FEATURES

- 自己消火性樹脂を用い、安全性が高い
- もれ電流が極めて小さい
- 静電容量が極めて小さい
- Very safe due to self-extinguishing resin
- Leakage current is very small.
- Electrostatic capacitance is very small.

用途 APPLICATIONS

- CRT周辺の異常電圧吸収
- Used to absorb abnormal voltages in the periphery of a CRT

形名表記法 ORDERING CODE

1

形式

AG	スパークギャップ
----	----------

2

外径形状

15	外形寸法毎の各タイプ
20	

3

樹脂材料

P	アルキド樹脂
---	--------

4

被覆状態

△	樹脂キャップなし
C	樹脂キャップ付

△=スペース

5

公称放電開始電圧 [VDC]

122	1200
492	4900

6

放電電圧許容差 [V]

F	±500
G	±800

7

包装

△ー	20タイプ単品(袋詰め)
Sー	15タイプ単品(袋詰め)
Bー	15タイプテーピング品

△=スペース

8

リード形状 [mm]

	形状	間隔	径	長さ
H3D	Hフォーミング	6.4	0.65	5.0±0.8
L3N	ストレート	6.4	0.65	24以上
K2M	Kフォーミング	5.0	0.60	20以上
K2U	Kフォーミング	5.0	0.60	5.0±1
K4M	Kフォーミング	6.4	0.60	20以上
K4U	Kフォーミング	6.4	0.60	5.0±1

A	G	1	5	P	C	1	2	2	F	S	—	K	2	M
1	2	3	4	5	6	7	8							
1		4		6		8								
Type		Coating conditions		Discharge voltage		Lead configuration [mm]								
AG Spark gaps		△ without resin cap		Tolerance [V]										
		C with resin cap		F ±500		H3D H-formed 6.4 0.65 5.0±0.8								
		△=Blank space		G ±800		L3N Straight 6.4 0.65 24Min.								
2						K2M K-formed 5.0 0.60 20Min.								
External dimension						K2U K-formed 5.0 0.60 5.0±1								
15 Type by external		5		7		K4M K-formed 6.4 0.60 20Min.								
20 dimension		Nominal discharge		Packaging		K4U K-formed 6.4 0.60 5.0±1								
		starting voltage [VDC]												
		122 1200		△— Type 20, bulk										
		492 4900		S— Type 15, bulk										
				B— Type 15, taped										
				△=Blank space										
3														
Resin material														
P Alkyd resin														

