

### ● General Description

The AGM15T06H combines advanced trench MOSFET technology with a low resistance package to provide extremely low  $R_{DS(ON)}$ .

This device is ideal for load switch and battery protection applications.

### ● Features

- Advance high cell density Trench technology
- Low  $R_{DS(ON)}$  to minimize conductive loss
- Low Gate Charge for fast switching
- Low Thermal resistance



### ● Application

- MB/VGA Vcore
- SMPS 2<sup>nd</sup> Synchronous Rectifier
- POL application
- BLDC Motor driver

### Product Summary

BVDSS	RDSON	ID
150V	6.3mΩ	160A

### TO-263 Pin Configuration



### Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
AGM15T06H	AGM15T06H	TO-263	---	---	800

**Table 1. Absolute Maximum Ratings (TA=25°C)**

Symbol	Parameter	Value	Unit
VDS	Drain-Source Voltage (VGS=0V)	150	V
VGS	Gate-Source Voltage (VDS=0V)	±20	V
ID	Drain Current-Continuous(Tc=25°C) <b>(Note 1)</b>	160	A
	Drain Current-Continuous(Tc=100°C)	95	A
IDM (pluse)	Drain Current-Continuous@ Current-Pulsed <b>(Note 2)</b>	500	A
PD	Maximum Power Dissipation(Tc=25°C)	250	w
	Maximum Power Dissipation(Tc=100°C)	100	w
EAS	Avalanche energy <b>(Note 3)</b>	520	mJ
TJ,TSTG	Operating Junction and Storage Temperature Range	-55 To 150	°C

**Table 2. Thermal Characteristic**

Symbol	Parameter	Typ	Max	Unit
RθJA	Thermal Resistance Junction-ambient (Steady State) <sup>1</sup>	---	60	°C/W
RθJC	Thermal Resistance Junction-Case <sup>1</sup>	---	0.5	°C/W


**Table 3. Electrical Characteristics (TA=25°C unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
<b>On/Off States</b>						
BVDSS	Drain-Source Breakdown Voltage	VGS=0V ID=250μA	150	--	--	V
IDSS	Zero Gate Voltage Drain Current	VDS=150V,VGS=0V	--	--	1	μA
IGSS	Gate-Body Leakage Current	VGS=±20V,VDS=0V	--	--	±100	nA
VGS(th)	Gate Threshold Voltage	VDS=VGS,ID=250μA	2.0	2.8	4.0	V
gFS	Forward Transconductance	VDS=5V,ID=20A	--	18	--	S
RDS(on)	Drain-Source On-State Resistance	VGS=10V, ID=20A	--	6.3	7.5	mΩ
		VGS=4.5V, ID=15A	--	7.5	12	mΩ
<b>Dynamic Characteristics</b>						
Ciss	Input Capacitance	VDS=75V,VGS=0V, F=1MHZ	--	5025	--	pF
Coss	Output Capacitance		--	410	--	pF
Crss	Reverse Transfer Capacitance		--	10	--	pF
Rg	Gate resistance	VGS=0V, VDS=0V,f=1.0MHz	--	--	--	Ω
<b>Switching Times</b>						
td(on)	Turn-on Delay Time	VGS=10V,VDS=75V, ID=80A,RGEN=6Ω	--	25	--	nS
tr	Turn-on Rise Time		--	31	--	nS
td(off)	Turn-Off Delay Time		--	60	--	nS
tf	Turn-Off Fall Time		--	20	--	nS
Qg	Total Gate Charge	VGS=10V, VDS=75V, ID=80A	--	19	--	nC
Qgs	Gate-Source Charge		--	11	--	nC
Qgd	Gate-Drain Charge		--	12	--	nC
<b>Source-Drain Diode Characteristics</b>						
ISD	Source-Drain Current(Body Diode)		--	--	160	A
VSD	Forward on Voltage	VGS=0V,IS=80A	--	--	1.5	V
trr	Reverse Recovery Time	IF=80A , dI/dt=100A/μs , TJ=25°C	--	--	--	ns
Qrr	Reverse Recovery Charge		--	--	--	nc


Notes 1.The maximum current rating is package limited.

Notes 2.Repetitive Rating: Pulse width limited by maximum junction temperature


Notes 3.EAS condition: TJ=25°C

**Diagram 1: Power dissipation**



$$P_{tot}=f(T_c)$$

**Diagram 2: Max. transient thermal impedance**






$$Z_{thJC}=f(t_p); \text{ parameter: } D= t_p/T$$


**Diagram 3: Safe operating area**


$$I_D=f(V_{GS}); T_j=25^\circ\text{C}; D=0; \text{ parameter: } t_p$$


**Diagram 4: Typ. output characteristics**


$$I_D=f(V_{GS}); T_j=25^\circ\text{C}; \text{ parameter: } V_{DS}$$


**Diagram 5: Typ. transfer characteristics**

 $I_D=f(V_{GS}); V_{DS}=5V; \text{parameter: } T_j$ 
**Diagram 6: Gate threshold voltage vs. Junction temperature**

 $V_{th}=f(T_j); I_D=250\mu\text{A}$ 
**Diagram 7: On-state resistance vs. Drain current**

 $R_{DS(on)}=f(I_D); T_j=25^\circ\text{C}; \text{parameter: } V_{GS}$ 
**Diagram 8: On-state resistance vs. Junction temperature**

 $R_{DS(on)}=f(T_j); I_D=20A; V_{GS}=10V$

**Diagram 9: Forward characteristics of reverse diode**



$$I_F = f(V_{SD}); \text{ parameter: } T_j$$

**Diagram 10: On-state resistance vs. V<sub>GS</sub> characteristics**




$$R_{DS(on)} = f(V_{GS}); I_D = 20A; \text{ parameter: } T_j$$

**Diagram 11: Breakdown Voltage Variation vs. Temperature**


$$V_{BR(DSS)} = f(T_j); I_D = 250\mu A$$

**Diagram 12: Maximum Drain Current**


$$I_D = f(T_c); V_{GS} = 10V$$

**Diagram 13: Typ. capacitances**

 $C=f(V_{DS}); V_{GS}=0V; f=1MHz$ 
**Diagram 14: Typ. gate charge**

 $V_{GS}=f(Q_{gate}); I_D=20A \text{ pulsed}; V_{DS}=75V$

**Table 7. Diode characteristics**

Test circuit for diode characteristics	Diode recovery waveform

**Table 8. Switching times**


Switching times test circuit for inductive load	Switching times waveform

**Table 9. Unclamped inductive load**

Unclamped inductive load test circuit	Unclamped inductive waveform

## TO-263 PACKAGE INFORMATION

Dimensions in mm unless otherwise specified



Symbol	Min	Nom	Max
A	9.66	9.97	10.28
B	1.02	1.17	1.32
C	8.59	9.00	9.40
D1	1.14	1.27	1.40
D2	0.70	0.83	0.95
D3		5.08	
E	15.09	15.24	15.39
F	1.15	1.28	1.40
G	4.30	4.50	4.70
H	2.29	2.54	2.79
I		0.25	
K	1.30	1.45	1.60
a1	0.45	0.55	0.65
a2(degree)	0°		8°




Disclaimer:

The information provided in this document is believed to be accurate and reliable. however, Shenzhen Core Control Electronics Technology Co., Ltd. does not assume any responsibility for the following consequences Do not consider the use of such information or use beyond its scope.

The information mentioned in this document may be changed at any time without notice.

The products and information provided in this document do not infringe patents. Shenzhen Core Control Electronics Technology Co., Ltd. assumes no responsibility for any infringement of any other rights of third parties. The result of using such products and information.

This document is the second version issued on May 10, 2022. This document replaces and Replace all previously provided information.

 It is a registered trademark of Shenzhen Core Control Electronics Technology Co., Ltd.

Copyright © 2017 Shenzhen Core Control Electronics Technology Co., Ltd. all rights reserved.