

**Features**

- On-chip Hall sensor with two different sensitivity and hysteresis settings for AH276
- Built-in protecting diode only for chip reverse power connecting
- -20°C to 85°C operating temperature
- Lead Free Finish/RoHS Compliant for Lead Free products (Note 1)
- Lead Free Package: SIP-4L

**General Description**

AH276 are integrated Hall sensors with output drivers, mainly designed for electronic commutation of brush-less DC Fan. This IC internally includes the regulator, protecting diode, Hall plate, amplifier, comparator, and a pair of complementary open-collector outputs (**DO**, **DOB**).


While the magnetic flux density (**B**) is larger than operate point (**Bop**), **DO** will turn on (low), and meanwhile **DOB** will turn off (high). Each output is latched until **B** is lower than release point (**Brp**), and then **DO**, **DOB** transfer each state.

For DC fan application, sometimes need to test power reverse connection condition. Internal diode only protects chip-side but not for coil-side. If necessary, add one external diode to block the reverse current from coil-side.

**Applications**

- Dual-coil Brush-less DC Motor
- Dual-coil Brush-less DC Fan
- Revolution Counting
- Speed Measurement

**Ordering Information**




Note: 1. RoHS revision 13.2.2003. Glass and High Temperature Solder Exemptions Applied, see *EU Directive Annex Notes 5 and 7*.


Device	Package Code	Packaging (Note 2)	Tube/Bulk	
			Quantity	Part Number Suffix
AH276Q-P	P	SIP-4	1000	-B

- Note: 2. Pad layout as shown on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.
3. Please refer to page 4 (Magnetic Characteristics table).


**Typical Application Circuit**



**Block Diagram**



**Pin Assignment**



Front View


- 1 : Vcc
- 2 : DO
- 3 : DOB
- 4 : GND

Name	P/I/O	Pin #	Description
Vcc	P	1	Power Supply Input
DO	O	2	Output Pin
DOB	O	3	Output Pin
GND	P	4	Ground

**Absolute Maximum Ratings ( @ TA=25°C )**

Characteristics	Symbol	Rating	Unit
Supply voltage	V <sub>CC</sub>	20	V
Reverse V <sub>CC</sub> Polarity Voltage	V <sub>RCC</sub>	-20	V
Magnetic flux density	B	Unlimited	
Output "on" current*	Continuous	0.4	A
	Hold	0.5	
	Peak (Start Up)	0.7	
Operating temperature range	T <sub>A</sub>	-20~+85	°C
Storage temperature range	T <sub>s</sub>	-65~+150	°C
Package Power Dissipation (SIP-4)	P <sub>D</sub>	550	mW
Maximum Junction Temp	T <sub>j</sub>	150	°C
Thermal Resistance (SIP-4)	θ <sub>jc</sub>	227	°C/W

\*Note: 4. P<sub>d</sub> shall be within Safety Operation Area.



**Electrical Characteristics (TA=+25°C)**

Characteristic	Symbol	Conditions	Min	Typ	Max	Units
Supply Voltage	V <sub>cc</sub>	(Note 5)	3.5	-	20	V
Output Zener Breakdown	V <sub>z</sub>	(Note 6)	-	35	-	V
Output Saturation Voltage	V <sub>ce(sat)</sub>	V <sub>cc</sub> =14V, I <sub>L</sub> =400mA	-	0.6	0.9	V
Output Leakage Current	I <sub>ceX</sub>	V <sub>ce</sub> =14V, V <sub>cc</sub> =14V	-	<0.1	10	μA
Supply Current	I <sub>cc</sub>	V <sub>cc</sub> =20V, Output Open	7	16	25	mA

Note: 5. The output DO/DOB is switching as magnetic field change (S>300G, N<-300G).  
6. V<sub>z</sub> is a typical value for design reference. V<sub>z</sub> will vary with different coils design.

**Magnetic Characteristics** ( $T_A=+25^{\circ}\text{C}$ ,  $V_{CC}=14\text{V}$ , Note 7)

**A grade**

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Operate Point	Bop	10	-	50	Gauss
Release Point	Brp	-50	-	-10	Gauss
Hysteresis	Bhy	-	75	-	Gauss


**B grade**

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Operate Point	Bop	5	-	70	Gauss
Release Point	Brp	-70	-	-5	Gauss
Hysteresis	Bhy	-	75	-	Gauss

**C grade**


Characteristic	Symbol	Min.	Typ.	Max.	Unit
Operate Point	Bop	-	-	100	Gauss
Release Point	Brp	-100	-	-	Gauss
Hysteresis	Bhy	-	75	-	Gauss

Note: 7. Magnetic characteristics are for design information, which will vary with supply voltage, operating temperature and after soldering.




**Performance Characteristics (SIP-4L)**

TA (°C)	25	50	60	70	80	85	90	95	100
PD (mW)	550	440	396	352	308	286	264	242	220
TA (°C)	105	110	115	120	125	130	135	140	150
PD (mW)	198	176	154	132	110	88	66	44	0




**Marking Information**




**Sensor Location** ( unit: mm )


Active Area Depth



Package Sensor Location



**Package Information** ( unit: mm )



**IMPORTANT NOTICE**

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

**LIFE SUPPORT**

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.