


### Features

- $S_{21} = 21.2 \text{ dB @ } 824 \text{ MHz}$   
= 20.8 dB @ 849 MHz
- NF of 0.70 dB over Frequency
- Unconditionally Stable
- Single 5V Supply
- High OIP3 @ Low Current

### Description

The plerow™ ALN-series is the compactly designed surface-mount module for the use of the LNA with or without the following gain blocks in the infrastructure equipment of the mobile wireless (CDMA, GSM, PCS, PHS, WCDMA, DMB, WLAN, WiBro, WiMAX), GPS, satellite communication terminals, CATV and so on. It has an exceptional performance of low noise figure, high gain, high OIP3, and low bias current. The stability factor is always kept more than unity over the application band in order to ensure its unconditionally stable implementation to the application system environment. The surface-mount module package including the completed matching circuit and other components necessary just in case allows very simple and convenient implementation onto the system board in mass production level.



1-stage Single Type

### Specifications (in Production)

Typ. @ T = 25°C,  $V_s = 5 \text{ V}$ , Freq. = 836.5 MHz,  $Z_{o,sys} = 50 \text{ ohm}$

Parameter	Unit	Specifications		
		Min	Typ	Max
Frequency Range	MHz	824		849
Gain	dB	20	21	
Gain Flatness	dB		$\pm 0.2$	$\pm 0.3$
Noise Figure	dB		0.70	0.75
Output IP3 <sup>(1)</sup>	dBm	27	28	
S11 / S22 <sup>(2)</sup>	dB			-19 / -9
Output P1dB	dBm	14	15	
Switching Time <sup>(3)</sup>	$\mu\text{sec}$			
Supply Current	mA		40	60
Supply Voltage	V		5	
Impedance	$\Omega$		50	
Max. RF Input Power	dBm	C.W 29 ~ 31 (before fail)		
Package Type & Size	mm	Surface Mount Type, 10Wx10Lx3.8H		

Operating temperature is -40°C to +85°C.

1) OIP3 is measured with two tones at an output power of +0 dBm / tone separated by 1 MHz.

2) S11/S22 (max) is the worst value within the frequency band.


3) Switching time means the time that takes for output power to get stabilized to its final level after switching DC voltage from 0 V to  $V_s$ .

### More Information

Website: [www.asb.co.kr](http://www.asb.co.kr)  
E-mail: [sales@asb.co.kr](mailto:sales@asb.co.kr)

Tel: (82) 42-528-7223  
Fax: (82) 42-528-7222

### Outline Drawing (Unit: mm)



Pin Number	Function
2	RF In
5	RF Out
6	$V_s$
Others	Ground

Note: 1. The number and size of ground via holes in a circuit board is critical for thermal RF grounding considerations.

2. We recommend that the ground via holes be placed on the bottom of all ground pins for better RF and thermal performance, as shown in the drawing at the left side.

**Typical Performance  
(Measured)**


---

**824~849 MHz**


---

**+5 V**


### S-parameters




### S-parameters & K Factor




### Noise Figure



### OIP3



### P1dB



## RF Performance with Voltage Change

### 1. S-parameter

	824 MHz			836.5 MHz				849 MHz		
	S21 (dB)	S11 (dB)	S22 (dB)	S21 (dB)	G/F (dB)	S11 (dB)	S22 (dB)	S21 (dB)	S11 (dB)	S22 (dB)
<b>4.50 V</b>	21.27	-21.14	-10.78	21.08	0.37	-21.65	-10.41	20.90	-21.68	-10.02
<b>4.75 V</b>	21.36	-22.19	-11.14	21.18	0.37	-22.57	-10.77	20.99	-22.29	-10.35
<b>5.00 V</b>	21.41	-23.15	-11.41	21.23	0.37	-23.30	-11.03	21.04	-22.76	-10.59
<b>5.25 V</b>	21.50	-24.19	-11.76	21.32	0.36	-24.09	-11.37	21.14	-23.39	-10.91
<b>5.50 V</b>	21.55	-25.09	-12.02	21.37	0.36	-24.85	-11.63	21.19	-23.83	-11.17

### 2. OIP3, P1dB & NF

	824 MHz			836.5 MHz			849 MHz		
	OIP3 (dBm)	P1dB (dBm)	NF (dB)	OIP3 (dBm)	P1dB (dBm)	NF (dB)	OIP3 (dBm)	P1dB (dBm)	NF (dB)
<b>4.50 V</b>	27.52	15.24	0.621	26.89	15.19	0.617	27.98	15.15	0.609
<b>4.75 V</b>	28.65	15.62	0.621	28.72	15.63	0.637	28.85	15.57	0.629
<b>5.00 V</b>	29.83	16.02	0.641	29.97	15.95	0.616	30.00	15.86	0.616
<b>5.25 V</b>	30.95	16.19	0.624	31.02	16.22	0.642	31.18	16.09	0.631
<b>5.50 V</b>	31.10	16.52	0.624	31.13	16.50	0.626	31.25	16.37	0.612

Note: tested at room temperature.

## RF Performance with Operating Temperature

### 1. S-parameter


	824 MHz			836.5 MHz				849 MHz		
	S21 (dB)	S11 (dB)	S22 (dB)	S21 (dB)	G/F (dB)	S11 (dB)	S22 (dB)	S21 (dB)	S11 (dB)	S22 (dB)
<b>-45 °C</b>	21.75	-22.45	-10.89	21.54	0.37	-21.59	-10.75	21.38	-22.52	10.49
<b>-10 °C</b>	21.57	-22.25	-11.02	21.35	0.38	-22.34	-10.98	21.19	-22.32	-10.75
<b>25 °C</b>	21.48	-22.17	-11.59	21.29	0.38	-22.24	-11.14	21.10	-22.25	-10.98
<b>60 °C</b>	21.30	-21.71	-12.00	21.12	0.38	-21.55	-11.50	21.92	-21.40	-11.17
<b>85 °C</b>	21.22	-21.02	-12.21	21.03	0.37	-21.01	-11.75	20.85	-21.15	-11.36

### 2. OIP3, P1dB & NF

	824 MHz			836.5 MHz			849 MHz		
	OIP3 (dBm)	P1dB (dBm)	NF (dB)	OIP3 (dBm)	P1dB (dBm)	NF (dB)	OIP3 (dBm)	P1dB (dBm)	NF (dB)
<b>-45 °C</b>	29.68	15.92	0.379	29.23	15.85	0.425	29.57	15.77	0.451
<b>-10 °C</b>	29.51	15.85	0.451	29.15	15.72	0.563	29.41	15.65	0.577
<b>25 °C</b>	29.40	15.81	0.533	29.05	15.63	0.640	29.27	15.59	0.635
<b>60 °C</b>	28.87	15.38	0.651	28.64	15.14	0.789	28.87	15.22	0.770
<b>85 °C</b>	28.74	15.23	0.753	28.44	15.06	0.877	28.48	15.17	0.887


Note: tested at  $V_s = 5V$ .

## Application Circuit




- 1) The tantal or MLC (Multi Layer Ceramic) capacitor is optional and for bypassing the AC noise introduced from the DC supply. The capacitance value may be determined by customer's DC supply status. The capacitor should be placed as close as possible to  $V_s$  pin and be connected directly to the ground plane for the best electrical performance.
- 2) DC blocking capacitors are always necessarily placed at the input and output port for allowing only the RF signal to pass and blocking the DC component in the signal. The DC blocking capacitors are included inside the ALN module. Therefore, C1 & C2 capacitors may not be necessary, but can be added just in case that the customer wants. The value of C1 & C2 is determined by considering the application frequency.

## Recommended Soldering Reflow Process



## Evaluation Board Layout



Size 25x25mm  
(for ALN-AT, BT, T Series – 10x10mm)