



DESCRIPTION

The AM3406 is the N-Channel logic enhancement mode power field effect transistor is produced using high cell density. Advanced trench technology to provide excellent $R_{DS(ON)}$.

This high density process is especially tailored to minimize on-state resistance. These devices are particularly suited for low voltage application, and low in-line power loss are needed in a very small outline surface mount package.

The AM3406 is available in SOT-23 Package.

ORDERING INFORMATION

Package Type	Part Number	
SOT-23	E3	AM3406E3R
		AM3406E3VR
Note	R : Tape & Reel V: Green Package	
AiT provides all Pb free products Suffix " V " means Green Package		


FEATURES

- 30V/6.0A, $R_{DS(ON)} = 20m\Omega$ (typ.) @ $V_{GS} = 10V$
- 30V/4.8A, $R_{DS(ON)} = 27m\Omega$ (typ.) @ $V_{GS} = 4.5V$
- Super high density cell design for extremely low $R_{DS(ON)}$
- Exceptional on-resistance and Maximum DC current capability
- This is a Full Green compliance
- Available in SOT-23 Package

APPLICATIONS

- Power Management in Note book
- Portable Equipment
- DSC
- LCD Display inverter
- Battery Powered System
- DC/DC Converter


P CHANNEL MOSFET



N-Channel



PIN DESCRIPTION



Pin #	Symbol	Function
1	G	Gate
2	S	Source
3	D	Drain



ABSOLUTE MAXIMUM RATINGS

T_A = 25°C unless otherwise noted

V _{DSS} , Drain-Source Voltage	30V
V _{GSS} , Gate-Source Voltage	±20V
I _D , Continuous Drain Current (T _J =150°C)	V _{GS} = 10V 6.0A
I _{DM} , Pulsed Drain Current	10A
I _S , Continuous Source Current (Diode Conduction)	5.0A
P _D , Power Dissipation	
T _A = 25°C	1.25W
T _A = 70°C	0.8W
T _J , Operation Junction Temperature	150°C
T _{STG} , Storage Temperature Range	-55°C ~ 150°C

Stress beyond above listed "Absolute Maximum Ratings" may lead permanent damage to the device. These are stress ratings only and operations of the device at these or any other conditions beyond those indicated in the operational sections of the specifications are not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

THERMAL DATA

Symbol	Parameter	Max	Unit
R _{θJA}	Thermal Resistance-Junction to Ambient	90	°C/W



ELECTRICAL CHARACTERISTICS

T_A = 25°C unless otherwise noted

Parameter	Symbol	Conditions	Min	Typ.	Max	Units
Static Parameters						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250μA	30	-	-	V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	1.0	-	2.0	V
Gate Leakage Current	I _{GSS}	V _{DS} = 0V, V _{GS} = ±20V	-	-	±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 30V, V _{GS} = 0V	-	-	1	μA
		V _{DS} = 30V, V _{GS} = 0V T _J = 55°C	-	-	5	
On-State Drain Current	I _{D(ON)}	V _{DS} ≥ -5V, V _{GS} = -4.5V	10	-	-	A
Drain-source On-Resistance	R _{DS(ON)}	V _{GS} = 10V, I _D = 6.0A	-	20	26	mΩ
		V _{GS} = 4.5V, I _D = 4.8A	-	27	33	
Forward Transconductance	G _{fs}	V _{DS} = 15V, I _D = 5.0A	-	12	-	S
Source-Drain Diode						
Diode Forward Voltage	V _{SD}	I _S = 1.7A, V _{GS} = 0V	-	0.7	1.2	V
Dynamic Parameters						
Total Gate Charge	Q _g	V _{DS} = 20V	-	6	-	nC
Gate-Source Charge	Q _{gs}	V _{GS} = 4.5V	-	1.1	-	
Gate-Drain Charge	Q _{gd}	I _D = 5A	-	2.5	-	
Input Capacitance	C _{iss}	V _{DS} = 15V V _{GS} = 0V f = 1MHz	-	414	-	pF
Output Capacitance	C _{oss}		-	60	-	
Reverse Transfer Capacitance	C _{rss}		-	49	-	
Turn-On Time	t _{d(on)}	V _{DD} = 12V	-	7.5	-	nS
	t _r	I _D = 5A	-	45	-	
Turn-Off Time	t _{d(off)}	V _{GS} = 10V	-	10	-	
	t _f	R _G = 3Ω	-	4	-	

NOTE1: Pulse test: pulse width ≤ 300μs, duty cycle ≤ 2%


NOTE2: Static parameters are based on package level with recommended wire-bonding




TYPICAL CHARACTERISTICS

25°C Unless Note


1. Output Characteristics




2. Drain-Source On Resistance




3. Gate Threshold Voltage




4. Gate Charge



5. Drain Source On Resistance




6. Capacitance







7. Power Dissipation



8. Drain Current




9. Thermal Transient Impedance





PACKAGE INFORMATION

Dimension in SOT-23 Package (Unit: mm)



SYMBOL	MIN	MAX
A	1.050	1.250
A1	0.000	0.100
A2	1.050	1.150
b	0.300	0.500
c	0.100	0.200
D	2.820	3.020
E	1.500	1.700
E1	2.650	2.950
e	0.950(BSC)	
e1	1.800	2.000
L	0.300	0.600
θ	0°	8°



IMPORTANT NOTICE

AiT Semiconductor Inc. (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Semiconductor Inc.'s integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Semiconductor Inc. assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.