

## P-Channel 60-V (D-S) MOSFET

### Key Features:



- Low  $r_{DS(on)}$  trench technology
- Low thermal impedance
- Fast switching speed

### Typical Applications:

- White LED boost converters
- Automotive Systems
- Industrial DC/DC Conversion Circuits



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**



| PRODUCT SUMMARY |                            |           |
|-----------------|----------------------------|-----------|
| $V_{DS}$ (V)    | $r_{DS(on)}$ (m $\Omega$ ) | $I_D$ (A) |
| -60             | 180 @ $V_{GS} = -10V$      | -2.7      |
|                 | 255 @ $V_{GS} = -4.5V$     | -2.3      |

| ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED) |                          |                |            |                  |
|---|--------------------------|----------------|------------|------------------|
| Parameter   |                          | Symbol         | Limit      | Units            |
| Drain-Source Voltage  |                          | $V_{DS}$       | -60        | V                |
| Gate-Source Voltage   |                          | $V_{GS}$       | $\pm 20$   |                  |
| Continuous Drain Current <sup>a</sup>                                       | $T_A = 25^\circ\text{C}$ | $I_D$          | -2.7       | A                |
|   | $T_A = 70^\circ\text{C}$ |                | -2.2       |                  |
| Pulsed Drain Current <sup>b</sup>   |                          | $I_{DM}$       | -15        |                  |
| Continuous Source Current (Diode Conduction) <sup>a</sup>                   |                          | $I_S$          | -2.5       | A                |
| Power Dissipation <sup>a</sup>  | $T_A = 25^\circ\text{C}$ | $P_D$          | 2          | W                |
|   | $T_A = 70^\circ\text{C}$ |                | 1.3        |                  |
| Operating Junction and Storage Temperature Range                            |                          | $T_J, T_{stg}$ | -55 to 150 | $^\circ\text{C}$ |

| THERMAL RESISTANCE RATINGS               |                 |                 |         |                    |
|--|-----------------|-----------------|---------|--------------------|
| Parameter                                |                 | Symbol          | Maximum | Units              |
| Maximum Junction-to-Ambient <sup>a</sup> | $t \leq 10$ sec | $R_{\theta JA}$ | 62.5    | $^\circ\text{C/W}$ |
|  | Steady State    |                 | 110     |                    |

### Notes

- Surface Mounted on 1" x 1" FR4 Board.
- Pulse width limited by maximum junction temperature

## Electrical Characteristics


| Parameter                       | Symbol       | Test Conditions  | Min | Typ   | Max       | Unit       |
|---------------------------------|--------------|--|-----|-------|-----------|------------|
| <b>Static</b>                   |              |  |     |       |           |            |
| Gate-Source Threshold Voltage   | $V_{GS(th)}$ | $V_{DS} = V_{GS}, I_D = -250 \mu A$  | -1  |       |           | V          |
| Gate-Body Leakage               | $I_{GSS}$    | $V_{DS} = 0 V, V_{GS} = \pm 20 V$  |     |       | $\pm 100$ | nA         |
| Zero Gate Voltage Drain Current | $I_{DSS}$    | $V_{DS} = -48 V, V_{GS} = 0 V$   |     |       | -1        | uA         |
|                                 |              | $V_{DS} = -48 V, V_{GS} = 0 V, T_J = 55^\circ C$   |     |       | -25       |            |
| On-State Drain Current          | $I_{D(on)}$  | $V_{DS} = -5 V, V_{GS} = -10 V$  | -5  |       |           | A          |
| Drain-Source On-Resistance      | $r_{DS(on)}$ | $V_{GS} = -10 V, I_D = -2.4 A$   |     |       | 180       | m $\Omega$ |
|                                 |              | $V_{GS} = -4.5 V, I_D = -2 A$  |     |       | 255       |            |
| Forward Transconductance        | $g_{fs}$     | $V_{DS} = -15 V, I_D = -2.4 A$   |     | 10    |           | S          |
| Diode Forward Voltage           | $V_{SD}$     | $I_S = -1.3 A, V_{GS} = 0 V$   |     | -0.83 |           | V          |
| <b>Dynamic</b>                  |              |  |     |       |           |            |
| Total Gate Charge               | $Q_g$        | $V_{DS} = -30 V, V_{GS} = -4.5 V,$<br>$I_D = -2.4 A$   |     | 4.9   |           | nC         |
| Gate-Source Charge              | $Q_{gs}$     |  |     | 1.6   |           |            |
| Gate-Drain Charge               | $Q_{gd}$     |  |     | 2.5   |           |            |
| Turn-On Delay Time              | $t_{d(on)}$  | $V_{DS} = -30 V, R_L = 12.5 \Omega,$<br>$I_D = -2.4 A,$<br>$V_{GEN} = -10 V, R_{GEN} = 6 \Omega$ |     | 6     |           | ns         |
| Rise Time                       | $t_r$        |  |     | 5     |           |            |
| Turn-Off Delay Time             | $t_{d(off)}$ |  |     | 18    |           |            |
| Fall Time                       | $t_f$        |  |     | 6     |           |            |
| Input Capacitance               | $C_{iss}$    | $V_{DS} = -15 V, V_{GS} = 0 V, f = 1 MHz$  |     | 385   |           | pF         |
| Output Capacitance              | $C_{oss}$    |  |     | 40    |           |            |
| Reverse Transfer Capacitance    | $C_{rss}$    |  |     | 28    |           |            |

## Notes


- Pulse test: PW  $\leq$  300us duty cycle  $\leq$  2%.
- Guaranteed by design, not subject to production testing.

**Analog Power (APL) reserves the right to make changes without further notice to any products herein. APL makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does APL assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in APL data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. APL does not convey any license under its patent rights nor the rights of others. APL products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the APL product could create a situation where personal injury or death may occur. Should Buyer purchase or use APL products for any such unintended or unauthorized application, Buyer shall indemnify and hold APL and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that APL was negligent regarding the design or manufacture of the part. APL is an Equal Opportunity/Affirmative Action Employer.**


Typical Electrical Characteristics




1. On-Resistance vs. Drain Current




2. Transfer Characteristics




3. On-Resistance vs. Gate-to-Source Voltage



4. Drain-to-Source Forward Voltage




5. Output Characteristics




6. Capacitance


Typical Electrical Characteristics




7. Gate Charge




8. Normalized On-Resistance Vs Junction Temperature



9. Safe Operating Area




10. Single Pulse Maximum Power Dissipation





11. Normalized Thermal Transient Junction to Ambient

Package Information



| DIM.   | MILLIMETERS |      |      |
|--------|-------------|------|------|
|        | MIN         | NOM  | MAX  |
| A      | 0.935       | ---  | 1.10 |
| A1     | 0.01        | ---  | 0.10 |
| A2     | 0.70        | ---  | 1.00 |
| b      | 0.25        | 0.32 | 0.40 |
| c      | 0.10        | 0.15 | 0.20 |
| D      | 2.95        | 3.05 | 3.10 |
| E      | 2.70        | 2.85 | 2.98 |
| E1     | 1.55        | 1.65 | 1.70 |
| e      | 0.95 BSC    |      |      |
| L      | 0.30        | ---  | 0.60 |
| L1     | 0.60REF     |      |      |
| L2     | 0.25BSC     |      |      |
| R      | 0.10        | ---  | ---  |
| theta  | 0?          | 4?   | 8?   |
| theta1 | 7? NDM      |      |      |



Note:

1. All Dimension Are In mm.
2. Package Body Sizes Exclude Mold Flash, Protrusion Or Gate Burrs. Mold Flash, Protrusion Or Gate Burrs Shall Not Exceed 0.10 mm Per Side.
3. Package Body Sizes Determined At The Outermost Extremes Of The Plastic Body Exclusive Of Mold Flash, Tie Bar Burrs, Gate Burrs And Interlead Flash, But Including Any Mismatch Between The Top And Bottom Of The Plastic Body.
4. The Package Top May Be Smaller Than The Package Bottom.
5. Dimension "B" Does Not Include Dambar Protrusion. Allowable Dambar Protrusion Shall Be 0.08 mm Total In Excess Of "B" Dimension At Maximum Material Condition. The Dambar Cannot Be Located On The Lower Radius Of The Foot.