

**AMC7635****300mA CMOS****Low DROPOUT REGULATOR****DESCRIPTION**


The AMC7635 of positive, linear regulator features low noise and low dropout voltage, making it ideal for battery applications. The space-saving SOT-23-5 package is attractive for "Pocket" and "Hand Held" applications.

In applications requiring a low noise, regulated supply, place a 1000pF capacitor between Bypass and Ground.

The AMC7635 is stable with an output capacitance of 2.2 μ F or greater.

FEATURES


- Guaranteed 300mA Output
- Accurate to within 1.5%
- Very Low Dropout Voltage
- Over-Temperature Shutdown
- Power-Saving Shutdown Mode
- Current Limiting
- Noise Reduction Bypass Capacitor
- Factory Pre-set Output Voltages
- Low Temperature Coefficient
- Available in SOT-23-5 packages

TYPICAL APPLICATION CIRCUIT**APPLICATIONS**

- Wireless Devices
- Portable Electronics
- Cordless Phones
- PC Peripherals
- Battery Powered Widgets
- Electronic Scales
- Instrumentation

VOLTAGE OPTIONS


AMC7635-1.5	- 1.5V Fixed
AMC7635-1.8	- 1.8V Fixed
AMC7635-2.0	- 2.0V Fixed
AMC7635-2.5	- 2.5V Fixed
AMC7635-2.8	- 2.8V Fixed
AMC7635-3.0	- 3.0V Fixed
AMC7635-3.1	- 3.1V Fixed
AMC7635-3.3	- 3.3V Fixed
AMC7635	- Adjustable Output

PACKAGE PIN OUT

5-Pin Plastic SOT-23-5
Surface Mount
(Top View)

ORDER INFORMATION

T _A (°C)	DB	Plastic SOT-23-5
		5-pin
0 to 70	AMC7635-X.XDBFT (Lead Free)	
Note: 1. All surface-mount packages are available in Tape & Reel. Append the letter "T" to part number (i.e. AMC7635-X.XDBT).		
Note: 2. The letter "F" is marked for Lead Free process.		

BLOCK DIAGRAM**ABSOLUTE MAXIMUM RATINGS** (Note)

Input Voltage, V _{IN}	7V
Operating Junction Temperature Range, T _J	0 °C to 150 °C
Storage Temperature Range, T _{STG}	-65 °C to 150 °C
Lead Temperature (soldering, 10 seconds)	260 °C

Note: Exceeding these ratings could cause damage to the device. All voltages are with respect to Ground.
Currents are positive into, negative out of the specified terminal.

POWER DISSIPATION TABLE

DB PACKAGE:		
Thermal Resistance from Junction to Ambient, θ _{JA}	220°C/W	
Junction Temperature Calculation: T _J = T _A + (PD × θ _{JA}). The θ _{JA} numbers are guidelines for the thermal performance of the device/pc-board system. Connect the ground pin to ground using a large pad or ground plane for better heat dissipation. All of the above assume no ambient airflow.		

RECOMMENDED OPERATING CONDITIONS

Parameter	Symbol	Min.	Typ.	Max.	Units
Input Voltage	V _{IN}	V _{OUT} + ΔV		6	V
Load Current (with adequate heat-sinking)	I _O	5			mA
Junction temperature	T _J			125	°C



AMC7635

ELECTRICAL CHARACTERISTICS

$V_{IN} = V_{OUT(Nominal)} + 0.5V$, $V_{IN,MAX} = 6V$, $T_A = 25^\circ C$ (unless otherwise noted)							
Parameter	Symbol	Test Conditions		Min	Typ	Max	Units
Output Voltage Accuracy	V_{OUT}	$I_O = 1mA$		-1.5		+1.5	%
		$I_O = 1$ to $300mA$		-2.5		+2.5	
Line Regulation	$\frac{\Delta V_{OUT}}{\Delta V_I V_{OUT}}$	$I_O = 1mA$, $V_{OUT} + 0.5V < V_{IN} < 6V$			0.15	0.35	%/V
Load Regulation	ΔV_{OUT}	$1mA \leq I_O \leq 300mA$			10	70	mV
Dropout Voltage	ΔV	$I_O=150mA$, $V_{OUT}=V_{OUT(NOM)}-2.0\%$	$V_{OUT(NOM)} \leq 2.0V$	330	500		mV
			$2.0V < V_{OUT(NOM)} \leq 2.5V$	220	350		
			$V_{OUT(NOM)} > 2.5V$	165	250		
		$I_O=300mA$, $V_{OUT}=V_{OUT(NOM)}-2.0\%$	$V_{OUT} \leq 2.0V$		1300		
			$2.0V < V_{OUT} \leq 2.5V$		900		
			$V_{OUT} > 2.5V$		600		
Maximum Output Current	I_O	$V_{OUT} > 0.96 \times V_{RATING}$		300			mA
Current Limit	I_{LIMIT}	$V_{OUT} > 1.2V$		300	400		
Ground Pin Current	I_Q	$I_O = 0mA \sim 10mA$		50	100		μA
		$I_O = 10mA \sim 150mA$		100	150		
		$I_O = 150mA \sim 300mA$		120	180		
Output Shutdown Delay		$C_{BP} = 0\mu F$, $C_{OUT} = 1\mu F$, $I_O = 100mA$		600			μS
EN "high" Bias Current	I_{IH}	$V_{EN} = V_{IN}$				0.1	μA
EN "low" Bias Current	I_{IL}	$V_{EN} = 0V$				0.5	
Shutdown Supply Current		$V_{EN} = GND$		0.01	1		μA
EN "low" Input Threshold	V_{IL}	$V_{IN} = 2.5$ to $5.5V$		0		0.4	V
EN "high" Input Threshold	V_{IH}	$V_{IN} = 2.5$ to $5.5V$		2		V_{IN}	
Power Supply Rejection Ratio	$PSRR$	$I_O=100mA$ $C_{BP}=0.01\mu F$ $C_{OUT}=2.2\mu F$	$f = 1kHz$	60			dB
			$f = 10kHz$	50			
			$f = 100kHz$	40			
Thermal Protection Temperature				150			$^\circ C$
Thermal Protection Temperature Hysteresis				30			

Note 1: For the adjustable device, the minimum load current is the minimum current required to maintain regulation. Normally the current in the resistor divider used to set the output voltage is selected to meet the minimum load current requirement.

Note 2: These parameters, although guaranteed, are not tested in production.




AMC7635

CHARACTERIZATION CURVES

Unless otherwise specified, $V_{IN} = 5V$, $C_{IN} = 1\mu F$, $C_{BP} = 0.01\mu F$, $C_{OUT} = 2.2\mu F$, $T_A = 25^{\circ}C$.


Chip Enable Transient Response

$V_{IN}=5V$, $C_{IN}=1\mu F$, $C_{OUT}=2.2\mu F$, $C_{BYP}=1000pF$




Chip Enable Transient Response

$V_{IN}=5V$, $C_{IN}=1\mu F$, $C_{OUT}=2.2\mu F$, $C_{BYP}=Open$




Short Circuit Response

$V_{IN}=5V$, $C_{IN}=1\mu F$, $C_{OUT}=2.2\mu F$, $C_{BP}=0.01\mu F$




Over Temperature Shutdown

$V_{IN}=5V$, $C_{IN}=1\mu F$, $C_{OUT}=2.2\mu F$, $C_{BYP}=0.01\mu F$




Load Step (1mA~300mA)







$V_{IN}=5V$, $C_{IN}=2.2\mu F$, $C_{OUT}=2.2\mu F$, $C_{BYP}=0.01\mu F$



Line Transient Response




$V_{IN,AVE}=5V$, $C_{IN}=2.2\mu F$, $C_{OUT}=2.2\mu F$, $C_{BYP}=0.01\mu F$



Ground Pin Current vs. Temperature**Ground Current vs. Input Voltage****Drop Out Voltage vs. Load Current****Safe Operating Area****Dropout Voltage vs. Temperature****Drop Out Voltage vs. Output Voltage**




AMC7635





APPLICATION INFORMATION



♦ Detailed Description

The AMC7635 CMOS low dropout regulator contains a PMOS pass transistor, a voltage reference, an error amplifier, over-current protection, and thermal shutdown circuit.

The P-channel pass transistor receives data from the error amplifier, over-current shutdown, and thermal protection circuits. During normal operation, the error amplifier compares the output voltage to a precision reference. Thermal shutdown and over-current circuits become active when the junction temperature exceeds 150°C, or the current exceeds 300mA. During thermal shutdown, the output voltage remains low. Normal operation is restored when the junction temperature drops below 120°C.

♦ External Capacitors

The AMC7635 is stable with an output capacitor to ground of 2.2μF or greater. Ceramic capacitors have the lowest ESR, and will offer the best AC performance. Conversely, Aluminum Electrolytic capacitors exhibit the highest ESR, resulting in the poorest AC response. Unfortunately, large value ceramic capacitors are comparatively expensive. One option is to parallel a 0.1μF ceramic capacitor with a 10μF Aluminum Electrolytic. The benefit is low ESR, high capacitance, and low over-all cost.

A second capacitor is recommended between the input and ground to stabilize V_{IN}. The input capacitor should be at least 0.1μF to have a beneficial effect.

A third capacitor can be connected between the BP pin and GND. This capacitor can be a low cost Polyester Film variety between the value of 0.001 ~ 0.01μF. A larger capacitor improves the AC ripple rejection, but also makes the output come up slowly. This "Soft" turn-on is desirable in some applications to limit turn-on surges.

All capacitors should be placed in close proximity to the pins. A "Quiet" ground termination is desirable. This can be achieved with a "Star" connection.

♦ EN

The EN pin is normally pulled to high. When shutdown, pulled low, the PMOS pass transistor shuts off, and all internal circuits are powered down. In this state, the quiescent current is less than 1μA. This pin behaves much like an electronic switch.



AMC7635

PACKAGE

5-Pin SOT-23-5

SEATING PLANE

GAUGE PLANE

	INCHES			MILLIMETERS		
	MIN	TYP	MAX	MIN	TYP	MAX
A	-	-	0.057	-	-	1.45
A1	-	-	0.006	-	-	0.15
A2	0.035	0.045	0.051	0.90	1.15	1.30
b	0.012	-	0.020	0.30	-	0.50
c	0.003	-	0.009	0.08	-	0.22
D	0.114 BSC			2.90 BSC		
E	0.110 BSC			2.80 BSC		
E1	0.063 BSC			1.60 BSC		
e	0.037 BSC			0.95 BSC		
e1	0.075 BSC			1.90 BSC		
L	0.012	0.018	0.024	0.30	0.45	0.60
L1	0.024 REF			0.60 REF		
L2	0.010 BSC			0.25 BSC		
°M	5°	10°	15°	5°	10°	15°



AMC7635

IMPORTANT NOTICE

ADDtek reserves the right to make changes to its products or to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

A few applications using integrated circuit products may involve potential risks of death, personal injury, or severe property or environmental damage. ADDtek integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life-support applications, devices or systems or other critical applications. Use of ADDtek products in such applications is understood to be fully at the risk of the customer. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

ADDtek assumes no liability to customer product design or application support. ADDtek warrants the performance of its products to the specifications applicable at the time of sale.

ADDtek Corp.
9F, No. 20, Sec. 3, Bade Rd., Taipei, Taiwan, 105
TEL: 2-25700299
FAX: 2-25700196
