



## AME5110

## 600mA / 1.2MHz PWM Buck DC-DC Converter

### ■ General Description

The AME5110 family of Fixed Frequency, High Efficiency, Synchronous Buck, DC-DC Converters, apply the latest innovations in Current-Mode Technology. Available in SOT-25 package, these devices are typically twice as efficient as standard LDO's, making them well suited for most portable applications.

The AME5110 is simple to use. As with standard LDO's, (1) Input, and (1) Output capacitor are required. The only other element is a small, low cost, 2.2µH inductor. The AME5110 is available with fixed output voltages of 1.5V and 1.8V, or adjustable at 600mA. Using a proprietary "Extreme Green" Technology, battery life is maximized with Frequency Foldback at light Load, and 100% duty when  $V_{in}$  approaches  $V_{out}$ .

### ■ Features


- High Efficiency "Extreme Green"
- 2.5V to 5.5V Input
- Short Circuit Protection
- Over-Temperature Shutdown
- Under-Voltage Lockout
- Superb Transient Response
- All AME's Lead Free Products Meet RoHS Standards

### ■ Applications


- Cellular Phones
- Digital Cameras
- Portable Electronics
- USB Devices
- MP3 Players
- LDO Replacement

### ■ Typical Application

#### Fixed Voltage Version




#### Adjustable Voltage Version




$$V_{OUT} = V_{FB} \frac{(R1+R2)}{R2}$$

**AME5110**


■ **Function Diagram**



**■ Pin Configuration**

**AME5110AEEVxxx**

1. EN
2. GND
3. SW
4.  $V_{IN}$
5.  $V_{OUT}$

**\* Die Attach:  
Conductive Epoxy**



**AME5110BEEVADJ**

1. EN
2. GND
3. SW
4.  $V_{IN}$
5.  $V_{FB}$

**\* Die Attach:  
Conductive Epoxy**

**■ Pin Description**

| Pin Number     |                | Pin Name  | Pin Description  |
|----------------|----------------|-----------|--|
| AME5110AEEVxxx | AME5110BEEVADJ |           |  |
| 1              | 1              | EN        | Enable Control Input.<br>Forcing this pin above 1.5V enables the part. Forcing this pin below 0.3V shuts down the device. In shutdown, all functions are disabled drawing <math><1\mu A</math> supply current. Do not leave EN floating. |
| 2              | 2              | GND       | Ground Pin   |
| 3              | 3              | SW        | Switch Node Connection to Inductor.<br>This pin connects to the drains of the internal main and synchronous power MOSFET switches.   |
| 4              | 4              | $V_{IN}$  | Main Supply Pin.<br>Must be closely decoupled to GND, Pin2, with a 2.2 $\mu F$ or greater ceramic capacitor.   |
| N/A            | 5              | $V_{FB}$  | Feedback Pin.<br>Receives the feedback voltage from an external resistive divider across the output.   |
| 5              | N/A            | $V_{OUT}$ | Output Voltage for fixed version   |

**AME5110**
**■ Ordering Information**


| Pin Configuration   | Operating Ambient Temperature Range | Package Type | Number of Pins | Output Voltage                            | Special Feature                            |
|---|-------------------------------------|--------------|----------------|---|--|
| <b>A</b><br>(SOT-25) 1. EN<br>2. GND<br>3. SW<br>4. V <sub>IN</sub><br>5. V <sub>OUT</sub><br><br><b>B</b><br>(SOT-25) 1. EN<br>2. GND<br>3. SW<br>4. V <sub>IN</sub><br>5. V <sub>FB</sub> | E: -40°C to 85°C                    | E: SOT-2X    | V: 5           | 150: 1.5V<br>180: 1.8V<br>ADJ: Adjustable | Y: Lead free & Low profile<br>Z: Lead free |

**■ Ordering Information**

| Part Number     | Marking* | Output Voltage | Package | Operating Ambient Temperature Range |
|-----------------|----------|----------------|---------|-------------------------------------|
| AME5110AEEV150Y | BARww    | 1.5V           | TSOT-25 | -40°C to 85°C                       |
| AME5110AEEV150Z | BARww    | 1.5V           | SOT-25  | -40°C to 85°C                       |
| AME5110AEEV180Y | BASww    | 1.8V           | TSOT-25 | -40°C to 85°C                       |
| AME5110AEEV180Z | BASww    | 1.8V           | SOT-25  | -40°C to 85°C                       |
| AME5110BEEVADJY | BATww    | ADJ            | TSOT-25 | -40°C to 85°C                       |
| AME5110BEEVADJZ | BATww    | ADJ            | SOT-25  | -40°C to 85°C                       |

Note: ww represents the date code and pls refer to Date Code Rule page on Package Dimension.

\* A line on top of the first letter represents lead free plating such as BARww.

Please consult AME sales office or authorized Rep./Distributor for the availability of package type.

**AME5110**
**■ Absolute Maximum Ratings**

| Parameter             | Symbol           | Maximum      | Unit |
|-----------------------|------------------|--------------|------|
| Input Supply Voltage  | $V_{IN}$         | 6            | V    |
| EN, $V_{FB}$ Voltages | $V_{EN}, V_{FB}$ | $V_{IN}$     | V    |
| SW Voltage            | $V_{SW}$         | $V_{IN}+0.3$ | V    |
| ESD Classification    |                  | C*           |      |

Caution: Stress above the listed absolute maximum rating may cause permanent damage to the device

\* HBM C: 4000V+

**■ Recommended Operating Conditions**

| Parameter                  | Symbol | Rating      | Unit |
|----------------------------|--------|-------------|------|
| Ambient Temperature Range  | $T_A$  | -40 to +85  | °C   |
| Junction Temperature Range | $T_J$  | -40 to +125 | °C   |

**■ Thermal Information**







| Parameter                                   | Package | Die Attach       | Symbol        | Maximum | Unit   |
|---|---------|------------------|---------------|---------|--------|
| Thermal Resistance*<br>(Junction to Case)   | SOT-25  | Conductive Epoxy | $\theta_{JC}$ | 81      | °C / W |
| Thermal Resistance<br>(Junction to Ambient) |         |                  | $\theta_{JA}$ | 260     | °C / W |
| Internal Power Dissipation                  |         |                  | $P_D$         | 400     | mW     |
| Maximum Junction Temperature                |         |                  |               | 150     | °C     |
| Solder Iron (10 Sec)**                      |         |                  |               | 350     | °C     |







\* Measure  $\theta_{JC}$  on center of molding compound if IC has no tab.

\*\* MIL-STD-202G210F



**AME5110**
**■ Electrical Specifications**
 $T_A=25^{\circ}\text{C}$ .  $V_{IN}=3.6\text{V}$  unless otherwise specified.

| Parameter                         | Symbol           | Test Condition   |   | Min    | Typ  | Max    | Units         |
|-----------------------------------|------------------|--|---|--------|------|--------|---------------|
| Input Voltage                     | $V_{IN}$         |  |   | 2.5    |      | 5.5    | V             |
| Feedback Current                  | $I_{FB}$         |  |   | -30    |      | +30    | nA            |
| Regulated Feedback Voltage        | $V_{FB}$         | $T_A=25^{\circ}\text{C}$   | AME<br>5110BEEVADJZ<br>and<br>AME<br>5110BEEVADJY | 0.6860 | 0.7  | 0.7140 | V             |
|                                   |                  | $T_A= 0^{\circ}\text{C to } 85^{\circ}\text{C}$                                |   | 0.6825 | 0.7  | 0.7175 |               |
|                                   |                  | $T_A= -40^{\circ}\text{C to } 85^{\circ}\text{C}$                              |   | 0.6790 | 0.7  | 0.7210 |               |
| Reference Voltage Line Regulation | $\Delta V_{FB}$  | $V_{IN}=2.5\text{V to } 5.5\text{V}$   | 5110BEEVADJY                                      |        | 0.04 | 0.4    | %/V           |
| Regulated Output Voltage          | $\Delta V_{OUT}$ | $V_{OUT}=1.5\text{V}$ ,<br>$I_{OUT}=100\text{mA}$                              | AME<br>5110AEEVxxxZ<br>and<br>AME<br>5110AEEVxxxY | 1.455  | 1.5  | 1.545  | V             |
|                                   |                  | $V_{OUT}=1.8\text{V}$ ,<br>$I_{OUT}=100\text{mA}$                              |   | 1.746  | 1.8  | 1.854  |               |
| Output Voltage Line Regulation    | $REG_{LINE}$     | $V_{IN}=2.5\text{V to } 5.5\text{V}$   | 5110AEEVxxxY                                      |        | 0.04 | 0.4    | %/V           |
| Switch Current Limit              | $I_{CL}$         | $V_{IN}=3\text{V}$ , $V_{FB}=0.5\text{V}$<br>Duty Cycle < 35%                  | AME<br>5110BEEVADJZ<br>and<br>AME<br>5110BEEVADJY |        | 1.7  |        | A             |
|                                   |                  | $V_{IN}=3\text{V}$ , $V_{OUT}=90\%$<br>Duty Cycle < 35%                        | AME<br>5110AEEVxxxZ<br>and<br>AME<br>5110AEEVxxxY |        |      |        |               |
| Output Voltage Load Regulation    | $V_{LOADREG}$    |  |   |        | 5    |        | %             |
| Shutdown Current                  | $I_{SD}$         | $V_{EN}=0\text{V}$ , $V_{IN}=4.2\text{V}$                                      | $T_A= -40^{\circ}\text{C to } 85^{\circ}\text{C}$ |        | 0.1  | 1      | $\mu\text{A}$ |
| Quiescent Current                 | $I_Q$            | $V_{FB}=0.5\text{V}$ or $V_{OUT}=90\%$<br>$V_{EN}=V_{IN}=4.2\text{V}$          | $T_A= -40^{\circ}\text{C to } 85^{\circ}\text{C}$ |        | 350  | 500    |               |
| Oscillator Frequency              | $f_{OSC}$        | $V_{IN}=2.5\text{V}$ & $I_{OUT}=100\text{mA}$                                  |   |        | 1.2  |        | MHz           |
|                                   |                  | $V_{FB}=0\text{V}$ or $V_{OUT}=0\text{V}$                                      |   |        | 310  |        | kHz           |
| $R_{DS(on)}$ of P-Channel FET     | $R_{DS(on)(P)}$  | $I_{SW}=100\text{mA}$  |   |        | 0.4  | 0.5    | $\Omega$      |
| $R_{DS(on)}$ of N-Channel FET     | $R_{DS(on)(N)}$  | $I_{SW}= -100\text{mA}$  |   |        | 0.35 | 0.45   | $\Omega$      |
| Switch Leakage Current            | $I_{SW}$         | $V_{EN}=0\text{V}$ ,<br>$V_{SW}=0\text{V}$ or $5\text{V}$ , $V_{IN}=5\text{V}$ |   | -1     |      | +1     | $\mu\text{A}$ |
| EN Input Threshold (High)         | $V_{EH}$         | $T_A= -40^{\circ}\text{C to } 85^{\circ}\text{C}$                              |   | 1.5    |      |        | V             |
| EN Input Threshold (Low)          | $V_{EL}$         | $T_A= -40^{\circ}\text{C to } 85^{\circ}\text{C}$                              |   |        |      | 0.3    |               |
| EN Input Current                  | $I_{EN}$         | $T_A= -40^{\circ}\text{C to } 85^{\circ}\text{C}$                              |   | -1     |      | +1     | $\mu\text{A}$ |

**Shutdown Current vs  $V_{IN}$** 

**Output Voltage vs. Load Current**

**EN Threshold-Turn On vs.  $V_{IN}$** 

**EN Threshold-Turn Off vs.  $V_{IN}$** 

**Supply Current vs Supply Voltage**

**Oscillator Frequency vs. Supply Voltage**


**EN Leakage Current vs.  $V_{IN}$** 

**Supply Current vs. Temp**

 **$R_{DS(ON)}$  vs Input Voltage**

**EN Threshold-Turn On vs. Temp**

 **$V_{OUT}$  vs. Temperature**

**EN Threshold-Turn Off vs. Temp**





**EN Leakage Current vs. Temp**

**Discontinuous Operation**


$V_{IN} = 3.6V$   
 $V_{OUT} = 1.5V$   
 $I_{LOAD} = 50mA$   
 $T_A = 25^\circ C$


**1mS/DIV**

**AME5110**
**■ Date Code Rule**


| Marking |          |          | Date Code |          | Year |
|---------|----------|----------|-----------|----------|------|
| A       | A        | A        | W         | W        | xxx0 |
| A       | A        | A        | W         | <u>W</u> | xxx1 |
| A       | A        | A        | <u>W</u>  | W        | xxx2 |
| A       | A        | A        | <u>W</u>  | <u>W</u> | xxx3 |
| A       | A        | <u>A</u> | W         | W        | xxx4 |
| A       | A        | <u>A</u> | W         | <u>W</u> | xxx5 |
| A       | A        | <u>A</u> | <u>W</u>  | W        | xxx6 |
| A       | A        | <u>A</u> | <u>W</u>  | <u>W</u> | xxx7 |
| A       | <u>A</u> | A        | W         | W        | xxx8 |
| A       | <u>A</u> | A        | W         | <u>W</u> | xxx9 |

**■ Tape and Reel Dimension**
**SOT-25**

**Carrier Tape, Number of Components Per Reel and Reel Size**


| Package | Carrier Width (W) | Pitch (P)  | Part Per Full Reel | Reel Size |
|---------|-------------------|------------|--------------------|-----------|
| SOT-25  | 8.0±0.1 mm        | 4.0±0.1 mm | 3000pcs            | 180±1 mm  |

**■ Tape and Reel Dimension**
**TSOT-25**

**Carrier Tape, Number of Components Per Reel and Reel Size**

| Package | Carrier Width (W) | Pitch (P)  | Part Per Full Reel | Reel Size |
|---------|-------------------|------------|--------------------|-----------|
| TSOT-25 | 8.0±0.1 mm        | 4.0±0.1 mm | 3000pcs            | 180±1 mm  |

**AME5110**
**■ Package Dimension**
**SOT-25**


| SYMBOLS              | MILLIMETERS |      | INCHES      |         |
|----------------------|-------------|------|-------------|---------|
|                      | MIN         | MAX  | MIN         | MAX     |
| <b>A</b>             | 1.20REF     |      | 0.0472REF   |         |
| <b>A<sub>1</sub></b> | 0.00        | 0.15 | 0.0000      | 0.0059  |
| <b>b</b>             | 0.30        | 0.55 | 0.0118      | 0.0217  |
| <b>D</b>             | 2.70        | 3.10 | 0.1063      | 0.1220  |
| <b>E</b>             | 1.40        | 1.80 | 0.0551      | 0.0709  |
| <b>e</b>             | 1.90 BSC    |      | 0.07480 BSC |         |
| <b>H</b>             | 2.60        | 3.00 | 0.10236     | 0.11811 |
| <b>L</b>             | 0.37BSC     |      | 0.0146BSC   |         |
| <b>q1</b>            | 0°          | 10°  | 0°          | 10°     |
| <b>S<sub>1</sub></b> | 0.95BSC     |      | 0.0374BSC   |         |

**TSOT-25**


| SYMBOLS                | MILLIMETERS |      | INCHES      |         |
|------------------------|-------------|------|-------------|---------|
|                        | MIN         | MAX  | MIN         | MAX     |
| <b>A+A<sub>1</sub></b> | 0.90        | 1.25 | 0.0354      | 0.0492  |
| <b>b</b>               | 0.30        | 0.50 | 0.0118      | 0.0197  |
| <b>c</b>               | 0.09        | 0.25 | 0.0035      | 0.0098  |
| <b>D</b>               | 2.70        | 3.10 | 0.1063      | 0.1220  |
| <b>E</b>               | 1.40        | 1.80 | 0.0551      | 0.0709  |
| <b>e</b>               | 1.90 BSC    |      | 0.07480 BSC |         |
| <b>H</b>               | 2.40        | 3.00 | 0.09449     | 0.11811 |
| <b>L</b>               | 0.35BSC     |      | 0.0138BSC   |         |
| <b>q1</b>              | 0°          | 10°  | 0°          | 10°     |
| <b>S<sub>1</sub></b>   | 0.95BSC     |      | 0.0374BSC   |         |



**www.ame.com.tw**  
**E-Mail: sales@ame.com.tw**

**Life Support Policy:**

These products of AME, Inc. are not authorized for use as critical components in life-support devices or systems, without the express written approval of the president of AME, Inc.

AME, Inc. reserves the right to make changes in the circuitry and specifications of its devices and advises its customers to obtain the latest version of relevant information.

© AME, Inc. , October 2006

Document: 2073-DS5110-A.04

**Corporate Headquarter**  
**AME, Inc.**

2F, 302 Rui-Guang Road, Nei-Hu District  
Taipei 114, Taiwan.  
Tel: 886 2 2627-8687  
Fax: 886 2 2659-2989

**U.S.A. (Subsidiary)**  
**Analog Microelectronics, Inc.**

3100 De La Cruz Blvd., Suite 201  
Santa Clara, CA. 95054-2438  
Tel : (408) 988-2388  
Fax: (408) 988-2489