

■ Pin Descriptions

Pin No.	Pin Name	Pin No.	Pin Name
1	V _{CC}	9	N.F.B Ch. 2
2	Output Ch. 1	10	GND (Input)
3	GND (Output Ch. 1)	11	N.F.B Ch. 2
4	Output Ch. 1	12	Input Ch. 2
5	Stand-by	13	Ripple Filter
6	Input Ch. 1	14	Output Ch. 2
7	N.F.B Ch. 1	16	GND (Output Ch. 2)
8	N.F.B Ch. 1	16	Output Ch. 2

■ Absolute Maximum Ratings (T_a = 25°C)

Item	Symbol	Rating	Unit
Supply Voltage	V _{CC} *1	24	V
Peak Supply Voltage	V _{CC(peak)} *2	50.0	V
Supply Current	I _{CC}	6.0	A
Power Dissipation	P _D *3	62.5	W
Operating Ambient Temperature	T _{op}	-30 - +75	°C
Storage Temperature	T _{stg}	-55 - +150	°C

*1 Non-signal *2 Time = 0.2s *3 R_{θjc} = 2°C/W

■ Electrical Characteristics (V_{CC} = 13.2V, R_L = 4Ω, f = 1kHz, T_a = 25°C)

Item	Symbol	Test Circuit	Condition	min.	typ.	max.	Unit
Quiescent Circuit Current	I _{CCQ}	1	V _{in} = 0mV		120	200	mA
Output Noise Voltage	V _{no} *	1	V _{in} = 0mV, R _g = 10kΩ		0.60	1.50	mV
Voltage Gain	G _v	1	V _{in} = 5mV	50.5	52.5	54.5	dB
Total Harmonic Distortion	THD	1	V _{in} = 5mV		0.20	0.75	%
Maximum Output Power (4Ω)	P _O	1	THD = 10%	9.0	12.5		W
Ripple Rejection Ratio	RR*	1	R _g = 0Ω, V _{in} = 0mV, Ripple = 300mV, 120Hz	35	40		dB
Output Offset Voltage	V _{offset}	1	V _{in} = 0mV	-300	0	+300	mV
Channel Balance	CB	1	V _{in} = 5mV	-1	0	+1	dB
Total Harmonic Distortion	THD	1	V _{in} = 5mV, 100Hz		0.26		%
Total Harmonic Distortion	THD	1	V _{in} = 5mV, 10kHz		0.45		%
Frequency Characteristics	f _{cut}	1	V _{in} = 5mV, -3dB down		22		kHz
Frequency Characteristics	f _{cl}	1	V _{in} = 5mV, -3dB down		21		Hz
Quiescent Circuit Current at Stand-by Pin ON	I _{CC(stand-by ON)}	1	Stand-by Pin ON		21		μA
Crosstalk	CT	1	V _{in} = 5mV, R _g = 10kΩ		61		dB

With 15Hz - 30kHz (12dB/oct) filter