



AO3702
**N-Channel Enhancement Mode Field Effect Transistor
with Schottky Diode**
General Description

The AO3702/L uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge.
 A Schottky diode is provided to facilitate the implementation of a bidirectional blocking switch, or for DC-DC conversion applications. AO3702 and AO3702L are electrically identical.
 -RoHs Complaint
 -AO3702L is Halogen Free

Features

V_{DS} (V) = 20V
 $I_D = 3.5A$ ($V_{GS} = 4.5V$)
 $R_{DS(ON)} < 62m\Omega$ ($V_{GS} = 4.5V$)
 $R_{DS(ON)} < 70m\Omega$ ($V_{GS} = 2.5V$)
 $R_{DS(ON)} < 85m\Omega$ ($V_{GS} = 1.8V$)
SCHOTTKY
 V_{DS} (V) = 20V, $I_F = 1A$, $V_F < 0.5V@0.5A$

 SOT-23-5
 Top View

Absolute Maximum Ratings $T_A=25^\circ C$ unless otherwise noted

Parameter	Symbol	MOSFET	Schottky	Units
Drain-Source Voltage	V_{DS}	20		V
Gate-Source Voltage	V_{GS}	± 8		V
Continuous Drain Current ^A	$T_A=25^\circ C$	3.5		A
	$T_A=70^\circ C$	2.7		
Pulsed Drain Current ^B	I_{DM}	25		
Schottky reverse voltage	V_{KA}		20	V
Continuous Forward Current ^A	$T_A=25^\circ C$		1	A
	$T_A=70^\circ C$		0.5	
Pulsed Forward Current ^B	I_{FM}		10	
Power Dissipation	$T_A=25^\circ C$	1.15	0.66	W
	$T_A=70^\circ C$	0.7	0.42	
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	-55 to 150	$^\circ C$

Parameter: Thermal Characteristics MOSFET		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient ^A	t ≤ 10s	R _{θJA}	80.3	110	°C/W
Maximum Junction-to-Ambient ^A	Steady-State		117	150	
Maximum Junction-to-Lead ^C	Steady-State	R _{θJL}	43	80	
Thermal Characteristics Schottky					
Maximum Junction-to-Ambient ^A	t ≤ 10s	R _{θJA}	153	190	°C/W
Maximum Junction-to-Ambient ^A	Steady-State		173	220	
Maximum Junction-to-Lead ^C	Steady-State	R _{θJL}	103	140	

Electrical Characteristics ($T_J=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}$, $V_{GS}=0\text{V}$	20			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=20\text{V}$, $V_{GS}=0\text{V}$ $T_J=55^{\circ}\text{C}$			1 5	μA
I_{GSS}	Gate-Body leakage current	$V_{DS}=0\text{V}$, $V_{GS}=\pm 8\text{V}$			± 100	nA
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}$, $I_D=250\mu\text{A}$	0.5	0.68	1	V
$I_{D(ON)}$	On state drain current	$V_{GS}=4.5\text{V}$, $V_{DS}=5\text{V}$	25			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS}=4.5\text{V}$, $I_D=3.5\text{A}$ $T_J=125^{\circ}\text{C}$		50 70	62 90	$\text{m}\Omega$
		$V_{GS}=2.5\text{V}$, $I_D=3\text{A}$		56	70	$\text{m}\Omega$
		$V_{GS}=1.8\text{V}$, $I_D=2.5\text{A}$		66	85	
g_{FS}	Forward Transconductance	$V_{DS}=5\text{V}$, $I_D=2\text{A}$		15		S
V_{SD}	Diode Forward Voltage	$I_S=1\text{A}$, $V_{GS}=0\text{V}$		0.7	1	V
I_S	Maximum Body-Diode Continuous Current				1.6	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	$V_{GS}=0\text{V}$, $V_{DS}=10\text{V}$, $f=1\text{MHz}$		260	320	pF
C_{oss}	Output Capacitance			48		pF
C_{rss}	Reverse Transfer Capacitance			27		pF
R_g	Gate resistance	$V_{GS}=0\text{V}$, $V_{DS}=0\text{V}$, $f=1\text{MHz}$		3	4.5	Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	$V_{GS}=4.5\text{V}$, $V_{DS}=10\text{V}$, $I_D=3.5\text{A}$		2.9	3.8	nC
Q_{gs}	Gate Source Charge			0.4		nC
Q_{gd}	Gate Drain Charge			0.6		nC
$t_{D(on)}$	Turn-On DelayTime	$V_{GS}=4.5\text{V}$, $V_{DS}=10\text{V}$, $R_L=3\Omega$, $R_{GEN}=6\Omega$		2.5		ns
t_r	Turn-On Rise Time			3.2		ns
$t_{D(off)}$	Turn-Off DelayTime			21		ns
t_f	Turn-Off Fall Time			3		ns
t_{rr}	Body Diode Reverse Recovery Time	$I_F=3.5\text{A}$, $dI/dt=100\text{A}/\mu\text{s}$		14	19	ns
Q_{rr}	Body Diode Reverse Recovery Charge	$I_F=3.5\text{A}$, $dI/dt=100\text{A}/\mu\text{s}$		3.4		nC
SCHOTTKY PARAMETERS						
V_F	Forward Voltage Drop	$I_F=0.5\text{A}$		0.37	0.5	V
I_{rm}	Maximum reverse leakage current	$V_R=16\text{V}$			0.1	mA
		$V_R=16\text{V}$, $T_J=125^{\circ}\text{C}$			20	
C_T	Junction Capacitance	$V_R=10\text{V}$		52		pF
t_{rr}	Schottky Reverse Recovery Time	$I_F=1\text{A}$, $dI/dt=100\text{A}/\mu\text{s}$		9.2	12	ns
Q_{rr}	Schottky Reverse Recovery Charge	$I_F=1\text{A}$, $dI/dt=100\text{A}/\mu\text{s}$		1.7		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^{\circ}\text{C}$. The value in any given application depends on the user's specific board design. The current rating is based on the $t \leq 10\text{s}$ thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C: The $R_{\theta JA}$ is the sum of the thermal impedance from junction to lead $R_{\theta JL}$ and lead to ambient.

D: The static characteristics in Figures 1 to 6 are obtained using $<300 \mu\text{s}$ pulses, duty cycle 0.5% max.

E: These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^{\circ}\text{C}$. The SOA curve provides a single pulse rating.

Rev1:March 2008

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: SCHOTTKY




Figure 12: Schottky Forward Characteristics




Figure 13: Schottky Capacitance Characteristics




Figure 14: Schottky Forward Drop vs. Junction Temperature




Figure 15: Schottky Leakage current vs. Junction Temperature




Figure 16: Schottky Normalized Maximum Transient Thermal Impedance