



P-Channel MOSFET

AO4413 (KO4413)

■ Features

- $V_{DS} (V) = -30V$
- $I_D = -15 A$ ($V_{GS} = -20V$)
- $R_{DS(ON)} < 7m\Omega$ ($V_{GS} = -20V$)
- $R_{DS(ON)} < 8.5m\Omega$ ($V_{GS} = -10V$)



■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	± 25	
Continuous Drain Current	$T_A = 25^\circ C$	I_D	-15	A
	$T_A = 70^\circ C$		-12.8	
Pulsed Drain Current		I_{DM}	-120	
Avalanche Current		I_{AS}, I_{AR}	50	
Avalanche energy	$L = 0.1mH$	E_{AS}, E_{AR}	125	mJ
Power Dissipation	$T_A = 25^\circ C$	P_D	3.1	W
	$T_A = 70^\circ C$		2	
Thermal Resistance.Junction- to-Ambient	$t \leq 10s$	R_{thJA}	40	$^\circ C/W$
	Steady-State		75	
Thermal Resistance.Junction- to-Lead		R_{thJL}	24	
Junction Temperature		T_J	150	$^\circ C$
Junction Storage Temperature Range		T_{stg}	-55 to 150	

P-Channel MOSFET

AO4413 (KO4413)

■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	V _{DSS}	I _D =-250 μA, V _{GS} =0V	-30			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-30V, V _{GS} =0V			-1	μA
		V _{DS} =-30V, V _{GS} =0V, T _J =55°C			-5	
Gate-Body leakage current	I _{GSS}	V _{DS} =0V, V _{GS} =±25V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} I _D =-250 μA	-1.5		-3.5	V
Static Drain-Source On-Resistance	R _{DS(on)}	V _{GS} =-20V, I _D =-15A			7	mΩ
		V _{GS} =-20V, I _D =-15A T _J =125°C			9	
		V _{GS} =-10V, I _D =-15A			8.5	
On state drain current	I _{D(ON)}	V _{GS} =-10V, V _{DS} =-5V	-120			A
Forward Transconductance	g _{FS}	V _{DS} =-5V, I _D =-15A		35		S
Input Capacitance	C _{iss}	V _{GS} =0V, V _{DS} =-15V, f=1MHz	2310		3500	pF
Output Capacitance	C _{oss}		410		760	
Reverse Transfer Capacitance	C _{rss}		280		660	
Gate resistance	R _g	V _{GS} =0V, V _{DS} =0V, f=1MHz	1.9		5.7	Ω
Total Gate Charge	Q _g	V _{GS} =-10V, V _{DS} =-15V, I _D =-15A	40		61	nC
Gate Source Charge	Q _{gs}		10		14	
Gate Drain Charge	Q _{gd}		10		22	
Turn-On DelayTime	t _{d(on)}	V _{GS} =-10V, V _{DS} =-15V, R _L =1Ω, R _{GEN} =3Ω		16		ns
Turn-On Rise Time	t _r			12		
Turn-Off DelayTime	t _{d(off)}			45		
Turn-Off Fall Time	t _f			22		
Body Diode Reverse Recovery Time	t _{rr}	I _F =-15A, dI/dt=100A/μs	14		22	nC
Body Diode Reverse Recovery Charge	Q _{rr}		9		13	
Maximum Body-Diode Continuous Current	I _S				-4	A
Diode Forward Voltage	V _{SD}	I _S =-1A, V _{GS} =0V			-1	V

Note : The static characteristics in Figures 1 to 6 are obtained using <300 μs pulses, duty cycle 0.5% max.

■ Marking

Marking	4413 KC****
---------	----------------

P-Channel MOSFET

AO4413 (KO4413)

■ Typical Characteristics




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

P-Channel MOSFET

AO4413 (KO4413)

■ Typical Characteristics




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Single Pulse Avalanche capability (Note C)




Figure 10: Maximum Forward Biased Safe Operating Area (Note F)




Figure 11: Single Pulse Power Rating Junction-to-Ambient (Note F)

P-Channel MOSFET

AO4413 (KO4413)

■ Typical Characteristics




Figure 12: Normalized Maximum Transient Thermal Impedance (Note F)