



## N-Channel MOSFET

## AO4482 (KO4482)

## ■ Features

- $V_{DS} (V) = 100V$
- $I_D = 6 A (V_{GS} = 10V)$
- $R_{DS(ON)} < 37m\Omega (V_{GS} = 10V)$
- $R_{DS(ON)} < 42m\Omega (V_{GS} = 4.5V)$

■ Absolute Maximum Ratings  $T_a = 25^\circ C$ 

Parameter	Symbol	Rating	Unit	
Drain-Source Voltage	$V_{DS}$	100	V	
Gate-Source Voltage	$V_{GS}$	$\pm 20$		
Continuous Drain Current	$I_D$	$T_A=25^\circ C$	6	
		$T_A=70^\circ C$		5
Pulsed Drain Current	$I_{DM}$	42	A	
Avalanche Current	$I_{AS}, I_{AR}$	35		
Avalanche Energy	$L=0.1mH$	$E_{AS}, E_{AR}$	61	mJ
Power Dissipation	$P_D$	$T_A=25^\circ C$	3.1	W
		$T_A=70^\circ C$	2	
Thermal Resistance.Junction- to-Ambient	$R_{thJA}$	$t \leq 10s$	40	$^\circ C/W$
		Steady-State	75	
Thermal Resistance.Junction- to-Lead	$R_{thJL}$	24		
Junction Temperature	$T_J$	150	$^\circ C$	
Storage Temperature Range	$T_{stg}$	-55 to 150		

## N-Channel MOSFET

## AO4482 (KO4482)

## ■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
Drain-Source Breakdown Voltage	V <sub>DSS</sub>	I <sub>D</sub> =250 μA, V <sub>GS</sub> =0V	100			V	
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> =100V, V <sub>GS</sub> =0V			1	μA	
		V <sub>DS</sub> =100V, V <sub>GS</sub> =0V, T <sub>J</sub> =55°C			5		
Gate-Body Leakage Current	I <sub>GSS</sub>	V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V			±100	nA	
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	1.6		2.7	V	
Static Drain-Source On-Resistance	R <sub>DS(on)</sub>	V <sub>GS</sub> =10V, I <sub>D</sub> =6A			37	mΩ	
		V <sub>GS</sub> =10V, I <sub>D</sub> =6A, T <sub>J</sub> =125°C			72		
		V <sub>GS</sub> =4.5V, I <sub>D</sub> =5A			42		
On State Drain Current	I <sub>D(on)</sub>	V <sub>GS</sub> =10V, V <sub>DS</sub> =5V	42			A	
Forward Transconductance	g <sub>FS</sub>	V <sub>DS</sub> =5V, I <sub>D</sub> =6A		35		S	
Input Capacitance	C <sub>iss</sub>	V <sub>GS</sub> =0V, V <sub>DS</sub> =50V, f=1MHz	1300		2000	pF	
Output Capacitance	C <sub>oss</sub>		70		130		
Reverse Transfer Capacitance	C <sub>rss</sub>		30		70		
Gate Resistance	R <sub>g</sub>	V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, f=1MHz	0.3		1.1	Ω	
Total Gate Charge (10V)	Q <sub>g</sub>	V <sub>GS</sub> =10V, V <sub>DS</sub> =50V, I <sub>D</sub> =6A	28		44	nC	
Total Gate Charge (4.5V)			14		22		
Gate Source Charge			Q <sub>gs</sub>	4			6
Gate Drain Charge			Q <sub>gd</sub>	5			13
Turn-On DelayTime	t <sub>d(on)</sub>	V <sub>GS</sub> =10V, V <sub>DS</sub> =50V, R <sub>L</sub> =8.3Ω, R <sub>GEN</sub> =3Ω		7		ns	
Turn-On Rise Time	t <sub>r</sub>			7			
Turn-Off DelayTime	t <sub>d(off)</sub>			28			
Turn-Off Fall Time	t <sub>f</sub>			7			
Body Diode Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> = 6A, di/dt= 500A/us	17.5		33	nC	
Body Diode Reverse Recovery Charge	Q <sub>rr</sub>		90		170		
Maximum Body-Diode Continuous Current	I <sub>S</sub>				4	A	
Diode Forward Voltage	V <sub>SD</sub>	I <sub>S</sub> =1A, V <sub>GS</sub> =0V			1	V	

Note : The static characteristics in Figures 1 to 6 are obtained using <300 us pulses, duty cycle 0.5% max.

## ■ Marking

Marking	4482
	KC****

## N-Channel MOSFET AO4482 (KO4482)

■ Typical Characteristics




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

## N-Channel MOSFET AO4482 (KO4482)

■ Typical Characteristics




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Single Pulse Avalanche capability (Note C)




Figure 10: Maximum Forward Biased Safe Operating Area (Note F)




Figure 11: Single Pulse Power Rating Junction-to-Ambient (Note F)

## N-Channel MOSFET AO4482 (KO4482)

■ Typical Characteristics




Figure 12: Normalized Maximum Transient Thermal Impedance (Note F)