


AO4707
**P-Channel Enhancement Mode Field Effect Transistor
with Schottky Diode**
General Description



The AO4707 uses advanced trench technology to provide excellent $R_{DS(ON)}$ and low gate charge. A Schottky diode is provided to facilitate the implementation of non-synchronous DC-DC converters. *Standard Product AO8820 is Pb-free (meets ROHS & Sony 259 specifications). AO8820L is a Green Product ordering option. AO8820 and AO8820L are electrically identical.*

Features

V_{DS} (V) = -30V
 I_D = -8A (V_{GS} = -10V)
 $R_{DS(ON)}$ < 33m Ω (V_{GS} = -10V)
 $R_{DS(ON)}$ < 56m Ω (V_{GS} = -4.5V)

SCHOTTKY

V_{DS} (V) = 30V, I_F = 3A, V_F < 0.52V@3A


SOIC-8

Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	MOSFET	Schottky	Units
Drain-Source Voltage	V_{DS}	-30		V
Gate-Source Voltage	V_{GS}	± 20		V
Continuous Drain Current ^A	I_D	$T_A=25^\circ\text{C}$	-8	A
		$T_A=70^\circ\text{C}$	-6.6	
Pulsed Drain Current ^B	I_{DM}	-40		
Schottky reverse voltage	V_{KA}		30	V
Continuous Forward Current ^A	I_F	$T_A=25^\circ\text{C}$	5	A
		$T_A=70^\circ\text{C}$	3.5	
Pulsed Forward Current ^B	I_{FM}		30	
Power Dissipation	P_D	$T_A=25^\circ\text{C}$	3	W
		$T_A=70^\circ\text{C}$	2	
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	-55 to 150	$^\circ\text{C}$

Parameter: Thermal Characteristics MOSFET		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient ^A	$t \leq 10\text{s}$	$R_{\theta JA}$	24	40	$^\circ\text{C/W}$
Maximum Junction-to-Ambient ^A	Steady-State		54	75	
Maximum Junction-to-Lead ^C	Steady-State	$R_{\theta JL}$	21	30	
Thermal Characteristics Schottky					
Maximum Junction-to-Ambient ^A	$t \leq 10\text{s}$	$R_{\theta JA}$	36	40	$^\circ\text{C/W}$
Maximum Junction-to-Ambient ^A	Steady-State		67	75	
Maximum Junction-to-Lead ^C	Steady-State	$R_{\theta JL}$	25	30	

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV _{DSS}	Drain-Source Breakdown Voltage	I _D =-250μA, V _{GS} =0V	-30			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-24V, V _{GS} =0V T _J =55°C			-1 -5	μA
I _{GSS}	Gate-Body leakage current	V _{DS} =0V, V _{GS} =±20V			±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250μA	-1.2	-2	-2.4	V
I _{D(ON)}	On state drain current	V _{GS} =-10V, V _{DS} =-5V	40			A
R _{DS(ON)}	Static Drain-Source On-Resistance	V _{GS} =-10V, I _D =-8A T _J =125°C		24.5 33	33	mΩ
		V _{GS} =-4.5V, I _D =-5A		41	56	mΩ
g _{FS}	Forward Transconductance	V _{DS} =-5V, I _D =-8A		14.5		S
V _{SD}	Diode Forward Voltage	I _S =-1A, V _{GS} =0V		-0.76	-1	V
I _S	Maximum Body-Diode Continuous Current				-4.2	A
DYNAMIC PARAMETERS						
C _{iss}	Input Capacitance			920		pF
C _{oss}	Output Capacitance	V _{GS} =0V, V _{DS} =-15V, f=1MHz		190		pF
C _{rss}	Reverse Transfer Capacitance			122		pF
R _g	Gate resistance	V _{GS} =0V, V _{DS} =0V, f=1MHz		3.6		Ω
SWITCHING PARAMETERS						
Q _g (10V)	Total Gate Charge (10V)			18.4		nC
Q _g (4.5V)	Total Gate Charge (4.5V)	V _{GS} =-10V, V _{DS} =-15V, I _D =-8A		9.3		nC
Q _{gs}	Gate Source Charge			2.7		nC
Q _{gd}	Gate Drain Charge			4.9		nC
t _{D(on)}	Turn-On Delay Time			7.1		ns
t _r	Turn-On Rise Time	V _{GS} =-10V, V _{DS} =-15V, R _L =1.8Ω,		3.4		ns
t _{D(off)}	Turn-Off Delay Time	R _{GEN} =3Ω		18.9		ns
t _f	Turn-Off Fall Time			8.4		ns
t _{rr}	Body Diode Reverse Recovery Time	I _F =-8A, di/dt=100A/μs		21.5		ns
Q _{rr}	Body Diode Reverse Recovery Charge	I _F =-8A, di/dt=100A/μs		12.5		nC
SCHOTTKY PARAMETERS						
V _F	Forward Voltage Drop	I _F =3.0A		0.48	0.52	V
I _{rm}	Maximum reverse leakage current	V _R =24V V _R =24V, T _J =125°C V _R =24V, T _J =150°C		0.07 4.2 15	0.15 20 60	mA
C _T	Junction Capacitance	V _R =15V		120		pF

A: The value of R_{θJA} is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The value in any given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C: The R_{θJA} is the sum of the thermal impedance from junction to lead R_{θJL} and lead to ambient.

D: The static characteristics in Figures 1 to 6,12,14 are obtained using 80 μs pulses, duty cycle 0.5% max.

E: These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.

Rev4: August 2005

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE

P-CHANNEL: TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

P-CHANNEL: TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: SCHOTTKY




Figure 12: Schottky Forward Characteristics




Figure 13: Schottky Capacitance Characteristics




Figure 14: Schottky Forward Drop vs. Junction Temperature




Figure 15: Schottky Leakage current vs. Junction Temperature

