




▼ Simple Drive Requirement
▼ Small package outline
▼ Surface mount package


SOT-23 G

BV_{DSS}	25V
$R_{DS(ON)}$	117m Ω
I_D	2.7A

Description

The Advanced Power MOSFETs from APEC provide the designer with the best combination of fast switching, low on-resistance and cost-effectiveness.


Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	25	V
V_{GS}	Gate-Source Voltage	± 20	V
$I_D @ T_A = 25^\circ\text{C}$	Continuous Drain Current ³ , V_{GS} @ 4.5V	2.7	A
$I_D @ T_A = 70^\circ\text{C}$	Continuous Drain Current ³ , V_{GS} @ 4.5V	2.2	A
I_{DM}	Pulsed Drain Current ^{1,2}	10	A
$P_D @ T_A = 25^\circ\text{C}$	Total Power Dissipation	1.38	W
	Linear Derating Factor	0.01	W/ $^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ\text{C}$

Thermal Data

Symbol	Parameter	Value	Unit
R_{thj-a}	Thermal Resistance Junction-ambient ³ Max.	90	$^\circ\text{C}/\text{W}$



AP2304N

Electrical Characteristics@T_j=25°C(unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250uA	25	-	-	V
ΔBV _{DSS} /ΔT _j	Breakdown Voltage Temperature Coefficient	Reference to 25°C, I _D =1mA	-	0.1	-	V/°C
R _{DS(ON)}	Static Drain-Source On-Resistance ²	V _{GS} =10V, I _D =2.5A	-		117	mΩ
		V _{GS} =4.5V, I _D =2A	-		190	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250uA	1	-	3	V
g _{fs}	Forward Transconductance	V _{DS} =4.5V, I _D =2.5A	-	3.4	-	S
I _{DSS}	Drain-Source Leakage Current (T _j =25°C)	V _{DS} =25V, V _{GS} =0V	-	-	1	uA
	Drain-Source Leakage Current (T _j =55°C)	V _{DS} =25V, V _{GS} =0V	-	-	10	uA
I _{GSS}	Gate-Source Leakage	V _{GS} =±20V	-	-	±100	nA
Q _g	Total Gate Charge ²	I _D =2.5A	-	5.9	10	nC
Q _{gs}	Gate-Source Charge	V _{DS} =15V	-	0.8	-	nC
Q _{gd}	Gate-Drain ("Miller") Charge	V _{GS} =10V	-	2.1	-	nC
t _{d(on)}	Turn-on Delay Time ²	V _{DS} =15V	-	4.5	-	ns
t _r	Rise Time	I _D =1A	-	11.5	-	ns
t _{d(off)}	Turn-off Delay Time	R _G =6Ω, V _{GS} =10V	-	12	-	ns
t _f	Fall Time	R _D =15Ω	-	3	-	ns
C _{iss}	Input Capacitance	V _{GS} =0V	-	110	-	pF
C _{oss}	Output Capacitance	V _{DS} =15V	-	85	-	pF
C _{rss}	Reverse Transfer Capacitance	f=1.0MHz	-	39	-	pF

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
I _S	Continuous Source Current (Body Diode)	V _D =V _G =0V , V _S =1.2V	-	-	1	A
I _{SM}	Pulsed Source Current (Body Diode) ¹		-	-	10	A
V _{SD}	Forward On Voltage ²	I _S =1.25A, V _{GS} =0V	-	-	1.2	V

Notes:

- 1.Pulse width limited by Max. junction temperature.
- 2.Pulse width ≤300us , duty cycle ≤2%.
- 3.Surface mounted on 1 in² copper pad of FR4 board ; 270°C/W when mounted on min. copper pad.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage v.s. Junction Temperature




Fig7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig10. Effective Transient Thermal Impedance




Fig 11. Switching Time Waveform




Fig 12. Gate Charge Waveform