



## DUAL LDO REGULATORS

## AP2401

### General Description

The AP2401 series are dual positive voltage regulator ICs fabricated by CMOS process. Each of these ICs consists of a voltage reference, two error amplifiers, two resistor networks for setting output voltages. Each channel has a current limit circuit for current protection.

The AP2401 series feature high ripple rejection, low dropout voltage, low noise, high output voltage accuracy, and low current consumption which make them ideal for use in various battery-powered devices. The chip enable function allows the output of each channel to be turned on/off independently, greatly reducing the power consumption.

The AP2401 series have 1.8V/2.5V, 1.8V/2.8V, 1.8V/3.3V and 2.8V/1.8V versions.

The AP2401 are available in standard SOT-23-6 package.

### Features

- Maximum Output Current/Channel: More Than 150mA (300mA Limit)
- High Output Voltage Accuracy:  $\pm 2\%$
- Low Quiescent Current/Channel: 25 $\mu$ A Typical
- Low Standby Current: 0.1 $\mu$ A Typical
- High PSRR: 70dB Typical ( $f=1$ kHz)
- Extremely Low Noise: 30 $\mu$ Vrms (10Hz to 100kHz)
- Operating Temperature: -40 to 85 $^{\circ}$ C
- Compatible with Low ESR Ceramic Capacitor

### Applications

- Mobile Phones, Cordless Phones
- Wireless Communication Equipment
- Portable Games
- Cameras, Video Recorders
- Sub-board Power Supplies for Telecom Equipment
- Battery Powered Equipment




Figure 1. Package Type of AP2401



## DUAL LDO REGULATORS

**AP2401**

### Pin Configuration




Figure 2. Pin Configuration of AP2401 (Top View)

### Pin Description

Pin Number	Pin Name	Function
1	CE1	On/Off control 1, logic high=enable; logic low=shutdown
2	$V_{IN}$	Input voltage
3	CE2	On/Off control 2, logic high=enable; logic low=shutdown
4	$V_{OUT2}$	Output voltage 2
5	GND	Ground
6	$V_{OUT1}$	Output voltage 1



## DUAL LDO REGULATORS

## AP2401

### Functional Block Diagram




Figure 3. Functional Block Diagram of AP2401



## DUAL LDO REGULATORS

## AP2401


### Ordering Information

Circuit Type

B: Active High  
(Without Built-in Pull-down Resistor)

1: Fixed Output 1.8V (Channel 1)  
3: Fixed Output 2.8V (Channel 1)

1: Fixed Output 1.8V (Channel 2)  
2: Fixed Output 2.5V (Channel 2)  
3: Fixed Output 2.8V (Channel 2)  
4: Fixed Output 3.3V (Channel 2)



E1: Lead Free

G1: Green

TR: Tape and Reel

Package

K: SOT-23-6

Package	Temperature Range	Condition	Output Voltages	Part Number		Marking ID		Packing Type
				Lead Free	Green	Lead Free	Green	
SOT-23-6	-40 to 85°C	Active High Without Built-in Pull-down Resistor	1.8V/2.5V	AP2401B12KTR-E1	AP2401B12KTR-G1	E9P	G9P	Tape & Reel
		Active High Without Built-in Pull-down Resistor	1.8V/2.8V	AP2401B13KTR-E1	AP2401B13KTR-G1	E9Q	G9Q	Tape & Reel
		Active High Without Built-in Pull-down Resistor	1.8V/3.3V	AP2401B14KTR-E1	AP2401B14KTR-G1	E9R	G9R	Tape & Reel
		Active High Without Built-in Pull-down Resistor	2.8V/1.8V	AP2401B31KTR-E1	AP2401B31KTR-G1	E8R	G8R	Tape & Reel

BCD Semiconductor's Pb-free products, as designated with "E1" suffix in the part number, are RoHS compliant. Products with "G1" suffix are available in green packages.


**DUAL LDO REGULATORS**
**AP2401**
**Absolute Maximum Ratings (Note 1)**

Parameter	Symbol	Value	Unit
Input Voltage	$V_{IN}$	6.5	V
Enable Input Voltage	$V_{CE}$	6.5	V
Output Current ( $T_A=25^\circ\text{C}$ )	$I_{OUT1}+I_{OUT2}$	700	mA
Power Dissipation ( $T_A=25^\circ\text{C}$ )	$P_D$	250	mW
Junction Temperature	$T_J$	150	$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-65 to 150	$^\circ\text{C}$
Lead Temperature (Soldering, 10sec)	$T_{LEAD}$	260	$^\circ\text{C}$
ESD (Human Body Model)	ESD	3000	V

Note 1: Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "Recommended Operating Conditions" is not implied. Exposure to "Absolute Maximum Ratings" for extended periods may affect device reliability.

**Recommended Operating Conditions**

Parameter	Symbol	Min	Max	Unit
Input Voltage	$V_{IN}$		6	V
Operating Junction Temperature Range	$T_J$	-40	85	$^\circ\text{C}$



## DUAL LDO REGULATORS

## AP2401

### Electrical Characteristics

(Channel 1/Channel 2:  $V_{IN}=V_{OUT}+1V$ ,  $T_J=25^{\circ}C$ ,  $C_{IN}=1\mu F$ ,  $C_{OUT}=1\mu F$ , unless otherwise specified.)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit	
Output Voltage Accuracy	$\Delta V_{OUT}/V_{OUT}$	Variation from specified $V_{OUT}$ , $I_{OUT}=30mA$	-2		2	%	
Input Voltage	$V_{IN}$				6	V	
Maximum Output Current	$I_{OUT}$		150			mA	
Load Regulation	$V_{RLOAD}$	$1mA \leq I_{OUT} \leq 100mA$		15	60	mV	
Line Regulation	$V_{RLINE}$	$V_{OUT}+1V \leq V_{IN} \leq 6V$ $I_{OUT}=30mA$ , $V_{CE}=V_{IN}$		0.01	0.2	%/V	
Dropout Voltage	$V_{DROP}$	$I_{OUT}=30mA$	$V_{OUT}=1.8V$		60	70	mV
			$V_{OUT}=2.5V$		45	55	
			$V_{OUT}=2.8V$		45	55	
			$V_{OUT}=3.3V$		35	45	
		$I_{OUT}=100mA$	$V_{OUT}=1.8V$		175	195	
			$V_{OUT}=2.5V$		135	160	
			$V_{OUT}=2.8V$		135	160	
			$V_{OUT}=3.3V$		125	150	
Quiescent Current	$I_Q$	$V_{CE}=V_{IN}=V_{OUT}+1V$ , $I_{OUT}=0mA$		25	45	$\mu A$	
Standby Current	$I_{STD}$	$V_{CE}$ in OFF mode		0.1	1	$\mu A$	
Power Supply Rejection Ratio	PSRR	Ripple 0.5Vp-p, $f=1kHz$ $V_{IN}=V_{OUT}+1V$ , $I_{OUT}=30mA$		70		dB	
Output Voltage Temperature Coefficient	$(\Delta V_{OUT}/V_{OUT})/\Delta T$	$I_{OUT}=30mA$ , $-40^{\circ}C \leq T_J \leq 85^{\circ}C$		$\pm 100$		ppm/ $^{\circ}C$	
Current Limit	$I_{LIMIT}$	$V_{CE}=V_{IN}$		300		mA	
Short Circuit Current	$I_{SHORT}$	$V_{CE}=V_{IN}$ , $V_{OUT}=0$		30		mA	
RMS Output Noise	$V_{NOISE}$	$T_A=25^{\circ}C$ $10Hz \leq f \leq 100kHz$		30		$\mu V_{rms}$	
CE "High" Voltage		CE input voltage "High"	1.3		6	V	
CE "Low" Voltage		CE input voltage "Low"			0.25	V	
Thermal Resistance (Junction to Case)	$\theta_{JC}$	SOT-23-6		61.3		$^{\circ}C/W$	



**DUAL LDO REGULATORS**

**AP2401**

**Typical Performance Characteristics**




Figure 4. Output Voltage vs. Output Current




Figure 5. Output Voltage vs. Output Current




Figure 6. Output Voltage vs. Output Current




Figure 7. Output Voltage vs. Output Current



**DUAL LDO REGULATORS**

**AP2401**

**Typical Performance Characteristics (Continued)**




Figure 8. Output Voltage vs. Output Current




Figure 9. Output Voltage vs. Output Current




Figure 10. Output Voltage vs. Output Current




Figure 11. Output Voltage vs. Output Current





**DUAL LDO REGULATORS**

**AP2401**

**Typical Performance Characteristics (Continued)**




Figure 12. Output Voltage vs. Input Voltage




Figure 13. Output Voltage vs. Input Voltage




Figure 14. Output Voltage vs. Input Voltage




Figure 15. Output Voltage vs. Input Voltage



**DUAL LDO REGULATORS**

**AP2401**

**Typical Performance Characteristics (Continued)**




Figure 16. Dropout Voltage vs. Output Current




Figure 17. Dropout Voltage vs. Output Current




Figure 18. Dropout Voltage vs. Output Current




Figure 19. Dropout Voltage vs. Output Current



**DUAL LDO REGULATORS**

**AP2401**

**Typical Performance Characteristics (Continued)**




Figure 20. Output Voltage vs. Junction Temperature




Figure 21. Output Voltage vs. Junction Temperature




Figure 22. Output Voltage vs. Junction Temperature




Figure 23. Output Voltage vs. Junction Temperature



**DUAL LDO REGULATORS**

**AP2401**

**Typical Performance Characteristics (Continued)**




Figure 24. Quiescent Current vs. Input Voltage




Figure 25. Quiescent Current vs. Input Voltage




Figure 26. Quiescent Current vs. Input Voltage




Figure 27. Quiescent Current vs. Input Voltage



DUAL LDO REGULATORS

AP2401

Typical Performance Characteristics (Continued)




Figure 28. Quiescent Current vs. Junction Temperature




Figure 29. Quiescent Current vs. Junction Temperature




Figure 30. Quiescent Current vs. Junction Temperature




Figure 31. Quiescent Current vs. Junction Temperature



DUAL LDO REGULATORS

AP2401

Typical Performance Characteristics (Continued)




Figure 32. Line Transient  
(Conditions:  $I_{OUT}=30mA$ ,  $C_{IN}=100nF$ ,  $C_{OUT}=1\mu F$ )




Figure 33. Line Transient  
(Conditions:  $I_{OUT}=30mA$ ,  $C_{IN}=100nF$ ,  $C_{OUT}=1\mu F$ )




Figure 34. Line Transient  
(Conditions:  $I_{OUT}=30mA$ ,  $C_{IN}=100nF$ ,  $C_{OUT}=1\mu F$ )




Figure 35. Line Transient  
(Conditions: channel 1 and 2 on,  $I_{OUT}=30mA$ ,  $C_{IN}=100nF$ ,  $C_{OUT}=1\mu F$ )



DUAL LDO REGULATORS

AP2401

Typical Performance Characteristics (Continued)




Figure 36. Line Transient

(Conditions: channel 1 and 2 on,  $I_{OUT}=30mA$ ,  $C_{IN}=C_{OUT}=1\mu F$ )




Figure 37. Load Transient

(Conditions:  $I_{OUT}=10$  to  $100mA$ ,  $C_{IN}=C_{OUT}=1\mu F$ )




Figure 38. Load Transient

(Conditions:  $I_{OUT}=10$  to  $100mA$ ,  $C_{IN}=C_{OUT}=1\mu F$ )




Figure 39. Load Transient

(Conditions:  $I_{OUT}=10$  to  $100mA$ ,  $C_{IN}=C_{OUT}=1\mu F$ )



DUAL LDO REGULATORS

AP2401

Typical Performance Characteristics (Continued)




Figure 40. Load Transient  
(Conditions:  $I_{OUT}=10$  to  $100\text{mA}$ ,  $C_{IN}=C_{OUT}=1\mu\text{F}$ )




Figure 41. Cross Talk 1  
(Conditions: channel 1 and 2 on,  $I_{OUT1}=30\text{mA}$ ,  $I_{OUT2}=10$  to  $100\text{mA}$ ,  $C_{IN}=C_{OUT}=1\mu\text{F}$ )




Figure 42. Cross Talk 2  
(Conditions: channel 1 and 2 on,  $I_{OUT1}=10$  to  $100\text{mA}$ ,  $I_{OUT2}=30\text{mA}$ ,  $C_{IN}=C_{OUT}=1\mu\text{F}$ )




Figure 43. Cross Talk 3  
(Conditions: channel 1 and 2 on,  $I_{OUT1}=30\text{mA}$ ,  $I_{OUT2}=10$  to  $100\text{mA}$ ,  $C_{IN}=C_{OUT}=1\mu\text{F}$ )





## DUAL LDO REGULATORS

## AP2401

### Typical Performance Characteristics (Continued)




Figure 44. Cross Talk 4  
(Conditions: channel 1 and 2 on,  $I_{OUT1}=10$  to  $100$ mA,  
 $I_{OUT2}=30$ mA,  $C_{IN}=C_{OUT}=1\mu$ F)




Figure 45. Cross Talk 5  
(Conditions: channel 1 and 2 on,  $I_{OUT1}=30$ mA,  
 $I_{OUT2}=10$  to  $100$ mA,  $C_{IN}=C_{OUT}=1\mu$ F)




Figure 46. Cross Talk 6  
(Conditions: channel 1 and 2 on,  $I_{OUT1}=10$  to  $100$ mA,  
 $I_{OUT2}=30$ mA,  $C_{IN}=C_{OUT}=1\mu$ F)




Figure 47. Cross Talk 7  
(Conditions: channel 1 and 2 on,  $I_{OUT1}=I_{OUT2}=10$  to  $100$ mA,  
 $C_{IN}=C_{OUT}=1\mu$ F)



DUAL LDO REGULATORS

AP2401

Typical Performance Characteristics (Continued)




Figure 48. Cross Talk 8

(Conditions: channel 1 and 2 on,  $I_{OUT1}=I_{OUT2}=10$  to  $100$ mA,  $C_{IN}=C_{OUT}=1\mu$ F)




Figure 49. Cross Talk 9

(Conditions: channel 1 and 2 on,  $I_{OUT1}=I_{OUT2}=10$  to  $100$ mA,  $C_{IN}=C_{OUT}=1\mu$ F)




Figure 50. Enable Voltage vs. Output Voltage

(Conditions:  $V_{CE1}=V_{CE2}=0$  to  $2$ V,  $I_{OUT}=0$ mA,  $C_{IN}=C_{OUT}=1\mu$ F)




Figure 51. ESR vs. Output Current



**DUAL LDO REGULATORS**

**AP2401**

**Typical Performance Characteristics (Continued)**




Figure 52. PSRR vs. Frequency




Figure 53. PSRR vs. Frequency




Figure 54. PSRR vs. Frequency




Figure 55. PSRR vs. Frequency



## Typical Application




Figure 56. Typical Application of AP2401




**DUAL LDO REGULATORS**

**AP2401**

**Mechanical Dimensions**

**SOT-23-6**

**Unit: mm(inch)**



www.DataSheet4U.com



## BCD Semiconductor Manufacturing Limited

<http://www.bcdsemi.com>

www.DataSheet4U.com

### IMPORTANT NOTICE

BCD Semiconductor Manufacturing Limited reserves the right to make changes without further notice to any products or specifications herein. BCD Semiconductor Manufacturing Limited does not assume any responsibility for use of any its products for any particular purpose, nor does BCD Semiconductor Manufacturing Limited assume any liability arising out of the application or use of any its products or circuits. BCD Semiconductor Manufacturing Limited does not convey any license under its patent rights or other rights nor the rights of others.

---

#### MAIN SITE

##### - Headquarters

##### BCD Semiconductor Manufacturing Limited

No. 1600, Zi Xing Road, Shanghai Zizhu Science-based Industrial Park, 200241, China  
Tel: +86-21-24162266, Fax: +86-21-24162277

##### - Wafer Fab

##### Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd.

800 Yi Shan Road, Shanghai 200233, China  
Tel: +86-21-6485 1491, Fax: +86-21-5450 0008

#### REGIONAL SALES OFFICE

##### Shenzhen Office

Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd., Shenzhen Office  
Room E, 5F, Noble Center, No.1006, 3rd Fuzhong Road, Futian District, Shenzhen,  
518026, China  
Tel: +86-755-8826 7951  
Fax: +86-755-8826 7865

##### Taiwan Office

BCD Semiconductor (Taiwan) Company Limited  
4F, 298-1, Rui Guang Road, Nei-Hu District, Taipei,  
Taiwan  
Tel: +886-2-2656 2808  
Fax: +886-2-2656 2806

##### USA Office

BCD Semiconductor Corp.  
30920 Huntwood Ave. Hayward,  
CA 94544, USA  
Tel : +1-510-324-2988  
Fax: +1-510-324-2788