



**Advanced Power
Electronics Corp.**


AP92T12GI-HF

Halogen-Free Product

N-CHANNEL ENHANCEMENT MODE

POWER MOSFET


- ▼ Simple Drive Requirement
- ▼ Lower On-resistance
- ▼ RoHS Compliant & Halogen-Free



BV_{DSS}	120V
$R_{DS(ON)}$	8.5m Ω
I_D	53A

Description

Advanced Power MOSFETs from APEC provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.



The TO-220CFM isolation package is widely preferred for commercial-industrial through hole applications.

Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	120	V
V_{GS}	Gate-Source Voltage	+20	V
$I_D@T_C=25^{\circ}C$	Continuous Drain Current, $V_{GS}@10V$	53	A
$I_D@T_C=100^{\circ}C$	Continuous Drain Current, $V_{GS}@10V$	38	A
I_{DM}	Pulsed Drain Current ¹	200	A
$P_D@T_C=25^{\circ}C$	Total Power Dissipation	60	W
T_{STG}	Storage Temperature Range	-55 to 175	$^{\circ}C$
T_J	Operating Junction Temperature Range	-55 to 175	$^{\circ}C$

Thermal Data

Symbol	Parameter	Value	Units
Rthj-c	Maximum Thermal Resistance, Junction-case	2.5	$^{\circ}C/W$
Rthj-a	Maximum Thermal Resistance, Junction-ambient	65	$^{\circ}C/W$



AP92T12GI-HF

Electrical Characteristics@T_j=25°C(unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250uA	120	-	-	V
R _{DS(ON)}	Static Drain-Source On-Resistance ²	V _{GS} =10V, I _D =30A	-	-	8.5	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250uA	2	-	5	V
g _{fs}	Forward Transconductance	V _{DS} =10V, I _D =30A	-	62	-	S
I _{DSS}	Drain-Source Leakage Current	V _{DS} =96V, V _{GS} =0V	-	-	25	uA
I _{GSS}	Gate-Source Leakage	V _{GS} = ±20V, V _{DS} =0V	-	-	±100	nA
Q _g	Total Gate Charge ²	I _D =30A	-	97	155	nC
Q _{gs}	Gate-Source Charge	V _{DS} =96V	-	27	-	nC
Q _{gd}	Gate-Drain ("Miller") Charge	V _{GS} =10V	-	48	-	nC
t _{d(on)}	Turn-on Delay Time ²	V _{DS} =60V	-	27	-	ns
t _r	Rise Time	I _D =30A	-	96	-	ns
t _{d(off)}	Turn-off Delay Time	R _G =3.3Ω, V _{GS} =10V	-	42	-	ns
t _f	Fall Time	R _D =2Ω	-	60	-	ns
C _{iss}	Input Capacitance	V _{GS} =0V	-	4600	7360	pF
C _{oss}	Output Capacitance	V _{DS} =25V	-	800	-	pF
C _{rss}	Reverse Transfer Capacitance	f=1.0MHz	-	260	-	pF
R _g	Gate Resistance	f=1.0MHz	-	2	-	Ω

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V _{SD}	Forward On Voltage ²	I _S =30A, V _{GS} =0V	-	-	1.3	V
t _{rr}	Reverse Recovery Time ²	I _S =10A, V _{GS} =0V	-	80	-	ns
Q _{rr}	Reverse Recovery Charge	dI/dt=100A/μs	-	260	-	nC

Notes:

- 1.Pulse width limited by Max. junction temperature.
- 2.Pulse test

THIS PRODUCT IS SENSITIVE TO ELECTROSTATIC DISCHARGE, PLEASE HANDLE WITH CAUTION.

USE OF THIS PRODUCT AS A CRITICAL COMPONENT IN LIFE SUPPORT OR OTHER SIMILAR SYSTEMS IS NOT AUTHORIZED.

APEC DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

APEC RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Normalized BV_{DSS} v.s. Junction Temperature




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage v.s. Junction Temperature



AP92T12GI-HF




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Switching Time Waveform




Fig 12. Gate Charge Waveform