

APD-128G032

Vishay Dale

**Plasma Display Modules**

128 x 32 Graphics Display with
Drive Electronics and TTL Level Data Interface

**FEATURES**

- TTL level video interface.
- Large characters.
- Highly visible for long distance viewing.
- > 30:1 contrast ratio.
- Bright and pleasant neon orange color.
- Slim profile.
- Very affordable.

The APD-128G032 DC plasma display offers viewing qualities designers seek such as high contrast, viewing angle of 150° minimum and long distance readability. Its bright (50 foot Lambert minimum) with characters and graphics figures presented in a pleasing neon orange color against a black background. Plasma is much more readable and eye-pleasing than liquid crystal or vacuum fluorescent displays and is filterable to red, amber or neutral density.

These plasma display panels are driven in a standard row-column refresh method much like a CRT display. The designer need only supply TTL level signals for SERIAL DATA, DOT CLOCK, COLUMN LATCH, ROW DATA, ROW CLOCK and DISPLAY ENABLE. The SERIAL DATA is entered with the DOT CLOCK up to frequencies as high as 8MHz. After a row of 128 pixels is clocked in, the COLUMN LATCH signal is toggled and the data is latched. At the time the data is latched, the display is briefly disabled using the DISPLAY ENABLE signal, then the row pointer is advanced with the ROW CLOCK signal. Once each frame the ROW DATA must be asserted to synchronize the column serial data with the beginning row. The recommended scanning frequency is approximately 70Hz, but may be as high as 200Hz. The high clock rate on the data clock allows for rapid refresh and maximum access time to the refresh ram.

ELECTRICAL SPECIFICATIONS

Voltage (s) Required: + 75 VDC, V_{sp} . - 110 VDC, V_{sn} .
+ 5 VDC, V_{cc} . + 12 VDC (- 98 VDC), V_{rw} .
(12 VDC to be referenced to - 110 VDC.)

Power Required: Typical = 12 watts. Maximum = 45 watts.

OPTICAL SPECIFICATIONS

Viewing Area: 12.75" [323.8mm] W x 3.15" [80.01mm] L.

Character Array: 8 x 8: 16 x 4. 6 x 8: 21 x 4.

Character Size: 0.65" [16.51mm] H x 0.45" [11.43mm] W.

Pixel Size: 0.050" [1.27mm].


Pixel Pitch: 0.100" [2.54mm].

Luminance: 50 foot lamberts.

STANDARD ELECTRICAL SPECIFICATIONS*					
DESCRIPTION	SYMBOL	MIN.	TYP.	MAX.	UNITS
Logic Supply	V_{cc}	+ 4.5	+ 5.0	+ 5.5	VDC
Anode Supply	V_{sp}	—	+ 75	+ 80.0	VDC
Cathode Supply	V_{sn}	—	- 110	- 125	VDC
Cathode Control**	V_{rw}	+ 10.8	+ 12.0	+ 15.0	VDC
Total V_{sp} and V_{sn}	V_{tot}	170	185	205	VDC
Logic 1 Input	V_{ih}	2.0	—	—	VDC
Logic 0 Input	V_{il}	—	—	0.8	VDC

*Recommended operating voltages . All maximums are absolute maximum.

** V_{rw} is referenced to V_{sn} .

DIMENSIONS in inches [millimeters]**ORDERING INFORMATION****DESCRIPTION**

DESCRIPTION	PART NUMBER
Display, Driver Electronics and TTL Interface	APD-128G032
Data Connector Kit	280105-05
Power Connector Kit	280108-12