


## Features

- +5 dBm Output Level at 811 MHz
- Channel Step Size : 20 kHz
- 2<sup>nd</sup> Harmonic : < -25 dBc
- Spurious Level : < -70 dBc
- Lock Time : < 10 ms
- 19 mA Current Consumption

## Description

The plerow<sup>TM</sup> PLL synthesizer module was designed for use in wireless and wireline systems in a wide range of frequency from 50 MHz to 6 GHz. ASB's PLL provides exceptionally low spurious and phase noise performance with fast locking time and low current consumption. All products are available in a surface-mount type package.



## Specifications

| Parameter                 | Unit   | Min.                  | Typical | Max.  |
|---------------------------|--------|-----------------------|---------|-------|
| Frequency Range           | MHz    | 806.5                 | 811     | 815.5 |
| Output Power              | dBm    | 4                     | 5       | 6     |
| Supply Voltage            | V      | 4.7                   | 5.0     | 5.3   |
| Current Consumption       | mA     |                       | 19      | 30    |
| Channel Step Size         | kHz    |                       | 20      |       |
| 2 <sup>nd</sup> Harmonics | dBc    |                       | -35     | -25   |
| Spurious Level            | dBc    |                       | -78     | -70   |
| Lock Time                 | ms     |                       | 3       | 10    |
| Reference Frequency       | MHz    |                       | 10      |       |
| Reference Input Level     | dBm    | -5                    | 0       | 5     |
| Phase Noise (C / N)       |        |                       |         |       |
| @ 10 kHz                  | dBc/Hz | -111                  | -108    | -105  |
| @ 100 kHz                 | dBc/Hz | -124                  | -121    | -118  |
| Output Impedance          | Ω      |                       | 50      |       |
| Operating Temp. Range     | °C     | -40                   | 25      | 85    |
| Package Type & Size       | mm     | SMT, 19.0W×19.0L×5.8H |         |       |

1) Measurement conditions are as follows: T = 25°C, V<sub>CC</sub> = 5 V, Freq. = 811 MHz, 50 ohm system.


## More Information

Website: [www.asb.co.kr](http://www.asb.co.kr)  
E-mail: [sales@asb.co.kr](mailto:sales@asb.co.kr)

Tel: (82) 42-528-7220  
Fax: (82) 42-528-7222

ASB, Inc., 4<sup>th</sup> Fl. Venture Town  
Bldg, KT HRDC, 367-17  
Goijeong-Dong, Seo-Gu,  
Daejeon, 302-716, Korea

## Outline Drawing



| Pin Configuration |             |
|-------------------|-------------|
| 1                 | CLOCK       |
| 2                 | DATA        |
| 3                 | ENABLE      |
| 4                 | OSC IN      |
| 9                 | VCC (VCO)   |
| 13                | RF OUT      |
| 15                | VCP (PLL)   |
| 16                | LOCK DETECT |
| Others            | Ground      |

| Dimension (mm)   |      |
|------------------|------|
| A                | 19.0 |
| B                | 19.0 |
| C                | 5.8  |
| D                | 1.5  |
| E                | 0.5  |
| F                | 1.75 |
| G                | 1.35 |
| H                | 15.0 |
| I                | 0.9  |
| Tolerance: ± 0.2 |      |