


Asymmetrical - Bridge NPT IGBT Power Module

$V_{CES} = 600V$
 $I_C = 90A @ T_c = 80^\circ C$



Application


- Welding converters
- Switched Mode Power Supplies
- Switched Reluctance Motor Drives

Features

- Non Punch Through (NPT) Fast IGBT®
 - Low voltage drop
 - Low tail current
 - Switching frequency up to 100 kHz
 - Soft recovery parallel diodes
 - Low diode VF
 - Low leakage current
 - Avalanche energy rated
 - RBSOA and SCSOA rated
- Kelvin emitter for easy drive
- Very low stray inductance
 - Symmetrical design
 - Lead frames for power connections
- Internal thermistor for temperature monitoring
- High level of integration

Benefits

- Outstanding performance at high frequency operation
- Stable temperature behavior
- Very rugged
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Solderable terminals both for power and signal for easy PCB mounting
- Easy paralleling due to positive TC of VCEsat
- Low profile
- RoHS compliant



Absolute maximum ratings

| Symbol | Parameter | Max ratings | Unit |
|-----------|---------------------------------------|---------------------|-------------|
| V_{CES} | Collector - Emitter Breakdown Voltage | 600 | V |
| I_C | Continuous Collector Current | $T_c = 25^\circ C$ | 110 |
| | | $T_c = 80^\circ C$ | 90 |
| I_{CM} | Pulsed Collector Current | $T_c = 25^\circ C$ | 315 |
| V_{GE} | Gate - Emitter Voltage | ± 20 | V |
| P_D | Maximum Power Dissipation | $T_c = 25^\circ C$ | 416 |
| RBSOA | Reverse Bias Safe Operating Area | $T_j = 150^\circ C$ | 200A @ 600V |

CAUTION: These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed. See application note APT0502 on www.microsemi.com

All ratings @ $T_j = 25^\circ\text{C}$ unless otherwise specified

Electrical Characteristics

| Symbol | Characteristic | Test Conditions | Min | Typ | Max | Unit |
|---------------|--------------------------------------|--|-----|------------|------------|---------------|
| I_{CES} | Zero Gate Voltage Collector Current | $V_{GE} = 0\text{V}$ $V_{CE} = 600\text{V}$ | | | 250 500 | μA |
| $V_{CE(sat)}$ | Collector Emitter saturation Voltage | $V_{GE} = 15\text{V}$ $I_C = 90\text{A}$ | | 2.0 2.2 | 2.5 | V |
| $V_{GE(th)}$ | Gate Threshold Voltage | $V_{GE} = V_{CE}, I_C = 1\text{mA}$ | 3 | | 5 | V |
| I_{GES} | Gate – Emitter Leakage Current | $V_{GE} = 20\text{V}, V_{CE} = 0\text{V}$ | | | ± 150 | nA |

Dynamic Characteristics

| Symbol | Characteristic | Test Conditions | Min | Typ | Max | Unit |
|--------------|------------------------------|--|-----|------|-----|------|
| C_{ies} | Input Capacitance | $V_{GE} = 0\text{V}$ | | 4300 | | pF |
| C_{oes} | Output Capacitance | $V_{CE} = 25\text{V}$ | | 470 | | |
| C_{res} | Reverse Transfer Capacitance | $f = 1\text{MHz}$ | | 400 | | |
| Q_g | Total gate Charge | $V_{GE} = 15\text{V}$ | | 330 | | nC |
| Q_{ge} | Gate – Emitter Charge | $V_{Bus} = 300\text{V}$ | | 290 | | |
| Q_{gc} | Gate – Collector Charge | $I_C = 90\text{A}$ | | 200 | | |
| $T_{d(on)}$ | Turn-on Delay Time | Inductive Switching (25°C) | | 26 | | ns |
| T_r | Rise Time | $V_{GE} = 15\text{V}$ | | 25 | | |
| $T_{d(off)}$ | Turn-off Delay Time | $V_{Bus} = 400\text{V}$ | | 150 | | |
| T_f | Fall Time | $I_C = 90\text{A}$ $R_G = 5\ \Omega$ | | 30 | | |
| $T_{d(on)}$ | Turn-on Delay Time | Inductive Switching (125°C) | | 26 | | ns |
| T_r | Rise Time | $V_{GE} = 15\text{V}$ | | 25 | | |
| $T_{d(off)}$ | Turn-off Delay Time | $V_{Bus} = 400\text{V}$ | | 170 | | |
| T_f | Fall Time | $I_C = 90\text{A}$ $R_G = 5\ \Omega$ | | 40 | | |
| E_{on} | Turn-on Switching Energy | $V_{GE} = 15\text{V}$ $V_{Bus} = 400\text{V}$ | | 4.3 | | mJ |
| E_{off} | Turn-off Switching Energy | $I_C = 90\text{A}$ $R_G = 5\ \Omega$ | | 3.5 | | |

Diode ratings and characteristics

| Symbol | Characteristic | Test Conditions | Min | Typ | Max | Unit |
|-----------|---|--|-----|-------------|------------|---------------|
| V_{RRM} | Maximum Peak Repetitive Reverse Voltage | | 600 | | | V |
| I_{RM} | Maximum Reverse Leakage Current | $V_R = 600\text{V}$ | | | 250 500 | μA |
| I_F | DC Forward Current | | | 100 | | A |
| V_F | Diode Forward Voltage | $I_F = 100\text{A}$ | | 1.6 | 1.8 | V |
| | | $I_F = 200\text{A}$ | | 1.9 | | |
| | | $I_F = 100\text{A}$ $T_j = 125^\circ\text{C}$ | | 1.4 | | |
| t_{rr} | Reverse Recovery Time | $I_F = 100\text{A}$ $V_R = 400\text{V}$ | | 180 220 | | ns |
| | | $T_j = 25^\circ\text{C}$ | | | | |
| Q_{rr} | Reverse Recovery Charge | $di/dt = 200\text{A}/\mu\text{s}$ | | 390 1450 | | nC |
| | | $T_j = 125^\circ\text{C}$ | | | | |

Thermal and package characteristics


| Symbol | Characteristic | Min | Typ | Max | Unit | |
|-------------------|---|-------------|-----|------|------|-----|
| R _{thJC} | Junction to Case Thermal Resistance | IGBT | | 0.3 | °C/W | |
| | | Diode | | 0.55 | | |
| V _{ISOL} | RMS Isolation Voltage, any terminal to case t = 1 min, I _{isol} < 1mA, 50/60Hz | 2500 | | | V | |
| T _J | Operating junction temperature range | -40 | | 150 | °C | |
| T _{STG} | Storage Temperature Range | -40 | | 125 | | |
| T _C | Operating Case Temperature | -40 | | 100 | | |
| Torque | Mounting torque | To Heatsink | M5 | 2.5 | 4.7 | N.m |
| Wt | Package Weight | | | | 160 | g |

Temperature sensor NTC (see application note APT0406 on www.microsemi.com for more information).

| Symbol | Characteristic | Min | Typ | Max | Unit |
|--------------------|----------------------------|-----|------|-----|------|
| R ₂₅ | Resistance @ 25°C | | 50 | | kΩ |
| B _{25/85} | T ₂₅ = 298.15 K | | 3952 | | K |









$$R_T = \frac{R_{25}}{\exp\left[B_{25/85}\left(\frac{1}{T_{25}} - \frac{1}{T}\right)\right]}$$









T: Thermistor temperature
 R_T: Thermistor value at T





SP4 Package outline (dimensions in mm)

 ALL DIMENSIONS MARKED "*" ARE TOLERANCED AS: $\text{⌀} \pm 0.1$

See application note APT0501 - Mounting Instructions for SP4 Power Modules on www.microsemi.com

Typical Performance Curve







Microsemi reserves the right to change, without notice, the specifications and information contained herein

Microsemi's products are covered by one or more of U.S. patents 4,895,810 5,045,903 5,089,434 5,182,234 5,019,522 5,262,336 6,503,786 5,256,583 4,748,103 5,283,202 5,231,474 5,434,095 5,528,058 and foreign patents. U.S. and Foreign patents pending. All Rights Reserved.