

24V Single-Phase Full-Wave Motor Driver for Fan Motor


Features

- **Single-Phase Full Wave Fan Driver**
- **Low Supply Current**
- **PWM Switch Control for Silent Drive**
- **Speed Controllable by DC Voltage or PWM Input Signal**
- **Built-in Quick Start Function (PWM Mode)**
- **Built-in Lock Protection and Auto-restart Function**
- **Enhance Low Duty Start UP Power**
- **FG/RD Output**
- **Include Hall Bias Circuit**
- **Built-in Current Limit Circuit**
- **Built-in Thermal Protection Circuit**
- **SSOP-16 and TSSOP-16P Package**
- **Lead Free and Green Device Available (RoHS Compliant)**

General Description


The APX9220 is a single-phase full wave motor driver for DC fan motors. The output switch signals of this IC are PWM controlled. It is suitable for both game machine and CPU cooler that need silent fans. The device is built-in lock protection, when fan is locked, the device will enter the lockup protection mode. It is also with thermal shutdown function. In normal operation, the supply current is 3.5mA. The APX9220 is available in SSOP-16 and TSSOP-16P packages.

Pin Configuration



Applications


- **CPU Cooler Fans**
- **Variable Speed Control Fans**
- **Motor Drivers for Silent Fans**



 = Thermal Pad (connected to the GND plane for better heat dissipation)

ANPEC reserves the right to make changes to improve reliability or manufacturability without notice, and advise customers to obtain the latest version of relevant information to verify before placing orders.

Ordering and Marking Information

APX9220	 Assembly Material Handling Code Temperature Range Package Code	Package Code N : SSOP-16 R : TSSOP-16P Operating Ambient Temperature Range I : -40 to 110°C Handling Code TR : Tape & Reel Assembly Material G : Halogen and Lead Free Device
APX9220 N :		XXXXX - Date Code
APX9220 R :		XXXXX - Date Code

Note: ANPEC lead-free products contain molding compounds/die attach materials and 100% matte tin plate termination finish; which are fully compliant with RoHS. ANPEC lead-free products meet or exceed the lead-free requirements of IPC/JEDEC J-STD-020D for MSL classification at lead-free peak reflow temperature. ANPEC defines "Green" to mean lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500ppm by weight).

Absolute Maximum Ratings (Note 1)

Symbol	Parameter	Ratings	Unit
V_{CC}	VCC Pin Supply Voltage (VCC to GND)	-0.3 to 36	V
I_{OUT}	Output Pin Maximum Output Current	1.05	A
V_{OUT}	Output Pin Output Voltage	-0.3 to V_{CC}	V
I_{5VREG}	5VREG Pin Maximum Output Current	20	mA
I_{HB}	HB Pin Maximum Output Current	10	mA
$V_{FG/RD}$	FG/RD Pin Output Voltage	-0.3 to 36	V
$I_{FG/RD}$	FG/RD Pin Maximum Output Sink Current	10	mA
V_{PWM}	PWM Pin Input Voltage	-0.3 to V_{CC}	V
V_{SET}	SET Pin Input Voltage	-0.3 to 7	V
V_{MIN}	MIN Pin Input Voltage	-0.3 to 7	V
V_{VLIM}	VLIM Pin Input Voltage	-0.3 to 7	V
V_{SEL}	SEL Pin Input Voltage	-0.3 to 7	V
V_{SSW}	SSW Pin Input Voltage	-0.3 to 7	V
T_J	Junction Temperature	-40 to 150	°C
T_{STG}	Storage Temperature	-65 to 150	°C
T_{SDR}	Maximum Lead Soldering Temperature (10 Seconds)	260	°C

Note1: Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Thermal Characteristics

Symbol	Parameter	Typical Value	Unit
$R_{TH,JA}$	Thermal Resistance-Junction to Ambient ^(Note 2) SSOP-16 TSSOP-16P	125 113	°C/W
P_D	Power Dissipation, $T_A=25^\circ\text{C}$ SSOP-16 TSSOP-16P	1 1.1	W

Note 2: $R_{TH,JA}$ is measured with the component mounted on a high effective thermal conductivity test board in free air.

Recommended Operating Conditions (Note3)

Symbol	Parameter	Range	Unit
V_{CC}	VCC Pin Supply Voltage Range	4 to 34	V
V_{HALL}	Hall Input Voltage Range	0.2 to 3	V
V_{SET}	SET Pin Input Voltage Range	0 to V_{SVREG}	V
V_{MIN}	MIN Pin Input Voltage Range	0 to V_{SVREG}	V
V_{VLIM}	VLIM Pin Input Voltage Range	0 to V_{SVREG}	V
V_{SSW}	SSW Pin Input Voltage Range	0 to V_{SVREG}	V
T_A	Ambient Temperature	-40 to 110	°C
T_J	Junction Temperature	-40 to 125	°C

Note 3: Refer to the typical application circuit.







Electrical Characteristics ($V_{CC} = 24V$, $T_A = 25^\circ C$, unless otherwise specified)

Symbol	Parameter	Test Conditions	APX9220			Unit
			Min	Typ	Max	
SUPPLY CURRENT						
V_{HB}	HB Pin Output Voltage	$I_{HB} = 5mA$	1.2	1.3	1.4	V
V_{5VREG}	5VREG Pin Output Voltage	$I_{5VREG} = 5mA$	4.75	5	5.25	V
I_{CC1}	Operating Current	Rotation Mode	2.5	4	5.5	mA
I_{CC2}		Lock Protection Mode	1.7	3.2	4.7	
OSCILLATOR						
V_{OSCH}	OSC Pin High Level Voltage		3.2	3.5	3.8	V
V_{OSCL}	OSC Pin Low Level Voltage		0.8	1	1.2	V
I_{osc1}	OSC Charge Current	$V_{osc}=1V$	15	20	25	μA
I_{osc2}	OSC Discharge Current	$V_{osc}=3.5V$	15	20	25	μA
F_{osc}	OSC Oscillation Frequency	$C_{osc}=100pF$	30	40	50	kHz
LOCK PROTECTION						
T_{ON}	Lock Detection On Time		0.35	0.5	0.65	sec
T_{OFF}	Lock Detection OFF Time		3.5	5	6.5	sec
T_{QS}	Quick Start Enable Time		-	66.5	90	msec
OUTPUT DRIVERS						
V_O	Output Lower Side Saturation Voltage	$I_{OUT} = 300mA$, Upper and Lower total	-	0.4	0.6	V
V_{FG}	FG Pin Low Voltage	$I_{FG} = 5mA$	-	0.1	0.3	V
I_{FGL}	FG Pin Leakage Current	$V_{FG} = 24V$	-	<0.1	1	μA
PWM CONTROL						
V_{PWMH}	PWM Input High Level Voltage		2.5		$V_{CC}+0.3$	V
V_{PWML}	PWM Input Low Level Voltage		-0.3		0.7	V
F_{PWM}	PWM Input Frequency		2		50	kHz
DTS	Start Up PWM Duty	$F_{PWM}=2KHz\sim50Khz$	6	8	10	%
HALL SENSITIVITY						
V_{HN}	FG Hall Input Sensitivity		-	10	20	mV
SOFT SWITCH CONTROL						
V_{hys_ss}	Soft Switch Hysteresis Voltage	0V <= SSW <= 1V or floating		30		mV
		SSW=2.5V		75		mV
		SSW=4V		120		mV
CURRENT LIMIT						
I_{LM}	Current Limit	$V_{VLIM}=0\sim0.5V$		150		mA
		$V_{VLIM}=3.5V$		1050		mA
THERMAL PROTECTION						
	Over-Temperature Shutdown Threshold		-	180	-	°C
	Over-Temperature Shutdown Hysteresis		-	40	-	






Pin Descriptions

PIN		FUNCTION
NO.	NAME	
1	PGND	Power Stage GND.
2	OUT2	H-bridge Output Connection.
3	VCC	Supply Voltage Input Pin.
4	5VREG	5V Regulator Output. This is a 5V constant-voltage output for application circuit biases.
5	MIN	Minimum Speed Setting. An external voltage into MIN pin to set fan speed.
6	SET	Speed Setting. An external voltage into SET pin to set fan speed.
7	OSC	Oscillation Frequency Setting. Connect a capacitor to GND to set oscillation frequency.
8	PWM	PWM Signal Input Terminal.
9	FG/RD	Rotation Speed Output/Rotation Detection Output.
10	IN+	Hall Input +. Connect to hall element positive output.
11	HB	Hall Bias. This is a 1.3V constant-voltage output for hall element bias.
12	IN-	Hall Input -. Connect to hall element negative output.
13	SSW	Voltage input pin for control between soft switches
14	SEL	FG/RD output select pin.
15	VLIM	Current Limit Setting. Use a voltage divider from 5VREG to set VLIM pin voltage to set current limit value.
16	OUT1	H-bridge Output Connection.


Typical Operating Characteristics



Typical Operating Characteristics (Cont.)




Block Diagram



Typical Application Circuit


1. SET Voltage Input Speed Control



Note R1 is optional to reduce the power consumption from HB supply current.
R2 is optional to adjust the amplitude of hall signal .

Typical Application Circuit

2. Direct PWM Input Speed Control.



Note R1 is optional to reduce the power consumption from HB supply current.
 R2 is optional to adjust the amplitude of hall signal.

Function Descriptions

Lockup Protection and Automatic Restart

The APX9220 provides the lockup protection and automatic restart functions for preventing the coil burn-out when the fan is locked. This IC has an internal counter to determine the shutdown time (T_{OFF}) and restart time (T_{ON}). During shutdown time, the output drivers keep turn off for 5 seconds and then enter the restart time. During the restart time, one output is high and the other is low, which makes a torque for fan rotation. The restart time has 0.5 second. If the locked condition is not removed, the shutdown/restart process will be recurred until the locked condition is released (see Fig1. Lockup/Auto Restart Waveform).




Figure 1. Lockup /Auto Restart Waveform

Quick Start and Standby mode

This IC would enter standby mode when the PWM input keeps low level for more than 66.5 ms (typ.). In standby mode, it will shut down amplifier and FG. Thus, the supply current is around 3.2mA. In standby mode, the lock protection function doesn't work, therefore, starting fan is unobstructed when releasing standby mode.




Figure 2. Quick Start Waveform

Output Drivers

All four drivers in the bridge output are designed for single phase full wave motor driver for fan motor. The linear output architecture is used as output driver.

Rotation Detection Function

The FG pin is an open drain output, connecting a pull up resistor to a high level voltage for the frequency generator function. When IN+ is larger than IN- then FG is high (switch off) and IN+ is smaller than IN- then FG is low (switch on). Open the terminal when not in using. RD pin is also open drain output. Low level is at rotation mode and High Level is at stop mode.

Thermal Protection

The APX9220 has thermal protection function, when internal junction temperature reaches 180°C, the output devices will be switched off. When the IC's junction temperature cools by 40°C, the thermal sensor will turn the output devices on again, resulting in a pulsed output during continuous thermal protection.

Truth Table

Input				Output				
IN-	IN+	OSC	PWM	OUT1	OUT2	FG	RD	Mode
H	L	H	H	H	L	L	L	Normal Operation Mode
L	H			L	H	OFF	L	
L	H	L	L	L	L	OFF	L	
H	L			L	L	L	L	
H	L	-	-	L	L	OFF	OFF	Lock Protection Mode
L	H			L	L	OFF		
-	-	-	L	OFF	OFF	OFF	OFF	Standby Mode

Note 4: OSC-H corresponds to $V_{OSC} > V_{SET}$ and OSC-L corresponds to $V_{OSC} < V_{SET}$

Application Information

Input Protection Diode & Capacitor

It should be added a protection diode (D1) to protect the damage from the power reverse connection. However, the protection diode will cause a voltage drop on the supply voltage. The current rating of the diode must be larger than the maximum output current. For the noise reduction purpose, there is a least $1\mu\text{F}$ capacitor (C1) recommended connecting between VCC and GND (see Typical Application Circuit).

FG/RD Resistor

The value of the FG/RD resistor could be decided by the following equation:

$$R_{FG} = \frac{V_{CC} - V_{FG}}{I_{FG}}$$

For example:

$$V_{CC}=12\text{V}, I_{FG}=5\text{mA}, V_{FG}=0.1\text{V}, R_{FG}=2.38\text{k}\Omega$$

The value of resistor in the range of $1\text{k}\Omega$ to $10\text{k}\Omega$ is recommended.

Adjustment of voltage between soft switches

The width of soft switch before and after switching is controlled by SSW voltage. The voltage range is between 1V to 4V .Normal adjustment voltage of SSW between hall input signals. (see Fig.4) When input signal amplitude is less V_{HYS_SS} IC is full duty.(see Fig.5)




Figure 4. When hall signal > V_{HYS_SS} . Different width of soft switch is controlled by SSW input voltage.





Figure 5. When hall signal < V_{HYS_SS} . Out1 and Out2 always are high switch. .

Package Information

SSOP-16




SYMBOL	SSOP-16			
	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A		1.75		0.069
A1	0.10	0.25	0.004	0.010
A2	1.24		0.049	
b	0.20	0.30	0.008	0.012
c	0.15	0.25	0.006	0.010
D	4.80	5.00	0.189	0.197
E	5.80	6.20	0.228	0.244
E1	3.80	4.00	0.150	0.157
e	0.635 BSC		0.025 BSC	
L	0.40	1.27	0.016	0.050
h	0.25	0.50	0.010	0.020
θ	0°	8°	0°	8°

- Note :
- Follow JEDEC MO-137 AB.
 - Dimension "D" does not include mold flash, protrusions or gate burrs.
Mold flash, protrusion or gate burrs shall not exceed 6 mil per side.
 - Dimension "E" does not include inter-lead flash or protrusions.
Inter-lead flash and protrusions shall not exceed 10 mil per side.


Package Information

TSSOP-16P



- Note : 1. Follow from JEDEC MO-153 AB.
 2. Dimension "D" does not include mold flash, protrusions or gate burrs. Mold flash, protrusion or gate burrs shall not exceed 6 mil per side.
 3. Dimension "E1" does not include inter-lead flash or protrusions. Inter-lead flash and protrusions shall not exceed 10 mil per side.

Carrier Tape & Reel Dimensions



Application	A	H	T1	C	d	D	W	E1	F
SSOP-16	330.0±2.00	50 MIN.	12.4+2.00 -0.00	13.0+0.50 -0.20	1.5 MIN.	20.2 MIN.	12.0±0.30	1.75±0.10	5.50±0.05
	P0	P1	P2	D0	D1	T	A0	B0	K0
	4.00±0.10	8.00±0.10	2.00±0.05	1.5+0.10 -0.00	1.5 MIN.	0.6+0.00 -0.40	6.55±0.20	5.25±0.20	2.10±0.20
Application	A	H	T1	C	d	D	W	E1	F
TSSOP-16P	330.0±2.00	50 MIN.	12.4+2.00 -0.00	13.0+0.50 -0.20	1.5 MIN.	20.2 MIN.	12.0±0.30	1.75±0.10	5.50±0.05
	4.00±0.10	8.00±0.10	2.00±0.05	1.5+0.10 -0.00	1.5 MIN.	0.6+0.00 -0.40	6.80±0.20	5.40±0.20	1.60±0.20

(mm)


Devices Per Unit

Package Type	Unit	Quantity
SSOP- 16	Tape & Reel	2500
TSSOP- 16P	Tape & Reel	2500


APX9220

Taping Direction Information


SSOP-16



TSSOP-16P



Classification Profile



Classification Reflow Profiles

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat & Soak Temperature min (T_{smin}) Temperature max (T_{smax}) Time (T_{smin} to T_{smax}) (t_s)	100 °C 150 °C 60-120 seconds	150 °C 200 °C 60-120 seconds
Average ramp-up rate (T_{smax} to T_p)	3 °C/second max.	3°C/second max.
Liquidous temperature (T_L) Time at liquidous (t_L)	183 °C 60-150 seconds	217 °C 60-150 seconds
Peak package body Temperature (T_p)*	See Classification Temp in table 1	See Classification Temp in table 2
Time (t_p)** within 5°C of the specified classification temperature (T_c)	20** seconds	30** seconds
Average ramp-down rate (T_p to T_{smax})	6 °C/second max.	6 °C/second max.
Time 25°C to peak temperature	6 minutes max.	8 minutes max.

* Tolerance for peak profile Temperature (T_p) is defined as a supplier minimum and a user maximum.
 ** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

Table 1. SnPb Eutectic Process – Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2. Pb-free Process – Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 mm – 2.5 mm	260 °C	250 °C	245 °C
≥2.5 mm	250 °C	245 °C	245 °C

Reliability Test Program

Test item	Method	Description
SOLDERABILITY	JESD-22, B102	5 Sec, 245°C
HOLT	JESD-22, A108	1000 Hrs, Bias @ $T_j=125^\circ\text{C}$
PCT	JESD-22, A102	168 Hrs, 100%RH, 2atm, 121°C
TCT	JESD-22, A104	500 Cycles, -65°C~150°C
HBM	MIL-STD-883-3015.7	VHBM \geq 2KV
MM	JESD-22, A115	VMM \geq 200V
Latch-Up	JESD 78	10ms, $I_{tr} \geq 100\text{mA}$

APX9220

Customer Service

Anpec Electronics Corp.

Head Office :

No.6, Dusing 1st Road, SBIP,
Hsin-Chu, Taiwan
Tel : 886-3-5642000
Fax : 886-3-5642050

Taipei Branch :

2F, No. 11, Lane 218, Sec 2 Jhongsing Rd.,
Sindian City, Taipei County 23146, Taiwan
Tel : 886-2-2910-3838
Fax : 886-2-2917-3838