




2.5V 1M × 32/36 pipelined burst synchronous SRAM

Features

- Organization: 1,048,576 words × 32 or 36 bits
- Fast clock speeds to 200 MHz
- Fast clock to data access: 3.1/3.5/3.8 ns
- Fast \overline{OE} access time: 3.1/3.5/3.8 ns
- Fully synchronous register-to-register operation
- Double-cycle deselect
- Asynchronous output enable control
- Available in 100-pin TQFP package
- Individual byte write and global write
- Multiple chip enables for easy expansion
- 2.5V core power supply
- Linear or interleaved burst control
- Snooze mode for reduced power-standby
- Common data inputs and data outputs

Logic block diagram



Selection guide

| | -200 | -166 | -133 | Units |
|-----------------------------------|------|------|------|-------|
| Minimum cycle time | 5 | 6 | 7.5 | ns |
| Maximum clock frequency | 200 | 166 | 133 | MHz |
| Maximum clock access time | 3.1 | 3.5 | 3.8 | ns |
| Maximum operating current | 450 | 400 | 350 | mA |
| Maximum standby current | 170 | 150 | 140 | mA |
| Maximum CMOS standby current (DC) | 90 | 90 | 90 | mA |



2.5V 32 Mb Synchronous SRAM products list^{1,2}

| Org | Part Number | Mode | Speed |
|-------|----------------|--------|-----------------|
| 2MX18 | AS7C252MPFS18A | PL-SCD | 200/166/133 MHz |
| 1MX32 | AS7C251MPFS32A | PL-SCD | 200/166/133 MHz |
| 1MX36 | AS7C251MPFS36A | PL-SCD | 200/166/133 MHz |
| 2MX18 | AS7C252MPFD18A | PL-DCD | 200/166/133 MHz |
| 1MX32 | AS7C251MPFD32A | PL-DCD | 200/166/133 MHz |
| 1MX36 | AS7C251MPFD36A | PL-DCD | 200/166/133 MHz |
| 2MX18 | AS7C252MFT18A | FT | 7.5/8.5/10 ns |
| 1MX32 | AS7C251MFT32A | FT | 7.5/8.5/10 ns |
| 1MX36 | AS7C251MFT36A | FT | 7.5/8.5/10 ns |
| 2MX18 | AS7C252MNTD18A | NTD-PL | 200/166/133 MHz |
| 1MX32 | AS7C251MNTD32A | NTD-PL | 200/166/133 MHz |
| 1MX36 | AS7C251MNTD36A | NTD-PL | 200/166/133 MHz |
| 2MX18 | AS7C252MNTF18A | NTD-FT | 7.5/8.5/10 ns |
| 1MX32 | AS7C251MNTF32A | NTD-FT | 7.5/8.5/10 ns |
| 1MX36 | AS7C251MNTF36A | NTD-FT | 7.5/8.5/10 ns |

1 Core Power Supply: VDD = 2.5V ± 0.125V

2 I/O Supply Voltage: VDDQ = 2.5V ± 0.125V


- PL-SCD : Pipelined Burst Synchronous SRAM - Single Cycle Deselect
- PL-DCD : Pipelined Burst Synchronous SRAM - Double Cycle Deselect
- FT : Flow-through Burst Synchronous SRAM
- NTD¹-PL : Pipelined Burst Synchronous SRAM with NTDTM
- NTD-FT : Flow-through Burst Synchronous SRAM with NTDTM

1NTD: No Turnaround Delay. NTDTM is a trademark of Alliance Semiconductor Corporation. All trademarks mentioned in this document are the property of their respective owners.



Pin assignment

100-pin TQFP - top view



Note: For pins 1, 30, 51, and 80, NC applies to the x32 configuration. DQPn applies to the x36 configuration.



Functional description

The AS7C251MPFD32A/36A is a high-performance CMOS 32-Mbit synchronous Static Random Access Memory (SRAM) device organized as 1,048,576 words x 32/36. It incorporates a two-stage register-register pipeline for highest frequency on any given technology.

Fast cycle times of 5/6/7.5 ns with clock access times (t_{CD}) of 3.1/3.5/3.8 ns enable 200,167 and 133 MHz bus frequencies. Three chip enable (\overline{CE}) inputs permit easy memory expansion. Burst operation is initiated in one of two ways: the controller address strobe (\overline{ADSC}), or the processor address strobe (\overline{ADSP}). The burst advance pin (\overline{ADV}) allows subsequent internally generated burst addresses.

Read cycles are initiated with \overline{ADSP} (regardless of \overline{WE} and \overline{ADSC}) using the new external address clocked into the on-chip address register when \overline{ADSP} is sampled low, the chip enables are sampled active, and the output buffer is enabled with \overline{OE} . In a read operation, the data accessed by the current address registered in the address registers by the positive edge of CLK are carried to the data-out registers and driven on the output pins on the next positive edge of CLK. \overline{ADV} is ignored on the clock edge that samples \overline{ADSP} asserted, but is sampled on all subsequent clock edges. Address is incremented internally for the next access of the burst when \overline{ADV} is sampled low and both address strobes are high. Burst mode is selectable with the \overline{LBO} input. With \overline{LBO} unconnected or driven high, burst operations use an interleaved count sequence. With \overline{LBO} driven low, the device uses a linear count sequence.

Write cycles are performed by disabling the output buffers with \overline{OE} and asserting a write command. A global write enable \overline{GWE} writes all 32/36 bits regardless of the state of individual $\overline{BW[a:d]}$ inputs. Alternately, when \overline{GWE} is high, one or more bytes may be written by asserting \overline{BWE} and the appropriate individual byte \overline{BWn} signals.

\overline{BWn} is ignored on the clock edge that samples \overline{ADSP} low, but it is sampled on all subsequent clock edges. Output buffers are disabled when \overline{BWn} is sampled LOW regardless of \overline{OE} . Data is clocked into the data input register when \overline{BWn} is sampled low. Address is incremented internally to the next burst address if \overline{BWn} and \overline{ADV} are sampled low. This device operates in double-cycle deselect feature during read cycles.

Read or write cycles may also be initiated with \overline{ADSC} instead of \overline{ADSP} . The differences between cycles initiated with \overline{ADSC} and \overline{ADSP} follow.

- \overline{ADSP} must be sampled high when \overline{ADSC} is sampled low to initiate a cycle with \overline{ADSC} .
- \overline{WE} signals are sampled on the clock edge that samples \overline{ADSC} low (and \overline{ADSP} high).
- Master chip enable $\overline{CE0}$ blocks \overline{ADSP} , but not \overline{ADSC} .

The AS7C251MPFD32A/36A family operates with a $2.5V \pm 5\%$ power supply for the device core (V_{DD}). These devices are available in a 100-pin TQFP package.

TQFP capacitance

| Parameter | Symbol | Test conditions | Min | Max | Unit |
|-------------------|-------------|-----------------|-----|-----|------|
| Input capacitance | C_{IN}^* | $V_{IN} = 0V$ | - | 5 | pF |
| I/O capacitance | $C_{I/O}^*$ | $V_{OUT} = 0V$ | - | 7 | pF |

* Guaranteed not tested

TQFP thermal resistance

| Description | Conditions | Symbol | Typical | Units | |
|---|---|---------------|---------------|-------|------|
| Thermal resistance (junction to ambient) ¹ | Test conditions follow standard test methods and procedures for measuring thermal impedance, per EIA/JESD51 | 1-layer | θ_{JA} | 40 | °C/W |
| | | 4-layer | θ_{JA} | 22 | °C/W |
| Thermal resistance (junction to top of case) ¹ | | θ_{JC} | 8 | °C/W | |

¹ This parameter is sampled



Signal descriptions

| Pin | I/O | Properties | Description |
|--------------------------|-----|------------|--|
| CLK | I | CLOCK | Clock. All inputs except \overline{OE} , ZZ, and \overline{LBO} are synchronous to this clock. |
| A,A0,A1 | I | SYNC | Address. Sampled when all chip enables are active and when \overline{ADSC} or \overline{ADSP} are asserted. |
| DQ[a,b,c,d] | I/O | SYNC | Data. Driven as output when the chip is enabled and when \overline{OE} is active. |
| $\overline{CE0}$ | I | SYNC | Master chip enable. Sampled on clock edges when \overline{ADSP} or \overline{ADSC} is active. When $\overline{CE0}$ is inactive, \overline{ADSP} is blocked. Refer to the “Synchronous truth table” for more information. |
| CE1, $\overline{CE2}$ | I | SYNC | Synchronous chip enables, active high, and active low, respectively. Sampled on clock edges when \overline{ADSC} is active or when $\overline{CE0}$ and \overline{ADSP} are active. |
| \overline{ADSP} | I | SYNC | Address strobe processor. Asserted low to load a new address or to enter standby mode. |
| \overline{ADSC} | I | SYNC | Address strobe controller. Asserted low to load a new address or to enter standby mode. |
| \overline{ADV} | I | SYNC | Advance. Asserted low to continue burst read/write. |
| \overline{GWE} | I | SYNC | Global write enable. Asserted low to write all 32/36 bits. When high, \overline{BWE} and $\overline{BW[a:d]}$ control write enable. |
| \overline{BWE} | I | SYNC | Byte write enable. Asserted low with \overline{GWE} high to enable effect of $\overline{BW[a:d]}$ inputs. |
| $\overline{BW[a,b,c,d]}$ | I | SYNC | Write enables. Used to control write of individual bytes when \overline{GWE} is high and \overline{BWE} is low. If any of $\overline{BW[a:d]}$ is active with \overline{GWE} high and \overline{BWE} low, the cycle is a write cycle. If all $\overline{BW[a:d]}$ are inactive, the cycle is a read cycle. |
| \overline{OE} | I | ASYNC | Asynchronous output enable. I/O pins are driven when \overline{OE} is active and chip is in read mode. |
| \overline{LBO} | I | STATIC | Selects Burst mode. When tied to V_{DD} or left floating, device follows interleaved Burst order. When driven Low, device follows linear Burst order. <i>This signal is internally pulled High.</i> |
| ZZ | I | ASYNC | Snooze. Places device in low power mode; data is retained. Connect to GND if unused. |
| NC | - | - | No connect |

Snooze Mode

SNOOZE MODE is a low current, power-down mode in which the device is deselected and current is reduced to I_{SB2} . The duration of SNOOZE MODE is dictated by the length of time the ZZ is in a High state.

The ZZ pin is an asynchronous, active high input that causes the device to enter SNOOZE MODE.

When the ZZ pin becomes a logic High, I_{SB2} is guaranteed after the time t_{ZZ1} is met. After entering SNOOZE MODE, all inputs except ZZ is disabled and all outputs go to High-Z. Any operation pending when entering SNOOZE MODE is not guaranteed to successfully complete. Therefore, SNOOZE MODE (READ or WRITE) must not be initiated until valid pending operations are completed. Similarly, when exiting SNOOZE MODE during t_{PUS} , only a DESELECT or READ cycle should be given while the SRAM is transitioning out of SNOOZE MODE.



Write enable truth table (per byte)

| Function | $\overline{\text{GWE}}$ | $\overline{\text{BWE}}$ | $\overline{\text{BWa}}$ | $\overline{\text{BWb}}$ | $\overline{\text{BWc}}$ | $\overline{\text{BWd}}$ |
|--------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| Write All Bytes | L | X | X | X | X | X |
| | H | L | L | L | L | L |
| Write Byte a | H | L | L | H | H | H |
| Write Byte c and d | H | L | H | H | L | L |
| Read | H | H | X | X | X | X |
| | H | L | H | H | H | H |

Key: X = don't care, L = low, H = high, n = a, b, c, d; $\overline{\text{BWE}}$, $\overline{\text{BWn}}$ = internal write signal.

www.DataSheet4U.com

Asynchronous Truth Table

| Operation | ZZ | $\overline{\text{OE}}$ | I/O Status |
|-------------|----|------------------------|-------------|
| Snooze mode | H | X | High-Z |
| Read | L | L | Dout |
| | L | H | High-Z |
| Write | L | X | Din, High-Z |
| Deselected | L | X | High-Z |

Notes:

1. X means "Don't Care"
2. ZZ pin is pulled down internally
3. For write cycles that follows read cycles, the output buffers must be disabled with $\overline{\text{OE}}$, otherwise data bus contention will occur.
4. Snooze mode means power down state of which stand-by current does not depend on cycle times
5. Deselected means power down state of which stand-by current depends on cycle times

Burst sequence table

| Interleaved burst address ($\overline{\text{LBO}} = 1$) | | | | | Linear burst address ($\overline{\text{LBO}} = 0$) | | | | |
|---|-------|-------|-------|-------|--|-------|-------|-------|-------|
| | A1 A0 | A1 A0 | A1 A0 | A1 A0 | | A1 A0 | A1 A0 | A1 A0 | A1 A0 |
| Starting Address | 0 0 | 0 1 | 1 0 | 1 1 | Starting Address | 0 0 | 0 1 | 1 0 | 1 1 |
| First Increment | 0 1 | 0 0 | 1 1 | 1 0 | First Increment | 0 1 | 1 0 | 1 1 | 0 0 |
| Second Increment | 1 0 | 1 1 | 0 0 | 0 1 | Second Increment | 1 0 | 1 1 | 0 0 | 0 1 |
| Third Increment | 1 1 | 1 0 | 0 1 | 0 0 | Third Increment | 1 1 | 1 0 | 0 1 | 1 0 |



Synchronous truth table ^[4]

| $\overline{CE0}^1$ | CE1 | $\overline{CE2}$ | \overline{ADSP} | \overline{ADSC} | \overline{ADV} | $\overline{WRITE}^{[2]}$ | \overline{OE} | Address accessed | CLK | Operation | DQ |
|--------------------|-----|------------------|-------------------|-------------------|------------------|--------------------------|-----------------|------------------|--------|----------------|----------------|
| H | X | X | X | L | X | X | X | NA | L to H | Deselect | Hi-Z |
| L | L | X | L | X | X | X | X | NA | L to H | Deselect | Hi-Z |
| L | L | X | H | L | X | X | X | NA | L to H | Deselect | Hi-Z |
| L | X | H | L | X | X | X | X | NA | L to H | Deselect | Hi-Z |
| L | X | H | H | L | X | X | X | NA | L to H | Deselect | Hi-Z |
| L | H | L | L | X | X | X | L | External | L to H | Begin read | Q |
| L | H | L | L | X | X | X | H | External | L to H | Begin read | Hi-Z |
| L | H | L | H | L | X | H | L | External | L to H | Begin read | Q |
| L | H | L | H | L | X | H | H | External | L to H | Begin read | Hi-Z |
| X | X | X | H | H | L | H | L | Next | L to H | Continue read | Q |
| X | X | X | H | H | L | H | H | Next | L to H | Continue read | Hi-Z |
| X | X | X | H | H | H | H | L | Current | L to H | Suspend read | Q |
| X | X | X | H | H | H | H | H | Current | L to H | Suspend read | Hi-Z |
| H | X | X | X | H | L | H | L | Next | L to H | Continue read | Q |
| H | X | X | X | H | L | H | H | Next | L to H | Continue read | Hi-Z |
| H | X | X | X | H | H | H | L | Current | L to H | Suspend read | Q |
| H | X | X | X | H | H | H | H | Current | L to H | Suspend read | Hi-Z |
| L | H | L | H | L | X | L | X | External | L to H | Begin write | D ³ |
| X | X | X | H | H | L | L | X | Next | L to H | Continue write | D |
| H | X | X | X | H | L | L | X | Next | L to H | Continue write | D |
| X | X | X | H | H | H | L | X | Current | L to H | Suspend write | D |
| H | X | X | X | H | H | L | X | Current | L to H | Suspend write | D |

1 X = don't care, L = low, H = high

2 For \overline{WRITE} , L means any one or more byte write enable signals (\overline{BWA} , \overline{BWB} , \overline{BWC} or \overline{BWD}) and \overline{BWE} are LOW or \overline{GWE} is LOW. \overline{WRITE} = HIGH for all \overline{BWx} , \overline{BWE} , \overline{GWE} HIGH. See "Write enable truth table (per byte)," on page 6 for more information.

3 For write operation following a READ, \overline{OE} must be high before the input data set up time and held high throughout the input hold time

4 ZZ pin is always Low.



Absolute maximum ratings

| Parameter | Symbol | Min | Max | Unit |
|--|-------------------|------|-----------------|------|
| Power supply voltage relative to GND | V_{DD}, V_{DDQ} | -0.3 | +3.6 | V |
| Input voltage relative to GND (input pins) | V_{IN} | -0.3 | $V_{DD} + 0.3$ | V |
| Input voltage relative to GND (I/O pins) | V_{IN} | -0.3 | $V_{DDQ} + 0.3$ | V |
| Power dissipation | P_d | - | 1.8 | W |
| Short circuit output current | I_{OUT} | - | 20 | mA |
| Storage temperature | T_{stg} | -65 | +150 | °C |
| Temperature under bias | T_{bias} | -65 | +135 | °C |

Stresses greater than those listed under “Absolute maximum ratings” may cause permanent damage to the device. This is a stress rating only, and functional operation of the device at these or any other conditions outside those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions may affect reliability.

Recommended operating conditions

| Parameter | Symbol | Min | Nominal | Max | Unit |
|---------------------------|-----------|-------|---------|-------|------|
| Supply voltage for inputs | V_{DD} | 2.375 | 2.5 | 2.625 | V |
| Supply voltage for I/O | V_{DDQ} | 2.375 | 2.5 | 2.625 | V |
| Ground supply | V_{SS} | 0 | 0 | 0 | V |



DC electrical characteristics

| Parameter | Sym | Conditions | Min | Max | Unit |
|------------------------------------|-----------------|--|--------|-----------------------|------|
| Input leakage current [†] | I _{LI} | V _{DD} = Max, 0V ≤ V _{IN} ≤ V _{DD} | -2 | 2 | μA |
| Output leakage current | I _{LO} | OE ≥ V _{IH} , V _{DD} = Max, 0V ≤ V _{OUT} ≤ V _{DDQ} | -2 | 2 | μA |
| Input high (logic 1) voltage | V _{IH} | Address and control pins | 1.7* | V _{DD} +0.3 | V |
| | | I/O pins | 1.7* | V _{DDQ} +0.3 | V |
| Input low (logic 0) voltage | V _{IL} | Address and control pins | -0.3** | 0.7 | V |
| | | I/O pins | -0.3** | 0.7 | V |
| Output high voltage | V _{OH} | I _{OH} = -4 mA, V _{DDQ} = 2.375V | 1.7 | - | V |
| Output low voltage | V _{OL} | I _{OL} = 8 mA, V _{DDQ} = 2.625V | - | 0.7 | V |

[†] LBO and ZZ pins have an internal pull-up or pull-down, and input leakage = ±10 μA.

*V_{IH} max < V_{DD} +1.5V for pulse width less than 0.2 X t_{CYC}

**V_{IL} min = -1.5 for pulse width less than 0.2 X t_{CYC}

I_{DD} operating conditions and maximum limits

| Parameter | Sym | Conditions | -200 | -166 | -133 | Unit |
|---|------------------|---|------|------|------|------|
| Operating power supply current ¹ | I _{CC} | $\overline{CE0} \leq V_{IL}$, CE1 ≥ V _{IH} , $\overline{CE2} \leq V_{IL}$, f = f _{Max} , I _{OUT} = 0 mA, ZZ ≤ V _{IL} | 450 | 400 | 350 | mA |
| Standby power supply current | I _{SB} | All V _{IN} ≤ 0.2V or ≥ V _{DD} - 0.2V, Deselected, f = f _{Max} , ZZ ≤ V _{IL} | 170 | 150 | 140 | mA |
| | I _{SB1} | Deselected, f = 0, ZZ ≤ 0.2V, all V _{IN} ≤ 0.2V or ≥ V _{DD} - 0.2V | 90 | 90 | 90 | |
| | I _{SB2} | Deselected, f = f _{Max} , ZZ ≥ V _{DD} - 0.2V, all V _{IN} ≤ V _{IL} or ≥ V _{IH} | 80 | 80 | 80 | |

¹ I_{CC} given with no output loading. I_{CC} increases with faster cycle times and greater output loading.



Timing characteristics over operating range

| Parameter | Sym | -200 | | -166 | | -133 | | Unit | Notes ¹ |
|--|-------------|------|-----|------|-----|------|-----|------|--------------------|
| | | Min | Max | Min | Max | Min | Max | | |
| Clock frequency | f_{Max} | – | 200 | – | 166 | – | 133 | MHz | |
| Cycle time | t_{CYC} | 5 | – | 6 | – | 7.5 | – | ns | |
| Clock access time | t_{CD} | – | 3.1 | – | 3.5 | – | 3.8 | ns | |
| Output enable low to data valid | t_{OE} | – | 3.1 | – | 3.5 | – | 3.8 | ns | |
| Clock high to output low Z | t_{LZC} | 0 | – | 0 | – | 0 | – | ns | 2,3,4 |
| Data output invalid from clock high | t_{OH} | 1.5 | – | 1.5 | – | 1.5 | – | ns | 2 |
| Output enable low to output low Z | t_{LZOE} | 0 | – | 0 | – | 0 | – | ns | 2,3,4 |
| Output enable high to output high Z | t_{HZOE} | – | 3.0 | – | 3.4 | – | 3.8 | ns | 2,3,4 |
| Clock high to output high Z | t_{HZC} | – | 3.0 | – | 3.4 | – | 3.8 | ns | 2,3,4 |
| Output enable high to invalid output | t_{OHOE} | 0 | – | 0 | – | 0 | – | ns | |
| Clock high pulse width | t_{CH} | 2.0 | – | 2.4 | – | 2.4 | – | ns | 5 |
| Clock low pulse width | t_{CL} | 2.0 | – | 2.4 | – | 2.4 | – | ns | 5 |
| Address setup to clock high | t_{AS} | 1.4 | – | 1.5 | – | 1.5 | – | ns | 6 |
| Data setup to clock high | t_{DS} | 1.4 | – | 1.5 | – | 1.5 | – | ns | 6 |
| Write setup to clock high | t_{WS} | 1.4 | – | 1.5 | – | 1.5 | – | ns | 6,7 |
| Chip select setup to clock high | t_{CSS} | 1.4 | – | 1.5 | – | 1.5 | – | ns | 6,8 |
| Address hold from clock high | t_{AH} | 0.4 | – | 0.5 | – | 0.5 | – | ns | 6 |
| Data hold from clock high | t_{DH} | 0.4 | – | 0.5 | – | 0.5 | – | ns | 6 |
| Write hold from clock high | t_{WH} | 0.4 | – | 0.5 | – | 0.5 | – | ns | 6,7 |
| Chip select hold from clock high | t_{CSH} | 0.4 | – | 0.5 | – | 0.5 | – | ns | 6,8 |
| \overline{ADV} setup to clock high | t_{ADVS} | 1.4 | – | 1.5 | – | 1.5 | – | ns | 6 |
| \overline{ADSP} setup to clock high | t_{ADSPS} | 1.4 | – | 1.5 | – | 1.5 | – | ns | 6 |
| \overline{ADSC} setup to clock high | t_{ADSCS} | 1.4 | – | 1.5 | – | 1.5 | – | ns | 6 |
| \overline{ADV} hold from clock high | t_{ADVH} | 0.4 | – | 0.5 | – | 0.5 | – | ns | 6 |
| \overline{ADSP} hold from clock high | t_{ADSPH} | 0.4 | – | 0.5 | – | 0.5 | – | ns | 6 |
| \overline{ADSC} hold from clock high | t_{ADSCH} | 0.4 | – | 0.5 | – | 0.5 | – | ns | 6 |





¹ See “Notes” on page 16.

Snooze Mode Electrical Characteristics


| Description | Conditions | Symbol | Min | Max | Units |
|------------------------------------|------------------|------------|-----|-----|-------|
| Current during Snooze Mode | $ZZ \geq V_{IH}$ | I_{SB2} | | 80 | mA |
| ZZ active to input ignored | | t_{PDS} | 2 | | cycle |
| ZZ inactive to input sampled | | t_{PUS} | 2 | | cycle |
| ZZ active to SNOOZE current | | t_{ZZI} | | 2 | cycle |
| ZZ inactive to exit SNOOZE current | | t_{RZZI} | 0 | | |



Key to switching waveforms

 Rising input
  Falling input
  don't care
  Undefined


Timing waveform of read cycle



Note: $\dot{Y} = \text{XOR}$ when $\overline{\text{LBO}} = \text{high/no connect}$; $\dot{Y} = \text{ADD}$ when $\overline{\text{LBO}} = \text{low}$. $\overline{\text{BW}}[a:d]$ is don't care.
*Outputs are disabled within two clk cycles after DSEL command




Timing waveform of write cycle



Note: $\dot{Y} = \text{XOR}$ when $\overline{\text{LBO}} = \text{high/no connect}$; $\dot{Y} = \text{ADD}$ when $\overline{\text{LBO}} = \text{low}$.




Timing waveform of read/write cycle (ADSP Controlled; ADSC High)



Note: \dot{Y} = XOR when $\overline{LB0}$ = high/no connect; \dot{Y} = ADD when $\overline{LB0}$ = low.




Timing waveform of read/write cycle(ADSC controlled, ADSP = HIGH)





Timing waveform of power down cycle





AC test conditions

- Output load: For t_{LZC} , t_{LZOE} , t_{HZOE} , t_{HZC} , see Figure C. For all others, see Figure B.
- Input pulse level: GND to 2.5V. See Figure A.
- Input rise and fall time (measured at 0.25V and 2.25V): 2 ns. See Figure A.
- Input and output timing reference levels: 1.25V.




Figure A: Input waveform




Figure B: Output load (A)

Thevenin equivalent:




Figure C: Output load(B)

Notes

- 1 For test conditions, see “AC test conditions”, Figures A, B, and C.
- 2 This parameter is measured with output load condition in Figure C.
- 3 This parameter is sampled but not 100% tested.
- 4 t_{HZOE} is less than t_{LZOE} , and t_{HZC} is less than t_{LZC} at any given temperature and voltage.
- 5 t_{CH} is measured as high if above V_{IH} , and t_{CL} is measured as low if below V_{IL} .
- 6 This is a synchronous device. All addresses must meet the specified setup and hold times for all rising edges of CLK. All other synchronous inputs must meet the setup and hold times for all rising edges of CLK when chip is enabled.
- 7 Write refers to \overline{GWE} , \overline{BWE} , and $\overline{BW[a:d]}$.
- 8 Chip select refers to $\overline{CE0}$, $CE1$, and $\overline{CE2}$.





Package dimensions

100-pin quad flat pack (TQFP)

| | TQFP | |
|----------|--------------|-------|
| | Min | Max |
| A1 | 0.05 | 0.15 |
| A2 | 1.35 | 1.45 |
| b | 0.22 | 0.38 |
| c | 0.09 | 0.20 |
| D | 13.90 | 14.10 |
| E | 19.90 | 20.10 |
| e | 0.65 nominal | |
| Hd | 15.85 | 16.15 |
| He | 21.80 | 22.20 |
| L | 0.45 | 0.75 |
| L1 | 1.00 nominal | |
| α | 0° | 7° |

Dimensions in millimeters



www.DataSheet4U.com



Ordering information

| Package & Width | 200 MHz | 166 MHz | 133 MHz |
|-----------------|-----------------------|-----------------------|-----------------------|
| TQFP x32 | AS7C251MPFD32A-200TQC | AS7C251MPFD32A-166TQC | AS7C251MPFD32A-133TQC |
| | AS7C251MPFD32A-200TQI | AS7C251MPFD32A-166TQI | AS7C251MPFD32A-133TQI |
| TQFP x36 | AS7C251MPFD36A-200TQC | AS7C251MPFD36A-166TQC | AS7C251MPFD36A-133TQC |
| | AS7C251MPFD36A-200TQI | AS7C251MPFD36A-166TQI | AS7C251MPFD36A-133TQI |

Note:

Add suffix 'N' to the above part numbers for lead free parts (Ex AS7C251MPFD32A-200TQCN)

Part numbering guide

| AS7C | 25 | 1M | PF | D | 32/36 | A | -XXX | TQ | C/I | X |
|------|----|----|----|---|-------|---|------|----|-----|----|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |

- Alliance Semiconductor SRAM prefix
- Operating voltage: 25 = 2.5V
- Organization: 1M = 1Meg
- Pipelined mode
- Deselect: D = Double cycle deselect
- Organization: 32 = x 32; 36 = x 36
- Production version: A = first production version
- Clock speed (MHz)
- Package type: TQ = TQFP
- Operating temperature: C = commercial (0° C to 70° C); I = industrial (-40° C to 85° C)
- N = Lead Free Part



Alliance Semiconductor Corporation
2575, Augustine Drive,
Santa Clara, CA 95054
Tel: 408 - 855 - 4900
Fax: 408 - 855 - 4999
www.alsc.com

Copyright © Alliance Semiconductor
All Rights Reserved
Part Number: AS7C251MPFD32A /
AS7C251MPFD36A
Document Version: v.1.1

© Copyright 2003 Alliance Semiconductor Corporation. All rights reserved. Our three-point logo, our name and Intelliwatt are trademarks or registered trademarks of Alliance. All other brand and product names may be the trademarks of their respective companies. Alliance reserves the right to make changes to this document and its products at any time without notice. Alliance assumes no responsibility for any errors that may appear in this document. The data contained herein represents Alliance's best data and/or estimates at the time of issuance. Alliance reserves the right to change or correct this data at any time, without notice. If the product described herein is under development, significant changes to these specifications are possible. The information in this product data sheet is intended to be general descriptive information for potential customers and users, and is not intended to operate as, or provide, any guarantee or warranty to any user or customer. Alliance does not assume any responsibility or liability arising out of the application or use of any product described herein, and disclaims any express or implied warranties related to the sale and/or use of Alliance products including liability or warranties related to fitness for a particular purpose, merchantability, or infringement of any intellectual property rights, except as express agreed to in Alliance's Terms and Conditions of Sale (which are available from Alliance). All sales of Alliance products are made exclusively according to Alliance's Terms and Conditions of Sale. The purchase of products from Alliance does not convey a license under any patent rights, copyrights; mask works rights, trademarks, or any other intellectual property rights of Alliance or third parties. Alliance does not authorize its products for use as critical components in life-supporting systems where a malfunction or failure may reasonably be expected to result in significant injury to the user, and the inclusion of Alliance products in such life-supporting systems implies that the manufacturer assumes all risk of such use and agrees to indemnify Alliance against all claims arising from such use.