

AT5231/AT5231T

300mA Low Dropout Voltage Linear Regulators



Immense Advance Tech.


FEATURES

- V_{IN} Range: 2.0V to 6.0V
- Low Dropout Voltage: 0.22V (Typ)
($V_{OUT}= 3.3V, I_{OUT}= 150mA$)
- Low-ESR Ceramic Capacitor for Output Stability
- Output Current: 300mA
- High Ripple Rejection: 65dB (Typ)($f= 10kHz$)
- Excellent Line Regulation: 0.01% / V(Typ)
- Output Voltage Accuracy: $\pm 2.0\%$
- Low Supply Current: 70 μ A (Typ)
- Standby Mode: 0.01 μ A (Typ)
- Over Current Protection
- Ceramic Capacitors are Recommend to be Used with this IC: $C_{IN} = C_{OUT} = 1\mu F$
- Built-In Over Shoot Protection Circuit
- Ultra Fast Transient Response
- RoHS Compliant

APPLICATION

- Power Source for Portable Communication Equipment
- Power Source for Battery-Powered Equipment

ORDER INFORMATION



DESCRIPTION


The AT5231/AT5231T Series are CMOS-based voltage regulator ICs with high output voltage accuracy, low supply current, low ON-resistance. Each of these ICs consists of a voltage reference unit, an error amplifier, resistor-net for voltage setting, a current limit circuit and a chip enable circuit.

These ICs perform with low dropout voltage and a chip enable function (SOT-25L, SOT-343/353 and DFN1.6x1.6-6L package only). The line transient response and load transient response of the AT5231/AT5231T Series are excellent, thus these ICs are very suitable for the power supply for handheld communication equipment.

AT5231 are available in the SOT-23L, SOT-23-3L, SOT-25L, SOT-343, SOT-353, SOT-89 and DFN1.6x1.6-6L packages.

AT5231T is available in the SOT-89 package.

PIN CONFIGURATIONS (TOP VIEW)




AT5231/AT5231T

300mA Low Dropout Voltage Linear Regulators




Immense Advance Tech.

ORDER INFORMATION





PIN CONFIGURATIONS (TOP VIEW)



PIN DESCRIPTIONS

Pin Name	Pin Description
V_{IN}	Input Pin
GND	Ground Pin
EN	Chip Enable Pin, Active High
NC	No Connection
V_{OUT}	Output Pin.

TYPICAL APPLICATION CIRCUITS




AT5231/AT5231T

300mA Low Dropout Voltage Linear Regulators



Immense Advance Tech.

BLOCK DIAGRAM



* Not available in AT5231T

AT5231/AT5231T

300mA Low Dropout Voltage Linear Regulators



Immense Advance Tech.

BSOLUTE MAXIMUM RATINGS (Note 1)

Parameter		Symbol	Max Value	Unit
Power Supply Voltage		V_{IN}	-0.3 to 6.5	V
Enable Voltage		V_{EN}	-0.3 to V_{IN}	V
Maximum Junction Temperature		T_J	125	°C
Storage Temperature Range		T_{STG}	-65 to +150	°C
Lead Temperature(Soldering) 5 Sec.		T_{LEAD}	260	°C
Power Dissipation $P_D @ T_A=25^\circ\text{C}$ (Note 2)	SOT-23L	P_D	280	mW
	SOT-23-3L		280	
	SOT-25L		300	
	SOT-89		640	
	SOT-343		250	
	SOT-353		250	
Thermal Resistance Junction to Ambient	SOT-23L	Θ_{JA}	357	°C/W
	SOT-23-3L		357	
	SOT-25L (Note 3)		333	
	SOT-89		156	
	SOT-343		400	
	SOT-353		400	
Thermal Resistance Junction to Case	SOT-23L	Θ_{JC}	106.6	°C/W
	SOT-23-3L		106.6	
	SOT-25L		106.6	
	SOT-89		100	
	SOT-343(SC-70-4L)		120	
	SOT-353(SC-70-5L)		120	
ESD Rating (Human Body Model) (Note 4)		V_{ESD}	2	kV

AT5231/AT5231T

300mA Low Dropout Voltage Linear Regulators



Immense Advance Tech.

RECOMMENDED OPERATING CONDITIONS (Note 5)

Parameter	Symbol	Operation Conditions	Unit
Supply Voltage	V_{IN}	6.0	V
Enable Voltage	V_{EN}	-0.3 to V_{IN}	V
Operating Junction Temperature Range	T_J	-40 to +125	°C
Operating Ambient Temperature Range	T_{OPA}	-40 to +85	°C

Note 1: Stresses listed as the above “Absolute Maximum Ratings” may cause permanent damage to the device. These are for stress ratings. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may remain possibility to affect device reliability.

Note 2: Thermal Resistance is specified with the component mounted on a low effective thermal conductivity test board in free air at $T_A=25^{\circ}\text{C}$.

Note 3: Thermal Resistance is specified with approximately 1 square of 1 oz copper.

Note 4: Devices are ESD sensitive. Handling precaution recommended.

Note 5: The device is not guaranteed to function outside its operating conditions.

AT5231/AT5231T

300mA Low Dropout Voltage Linear Regulators



Immense Advance Tech.

ELECTRICAL CHARACTERISTICS

T_J = 25°C, unless otherwise noted

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage (Note 6)	V _{OUT}	V _{IN} =Set V _{OUT} +1V 1mA ≤ I _{OUT} ≤ 30mA	V _{OUT} x0.980		V _{OUT} x1.020	V
Output Current	I _{OUT}	V _{IN} - V _{OUT} = 1.0V	300			mA
Load Regulation (Note 6)	Reg_load	V _{IN} =Set V _{OUT} +1V 1mA ≤ I _{OUT} ≤ 150Ma V _{OUT} >2V V _{OUT} ≤2V		0.005 20	0.015 30	%/mA mV
Line Regulation (Note 6)	Reg_line	V _{OUT} > 1.7V Set V _{OUT} + 0.5V ≤ V _{IN} ≤ 6V (V _{OUT} ≤ 1.7V, 2.2V ≤ V _{IN} ≤ 6V) I _{OUT} = 30mA		0.01	0.20	%/V
Dropout Voltage (Note 6, 7)	V _{DROP}	V _{OUT} < 1.5V V _{OUT} = 1.5V V _{OUT} = 1.6V, V _{OUT} = 1.7V 1.8V ≤ V _{OUT} ≤ 2.0V 2.1V ≤ V _{OUT} ≤ 2.7V 2.8V ≤ V _{OUT} ≤ 4.8V		0.48 0.46 0.44 0.42 0.28 0.22	1.00 0.70 0.65 0.60 0.55 0.35	V
Ripple Rejection	RR	f = 10kHz Ripple 0.5Vp-p V _{OUT} > 1.7V, V _{IN} - V _{OUT} = 1.0V V _{OUT} ≤ 1.7V, V _{IN} - V _{OUT} = 1.2V I _{OUT} = 10mA		65		dB
Supply Current	I _{SS}	V _{IN} = Set V _{OUT} + 1V, I _{OUT} = 0mA		70		μA
Supply Current (Standby)	I _{standby}	V _{IN} = Set V _{OUT} + 1V, V _{EN} = GND		0.01	0.1	μA
Input Voltage	V _{IN}		2.0		6.0	V
Output Voltage Temperature Coefficient	ΔV _{OUT} /ΔT	I _{OUT} = 30mA -40°C ≤ T _J ≤ 85°C		±100		ppm/°C
Current Limit	I _{LIM}			400		mA

AT5231/AT5231T

300mA Low Dropout Voltage Linear Regulators



Immense Advance Tech.

ELECTRICAL CHARACTERISTICS (CONTINUED)

T_J =25°C, unless otherwise noted

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
EN Pull-Down Resistance	R _{PD}		0.7	2.0	8.0	MΩ
EN Input Voltage "H"	V _{ENH}		1.5		V _{IN}	V
EN Input Voltage "L"	V _{ENL}		0		0.3	V
Output Noise	en	BW 10Hz to 100kHz		30		μVrms
On Resistance for Auto-Discharge	R _{LOW}	V _{EN} =0V		60		Ω
Startup Time (Note 8)	T _{STR}	V _{IN} = V _{OUT} +1V, V _{OUT} = 2.8V, C _{IN} = C _{OUT} =1μF		30		μs

Note 6: Low duty cycle pulse testing with Kelvin connections repaired.

Note 7: Defined as the input to output differential at which the output voltage drops to 2% below the value measured at a differential of 1V.

Note 8: Time from V_{EN}= 1.5V to V_{OUT}= 95% (V_{OUT(NOM)}).

AT5231/AT5231T


300mA Low Dropout Voltage Linear Regulators




Immense Advance Tech.

TYPICAL CHARACTERISTICS


(1) Dropout Voltage VS. Temperature
AT5231/AT5231T-1.5V




(2) Dropout Voltage VS. Temperature
AT5231/AT5231T-2.5V




(3) Dropout Voltage VS. Temperature
AT5231/AT5231T-2.8V



(4) Dropout Voltage VS. Temperature
AT5231/AT5231T-3.0V



(5) Dropout Voltage VS. Temperature
AT5231/AT5231T-3.3V



AT5231/AT5231T



300mA Low Dropout Voltage Linear Regulators





Immense Advance Tech.

TYPICAL CHARACTERISTICS (CONTINUED)



(6) Supply Current VS. Input Voltage ($T_J = 25^\circ\text{C}$) (7) Supply Current VS. Input Voltage ($T_J = 25^\circ\text{C}$)
AT5231/AT5231T-1.2V AT5231/AT5231T-1.5V



(8) Supply Current VS. Input Voltage ($T_J = 25^\circ\text{C}$) (9) Supply Current VS. Input Voltage ($T_J = 25^\circ\text{C}$)
AT5231/AT5231T-2.5V AT5231/AT5231T-2.8V



(10) Supply Current VS. Input Voltage ($T_J = 25^\circ\text{C}$) (11) Supply Current VS. Input Voltage ($T_J = 25^\circ\text{C}$)
AT5231/AT5231T-3.0V AT5231/AT5231T-3.3V



AT5231/AT5231T


300mA Low Dropout Voltage Linear Regulators




Immense Advance Tech.

TYPICAL CHARACTERISTICS (CONTINUED)


(12) Output Voltage VS. Temperature
AT5231/AT5231T-1.2V




(13) Output Voltage VS. Temperature
AT5231/AT5231T-1.5V




(14) Output Voltage VS. Temperature
AT5231/AT5231T-2.5V




(15) Output Voltage VS. Temperature
AT5231/AT5231T-2.8V



(16) Output Voltage VS. Temperature
AT5231/AT5231T-3.0V



(17) Output Voltage VS. Temperature
AT5231/AT5231T-3.3V



AT5231/AT5231T


300mA Low Dropout Voltage Linear Regulators




Immense Advance Tech.

TYPICAL CHARACTERISTICS (CONTINUED)


(18) Supply Current VS. Temperature
AT5231/AT5231T-1.2V




(19) Supply Current VS. Temperature
AT5231/AT5231T-1.5V




(20) Supply Current VS. Temperature
AT5231/AT5231T-2.5V




(21) Supply Current VS. Temperature
AT5231/AT5231T-2.8V



(22) Supply Current VS. Temperature
AT5231/AT5231T-3.0V



(23) Supply Current VS. Temperature
AT5231/AT5231T-3.3V



AT5231/AT5231T


300mA Low Dropout Voltage Linear Regulators




Immense Advance Tech.

TYPICAL CHARACTERISTICS (CONTINUED)


(24) Ripple Rejection VS. Frequency
($V_{OUT}=1.5V$, $C_{OUT}=\text{Ceramic } 1.0 \mu F$)




(25) Ripple Rejection VS. Frequency
($V_{OUT}=1.8V$, $C_{OUT}=\text{Ceramic } 1.0 \mu F$)




(26) Ripple Rejection VS. Frequency
($V_{OUT}=2.5V$, $C_{OUT}=\text{Ceramic } 1.0 \mu F$)




(27) Ripple Rejection VS. Frequency
($V_{OUT}=2.8V$, $C_{OUT}=\text{Ceramic } 1.0 \mu F$)



(28) Ripple Rejection VS. Frequency
($V_{OUT}=3.0V$, $C_{OUT}=\text{Ceramic } 1.0 \mu F$)



(29) Ripple Rejection VS. Frequency
($V_{OUT}=3.3V$, $C_{OUT}=\text{Ceramic } 1.0 \mu F$)



AT5231/AT5231T

300mA Low Dropout Voltage Linear Regulators




Immense Advance Tech.

TYPICAL CHARACTERISTICS (CONTINUED)


(30) V_{EN} Turn ON/OFF

$(V_{IN} = V_{OUT} + 1V, V_{OUT} = 1.2V)$
 $CH1 = V_{EN}, CH2 = V_{OUT}, CH3 = V_{IN}$




(31) V_{EN} Turn ON/OFF

$(V_{IN} = V_{OUT} + 1V, V_{OUT} = 1.5V)$
 $CH1 = V_{EN}, CH2 = V_{OUT}, CH3 = V_{IN}$




(32) V_{EN} Turn ON/OFF

$(V_{IN} = V_{OUT} + 1V, V_{OUT} = 3.0V)$
 $CH1 = V_{EN}, CH2 = V_{OUT}, CH3 = V_{IN}$




(33) V_{EN} Turn ON/OFF

$(V_{IN} = V_{OUT} + 1V, V_{OUT} = 3.3V)$
 $CH1 = V_{EN}, CH2 = V_{OUT}, CH3 = V_{IN}$



(34) V_{EN} Turn ON/OFF


$(V_{IN} = V_{OUT} + 1V, V_{OUT} = 4.2V)$
 $CH1 = V_{EN}, CH2 = V_{OUT}, CH3 = V_{IN}$



(35) Over-Shoot Response

$(V_{IN} = 4.3V, V_{EN} = 2V, C_{IN} = C_{OUT} = \text{Ceramic } 1.0\mu F)$
 $V_{OVER-SHOOT} = 0V$

AT5231/AT5231T-3.3V



AT5231/AT5231T

300mA Low Dropout Voltage Linear Regulators



Immense Advance Tech.

TYPICAL CHARACTERISTICS (CONTINUED)


(36) Input Transient Response

($I_{OUT} = 30\text{mA}$, $C_{IN} = \text{Ceramic } 1.0 \mu\text{F}$,

$tr = tf = 5 \mu\text{s}$, $C_{OUT} = \text{Ceramic } 1.0 \mu\text{F}$)

$V_{IN} = 4.3\text{V} \sim 5.3\text{V}$, $\Delta = V_{OUT, TRANSIENT, P-P} = 8\text{mV}$

AT5231/AT5231T-3.3V




(37) Load Transient Response

($V_{IN} = 4.3\text{V}$, $C_{IN} = \text{Ceramic } 1.0 \mu\text{F}$, $tr = tf = 1 \mu\text{s}$,

$C_{OUT} = \text{Ceramic } 1.0 \mu\text{F}$)

$I_{OUT} = 50\text{mA} \sim 100\text{mA}$, $\Delta = V_{OUT, TRANSIENT, P-P} = 9.2\text{mV}$

AT5231/AT5231T-3.3V



AT5231/AT5231T


300mA Low Dropout Voltage Linear Regulators



Immense Advance Tech.

PACKAGE OUTLINE DIMENSIONS

SOT-23L PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	6°

AT5231/AT5231T


300mA Low Dropout Voltage Linear Regulators




Immense Advance Tech.

PACKAGE OUTLINE DIMENSIONS

SOT-23-3L PACKAGE OUTLINE DIMENSIONS



SOT23-3L PACKAGE FOOTPRINT (mm)



AT5231/AT5231T


300mA Low Dropout Voltage Linear Regulators




Immense Advance Tech.

PACKAGE OUTLINE DIMENSIONS

SOT-25L PACKAGE OUTLINE DIMENSIONS



SOT-25L PACKAGE FOOTPRINT (mm)




AT5231/AT5231T

300mA Low Dropout Voltage Linear Regulators




Immense Advance Tech.

PACKAGE OUTLINE DIMENSIONS SOT-343 PACKAGE OUTLINE DIMENSIONS



SOT-343 PACKAGE FOOTPRINT (mm)




AT5231/AT5231T

300mA Low Dropout Voltage Linear Regulators




Immense Advance Tech.

PACKAGE OUTLINE DIMENSIONS SOT-353 PACKAGE OUTLINE DIMENSIONS



SOT-89 PACKAGE OUTLINE DIMENSIONS



AT5231/AT5231T


300mA Low Dropout Voltage Linear Regulators



Immense Advance Tech.

PACKAGE OUTLINE DIMENSIONS

DFN1.6x1.6-6L PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.450/0.550	0.550/0.650	0.018/0.022	0.022/0.026
A1	0.000	0.050	0.000	0.002
A3	0.152REF.		0.006REF.	
D	1.550	1.650	0.061	0.065
E	1.550	1.650	0.061	0.065
E1	0.550	0.650	0.022	0.026
D1	0.950	1.050	0.037	0.041
k	0.200MIN.		0.008REF.	
b	0.200	0.300	0.008	0.012
e	0.500BSC.		0.020BSC.	
L	0.164	0.316	0.006	0.012

Note :

Information provided by IAT is believed to be accurate and reliable. However, we cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in an IAT product; nor for any infringement of patents or other rights of third parties that may result from its use. We reserve the right to change the circuitry and specifications without notice.

Life Support Policy: IAT does not authorize any IAT product for use in life support devices and/or systems. Life support devices or systems are devices or systems which, (I) are intended for surgical implant into the body or (II) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user. Typical numbers are at 25°C and represent the most likely norm.